

GIGABYTE B650 GAMING X AX Motherboard - Supports AMD Series 7000 CPUs, 8+2+2 Phases Digital VRM, up to 8000MHz DDR5 (OC), 1xPCIe 5.0+2xPCIe 4.0 x4 M.2, Wi-Fi 6E, GbE LAN, USB 3.2 Gen 2x2



Brand : GIGABYTE

Product code: B650 GAMING X AX

Product name : B650 GAMING X AX Motherboard - Supports AMD Series 7000 CPUs, 8+2+2 Phases Digital VRM, up to 8000MHz DDR5 (OC), 1xPCIe 5.0+2xPCIe 4.0 x4 M.2, Wi-Fi 6E, GbE LAN, USB 3.2 Gen 2x2

ATX, Socket AM5, AMD B650 chipset, 4x DDR5 DIMM, Wi-Fi 6E, AMI UEFI BIOS

[GIGABYTE B650 GAMING X AX Motherboard - Supports AMD Series 7000 CPUs, 8+2+2 Phases Digital VRM, up to 8000MHz DDR5 \(OC\), 1xPCIe 5.0+2xPCIe 4.0 x4 M.2, Wi-Fi 6E, GbE LAN, USB 3.2 Gen 2x2:](#)

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge technology.



Processor		Rear panel I/O ports	
Processor manufacturer *	AMD	USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1
Processor socket *	Socket AM5	Ethernet LAN (RJ-45) ports *	1
Compatible processor series *	AMD Ryzen 7000 Series	HDMI ports quantity *	1
Supported processor sockets	Socket AM5	HDMI version	2.1
Maximum internal memory supported by processor	192 GB	DisplayPorts quantity	1
Memory		DisplayPort version	1.4
Supported memory types *	DDR5-SDRAM	Headphone outputs	3
Number of memory slots *	4	Microphone in	✓
Memory slots type	DIMM	WiFi-AP antenna jack	2
Memory channels	Dual-channel	USB connector type	USB Type-A, USB Type-C
ECC compatibility	Non-ECC	Network	
Supported memory clock speeds	4400,4800,5200,5600,6000,6200,6400,6600,6800,7000,7200,7600,7800,8000 MHz	Ethernet LAN	✓
Supported memory clock speed (max)	8000 MHz	Ethernet interface type	2.5 Gigabit Ethernet
Maximum internal memory *	192 GB	Wi-Fi *	✓
Supported memory module capacities	1GB, 2GB, 4GB, 8GB, 12GB, 16GB, 32GB, 48GB	Top Wi-Fi standard	Wi-Fi 6E (802.11ax)
Unbuffered memory	✓	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)
Storage controllers		WLAN controller model	Realtek RTL8852CE
Supported storage drive types	HDD & SSD	Bluetooth	✓
Supported storage drive interfaces *	M.2, PCI Express 4.0, SATA III	Bluetooth version	5.3
Number of HDDs supported	4	Features	
Number of storage drives supported	7	Motherboard chipset *	AMD B650
RAID support	✓	Audio output channels *	7.1 channels
RAID levels	0, 1, 10	Product colour	Brown
Graphics		PC health monitoring	Fan, Temperature, Voltage, Water cooling
Parallel processing technology support *	Not supported	Component for *	PC
On-board graphics card	✗	Motherboard form factor *	ATX
Maximum resolution	4096 x 2160 pixels	Motherboard chipset family *	AMD
HDCP	✓	Windows operating systems supported	Windows 10 x64, Windows 11 x64
DirectX version	12.0		
Internal I/O			
USB 2.0 connectors *	2		


Internal I/O		Expansion slots	
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	PCI Express x16 slots	3
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	1	Number of M.2 (M) slots	3
Number of SATA III connectors *	4	BIOS	
Total number of SATA connectors	4	BIOS type *	UEFI AMI
Front panel audio connector	✓	BIOS memory size	256 Mbit
Front panel connector	✓	ACPI version	5.0
ATX Power connector (24-pin)	✓	Clear CMOS jumper	✓
CPU fan connector	✓	Desktop Management Interface (DMI) version	2.7
EPS power connector (8-pin)	✓	System Management BIOS (SMBIOS) version	2.7
TPM connector	✓	Logistics data	
Serial port headers	1	Country of origin	China
12V power connector	✓	Products per shipping (inner) case	1 pc(s)
RGB LED pin header	✓	Battery	
Rear panel I/O ports		Battery weight	3 g
USB 2.0 ports quantity *	3	Lithium weight per battery	0.07 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3	Number of battery cells	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	1	Battery technology	Lithium-Manganese Dioxide (LiMnO2)
		Battery type	CR2032
		Packaging data	
		Package width	335 mm
		Package depth	270 mm
		Package height	80 mm
		Package weight	2.2 kg
		Weight & dimensions	
		Height	35 mm
		Packaging content	
		Cables included	SATA
		Batteries included	✓
		Technical details	
		Warranty period	3 year(s)



4719331849849



0889523034156



889523034156

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.