

## Brother QL-700 label printer Direct thermal 300 x 300 DPI 150 mm/sec DK

Brand : Brother

Product code: QL-700

Product name : QL-700

- Prints cost-effective, pre-sized labels for common office uses such as file folders, envelopes, discs, banners - even packages

- Ultra-fast printing up to 93 labels per minute‡

- Also prints on continuous paper and tape rolls for banners and signs up to 3 ft. long

- Print postage from your desktop – print the exact postage you need, when you need it, with <code>pbSmartPostage</code>  $\$ 

- High-resolution printing (up to 300 x 600 dpi), for crisp text and graphics

- Auto cutter provides precise cuts for printing 1 or multiple labels at a time

- Convenient, drop-in rolls. No ink or toner needed

- "Plug & Label" feature lets you create and print labels without installing software‡

- "Label Collection" feature provides beautiful, pre-designed labels and banners with commonly-used text

High-speed, Professional Label Printer, AutoCutter, 300 x 600 dpi, 150 mm/sec, True Type, USB






Printing		Weight & dimensions	
Print technology * Maximum resolution * Print speed * Maximum printing width *	n resolution * 300 x 300 DPI ed * 150 mm/sec n printing width * 6.2 cm n print height 5.9 cm printing √	Width Depth Height Weight	128 mm 221 mm 153 mm 1.1 kg
Maximum print height Vertical printing Retated printing		Packaging data Quantity per pack 1	1 pc(s)
Rotated printing Paper handling	•	Package dimensions (WxDxH) Package width	182 x 262 x 233 mm 260.4 mm
Maximum label width Maximum label length	6.2 cm 1 m	Package depth Package height Package weight	184.2 mm 234.9 mm 2 kg
Ports & interfaces Ethernet LAN *	×	Packaging content	2 kg
Wi-Fi * PC connected Performance	x v	Bundled software	Software, USB Cable, Power Cord, Quick Setup Guide, Documentation, Starter rolls: DK-1201 Die-cut Standard Address Labels (100
Built-in barcodes	CODABAR (NW-7), EAN128, EAN13, EAN8, Interleaved 2/5, PDF417, POSTNET, UPC-A, UPC-E		labels), plus DK-2205 2.4" Continuous Length Paper Tape (26.2 ft.)
Tape type	DK	Logistics data	
Tape cutting	Automatic	Harmonized System (HS) code	84433210
Design		Master (outer) case width	274 mm
Product colour *	Black, White	Master (outer) case length	555 mm
Power		Other features	120 221 152
AC input voltage AC input frequency AC adapter output current	120 V 60 Hz 1.7 A	Dimensions (WxDxH) Network ready Number of label formats Quantity outer carton	128 x 221 x 153 mm 22 3 pc(s)
System requirements			
Mac compatibility	1		






















Disclaimes. The Information published here (this "Information") is based on sources that can be considered reliable, twoically the manufacturar, but this Information is provided "AS IS) and without guarantee of correctness or completeness. The Information is or v indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party desides to a usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date