## PHILIPS

## Philips 49B2U6903CH/00 computer monitor 124.5 cm (49") 5120 x 1440 pixels Dual QHD LCD Grey

**Brand**: Philips Product code: 49B2U6903CH/00

Product name: 49B2U6903CH/00

Curved Business monitor 49B2U6903CH 32:9 SuperWide Thunderbolt™ 4 monitor

Philips 49B2U6903CH/00 computer monitor 124.5 cm (49") 5120 x 1440 pixels Dual QHD LCD Grey:

This Philips Thunderbolt™ 4 monitor is designed with everything you need for a collaborative remote workspace. Its webcam fashions features such as auto-framing and a busy light for an unmatched video conferencing experience.

Philips 49B2U6903CH/00. Display diagonal: 124.5 cm (49"), Display resolution:  $5120 \times 1440 \text{ pixels}$ , HD type: Dual QHD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal:  $178^\circ$ , Viewing angle, vertical:  $178^\circ$ . Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Grey







Display		Ports & interfaces	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * LED backlight Backlight type Display brightness (peak) Display brightness (typical) Response time * Anti-glare screen Screen shape * Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch	124.5 cm (49") 5120 x 1440 pixels Dual QHD 32:9 LCD VA  ✓ W-LED 500 cd/m² 450 cd/m² 4 ms  ✓ Curved 3000:1 80000000:1 100 Hz 178° 1.07 billion colours 0.2328 x 0.2328 mm	HDMI version DisplayPorts quantity DisplayPort version Thunderbolt 4 ports quantity Audio output HDCP HDCP version  Ergonomics VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD)	2.0 1 1.4 1 1.4 1  1.4/2.2   1.4/2.2   100 x 100 mm  Kensington  15 cm  -30 - 30°  -5 - 20°  Simplified Chinese, Traditional
Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal	109 ppi 30 - 200 kHz 48 - 120 Hz 119.2 cm	On Screen Display (OSD) languages	Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Turkish, Ukrainian
Viewable size, vertical	33.5 cm	Power	
High Dynamic Range (HDR) supported	✓	Energy efficiency class (SDR) *	F
High Dynamic Range (HDR) technology DDC/CI	High Dynamic Range (HDR) 400	Power consumption (typical) * Power consumption (standby) *	41.85 W 0.5 W
DDC/CI	4	Power consumption (PowerSave)	37.5 W

Display		Power	
Haze rate Surface hardness NTSC coverage (typical)	25% 3H 97%	AC input voltage AC input frequency Power supply type	100 - 240 V 50/60 Hz Internal
Performance		Operational conditions	
VESA Adaptive Sync support	✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 20 - 80% 0 - 3658 m 3658 - 12192 m
Multimedia			
Number of speakers RMS rated power Built-in speaker(s) * Megapixel (approx.)	2 10 W ✓ 5 MP		
		Weight & dimensions	
Built-in microphone Built-in camera *	4	Width (with stand) Depth (with stand)	1193 mm 268 mm
Design		Height (with stand)	586 mm
Market positioning * Product colour *	Business Grey	Weight (with stand) Width (without stand) Depth (without stand)	15.5 kg 1193 mm 164 mm
Ports & interfaces		Height (without stand)	373 mm
Built-in USB hub *	✓	Weight (without stand)	11.8 kg
USB hub version	3.2 Gen 2 (3.1 Gen 2)	Packaging data	
Number of USB Type-C upstream ports quantity	1	Package width	1290 mm
USB Type-A downstream ports quantity	4	Package depth Package height	300 mm 475 mm
USB Type-C downstream ports	2 100 W 2	Package weight	19.5 kg
quantity USB Power Delivery USB Power Delivery up to HDMI * HDMI ports quantity		Packaging content	
		Stand included	✓
		Cables included	DisplayPort, HDMI, Power, Thunderbolt
		Sustainability	
		Doesn't contain	Mercury, PVC/BFR
		Other features	
		HBR3 support	✓



8712581804763

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.