



Manhattan HDMI Cable with Ethernet, 4K@60Hz (Premium High Speed), 1.8m, Male to Male, Black, Equivalent to HDMM2MP (except 20cm shorter), Ultra HD 4k x 2k, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag

Brand : Manhattan

Product code: 355346

Product name : HDMI Cable with Ethernet, 4K@60Hz (Premium High Speed), 1.8m, Male to Male, Black, Equivalent to HDMM2MP (except 20cm shorter), Ultra HD 4k x 2k, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag

- Premium certified HDMI cable
- Supports 4K@60Hz Ultra High Definition (UHD) resolution, 3D video and Deep colour
- Supports 4:4:4 Chroma Subsampling and HDR
- Up to 18 Gbps bandwidth
- Supports HDMI Ethernet Channel (HEC)
- High-speed Ethernet, bi-directional networking up to 100 Mbps
- Supports HDMI Audio Return Channel (ARC)
- ARC to transmit TV's audio through your system; no need for additional cable
- Compliant with Premium High Speed HDMI with Ethernet specifications
- Double shielded to reduce EMI and other interference sources
- Compatible with any HDMI device, such as a Blu-ray player, game console, stereo, PC and more
- Lifetime warranty

HDMI Cable with Ethernet, 4K, Male to Male, 1.8m, Premium, 4K@60Hz UHD, HEC, ARC, 3D, 18 Gbps, Shielded, Black



| Features | | Features | |
|--------------------------------|------------------------|-----------------------------------|--------------------------|
| Cable length * | 1.8 m | Maximum refresh rate | 60 Hz |
| Connector 1 * | HDMI Type A (Standard) | AWG wire size | 30 |
| Connector 2 * | HDMI Type A (Standard) | Connector contacts plating * | Gold |
| Connector 1 gender * | Male | Cable jacket material | Polyvinyl chloride (PVC) |
| Connector 2 gender * | Male | Magnetically shielded | ✓ |
| Connector 1 form factor | Straight | Certification | ISO 9002 |
| Connector 2 form factor | Straight | Quantity per pack * | 1 pc(s) |
| Product colour * | Black | Operational conditions | |
| 3D | ✓ | Operating temperature (T-T) | 0 - 40 °C |
| Supported graphics resolutions | 3840 x 2160 | Storage temperature (T-T) | -20 - 60 °C |
| Audio Return Channel (ARC) | ✓ | Operating relative humidity (H-H) | 0 - 96% |
| HDMI Ethernet channel | ✓ | Weight & dimensions | |
| Data transfer rate | 18 Gbit/s | Weight | 104 g |
| Bandwidth | 600 MHz | Logistics data | |
| | | Harmonized System (HS) code | 84733080 |



0766623355346



766623355346

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date