

Brother RJ3230BL label printer Direct thermal 203 x 203 DPI 127 mm/sec Wireless Wi-Fi Bluetooth

Brand : Brother Product code: RJ-3230BL

Product name: RJ3230BL

- Prints receipts and labels
- Weight 807g
- Print width of up to 72mm
- Print speeds up to 5ips (127 mm/sec)
- USB and Bluetooth connectivity
- Drop tested to 2m
- IP54 certification
- 203dpi print resolution
- Raster, ESC/P, P-Touch Template, ZPL2
- CPCL supported

Prints receipts and labels, Bluetooth v 5.0, USB, Android, iOS, 203dpi, 807g

Brother RJ3230BL label printer Direct thermal 203 x 203 DPI 127 mm/sec Wireless Wi-Fi Bluetooth:

The RJ-3230BL mobile printer offers a fast print solution, designed to endure relentless usage.

With a range of accessories, you can wear the Bluetooth printer on-body or mount on a surface to suit your business needs.

This compact and portable printer is ready to support busy workforces' labelling and receipt requirements.

Brother RJ3230BL. Print technology: Direct thermal, Maximum resolution: 203 x 203 DPI, Print speed: 127 mm/sec. Connectivity technology: Wireless. Battery technology: Lithium Polymer (LiPo). Product colour: Black





Printing		Design	
Maximum resolution * Print speed * Maximum printing width *	Direct thermal 203 x 203 DPI 127 mm/sec 7.2 cm 3 m	Product colour *	Black
		Power	
		Battery technology Battery capacity	Lithium Polymer (LiPo) 3000 mAh
Ports & interfaces		System requirements	
Connectivity technology *	Wireless	Windows operating systems supported	Windows 10, Windows 7, Windows 8.1
Ethernet LAN *	X	Mobile operating systems supported	Android, iOS
Wi-Fi * Bluetooth		Weight & dimensions	
Bluetooth version	5.0	Width	117 mm
USB port *	✓	Depth	180 mm
Performance		Height Weight	77 mm 807 q
Page description languages	CPCL-native, ESC P, Raster_P, ZPL II AZTECCODE, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, Data Matrix, EAN13, EAN8, GS1 DataBar, GS1-128, ITF, MSI, MaxiCode, Micro QR Code, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E	Logistics data	
Built-in barcodes		Harmonized System (HS) code	84433210
Drop Stop function	✓		





012502664116

0012502664116



4977766814867

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.