PHILIPS

Philips 86BDL3511Q/00 Public Display Digital signage flat panel 2.18 m (86") IPS 400 cd/m 2 4K Ultra HD Black

Brand : Philips Product code: 86BDL3511Q/00

Product name: 86BDL3511Q/00 Public Display

86BDL3511Q - 86", Ultra HD, Direct LED Backlight

Philips 86BDL3511Q/00 Public Display. Product design: Digital signage flat panel. Display diagonal: 2.18 m (86"), Display technology: IPS, Display resolution: $3840 \times 2160 \text{ pixels}$, Display brightness: 400 cd/m^2 ,

HD type: 4K Ultra HD. Product colour: Black





Display		Performance	
Display diagonal * 2.18 m (Display technology * 1PS 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	3840 x 2160 pixels 400 cd/m² 4K Ultra HD X 16:9	Purpose * On Screen Display (OSD) Number of OSD languages On Screen Display (OSD) languages	Universal ✓ 12 Arabic, Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Polish, Russian, Turkish
		Power	
	1200:1 500000:1 178°	Power consumption (typical) * Power consumption (standby) * Energy efficiency class (SDR) Energy consumption (SDR) per 1000 hours AC input voltage AC input frequency Energy efficiency scale	360 W 0.5 W G 355 kWh 100-240 50 - 60 Hz A to G
Ports & interfaces		Computer system	
HDMI ports quantity * HDMI version DVI port * DVI-I ports quantity	3 2.0 ✓ 1	Video formats supported Audio formats supported Image formats supported	H.264, M-JPEG, WMV3 AAC, HE-AAC, WMA BMP, JPEG, PNG
USB port *	· ✓	Weight & dimensions	
USB ports quantity USB version Ethernet LAN * Ethernet LAN (RJ-45) ports	2 2.0 ✓	Display width Display depth Display height Display weight	1929 mm 69.5 mm 1100 mm 49.5 kg
RS-232C	1	Packaging content	
Infrared data port OPS module slot	1	Cables included	AC, RS-232
Audio	•	Operational conditions	
Built-in speaker(s) * Number of built-in speakers RMS rated power	✓ 2 10 W	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 20 - 80% -20 - 60 °C 5 - 95%
Design		Certificates	
Product design * Placement supported * Product colour *	Digital signage flat panel Indoor Black	Certification	CEosd FCC, Class A CB BSMI VCCI CU ETL EMF PSB
VESA mounting *	Jidek ✓	Logistics data	
Panel mounting interface Bezel width (top)	600 x 400 mm 1.55 cm	Harmonized System (HS) code	85285210





8712581778620

0685417580484



685417580484

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.