

ASUS ROG THOR 1200W Platinum II power supply unit 24-pin ATX ATX Grey

Brand : ASUS

Product code: 90YE00L0-B0NA00

Product name : ROG THOR 1200W Platinum II



- Lambda A++ Certification confirms the latest Thor wields menacing power in absolute stealth
 - ROG heatsinks cover critical components, delivering lower temperatures and reduced noise
 - A 135mm Axial-tech fan with PWM control delivers lower noise and keeps thermals in check
 - Built with 100% Japanese capacitors and other premium components to achieve 80 Plus Platinum Certification
 - OLED display monitors power draw in real time
 - Aura Sync compatibility lets you customize and sync lighting effects with other compatible hardware
- ROG Thor 1200W Platinum II is the quietest PSU in its class.

ASUS ROG THOR 1200W Platinum II. Total power: 1200 W, AC input voltage: 100 - 240 V, Maximum input current (@220V): 100 A. Motherboard power connector: 24-pin ATX, Cabling type: Fully-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Platinum. Product colour: Grey, Cooling type: Active, Number of fans: 1 fan(s). Cables included: AC



Power		Ports & interfaces	
Total power *	1200 W	Cabling type	Fully-Modular
AC input voltage *	100 - 240 V	Performance	
Maximum input current (@220V)	100 A	80 PLUS certification *	80 PLUS Platinum
Combined power (+3.3V)	125 W	Purpose *	PC
Combined power (+12V)	1200 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5V)	125 W	Design	
Combined power (-12V)	3.6 W	Product colour	Grey
Combined power (+5Vsb)	15 W	Cooling type	Active
Max output current (+3.3V)	25 A	Number of fans	1 fan(s)
Max output current (+12V)	100 A	Illumination	✓
Max output current (+5V)	25 A	On/off switch	✓
Max output current (-12V)	0.3 A	Packaging content	
Max output current (+5Vsb)	3 A	Cables included	AC
Power protection features	Over power, Over voltage, Overcharge, Short circuit, Under voltage	Weight & dimensions	
Ports & interfaces		Width	190 mm
Motherboard power connector *	24-pin ATX	Depth	150 mm
Number of SATA power connectors	12	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	6	Weight	2.37 kg
PCI Express power connectors (6+2 pin)	8	Packaging data	
CPU power connector (4+4 pin)	✓	Package width	378 mm
ATX Power connector (24-pin)	✓	Package depth	240 mm
		Package height	130 mm
		Package weight	4.78 kg
		Package type	Box
		Logistics data	
		Harmonized System (HS) code	84733020



4711081236061

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date