



CompactFlash Cards CompactFlash 133

Fast, reliable, and high-capacity. With consistent performance and vast storage capacity, Transcend's CompactFlash 133 cards are the perfect match for enthusiast and prosumer level DSLR cameras and camcorders. Additionally, the top-tier MLC NAND flash chips inside are durable and reliable.



Outstanding transfer performance

Transcend's CompactFlash 133 cards operate in Ultra DMA (UDMA) transfer mode 4. An entry-level DSLR camera equipped with a 133x CF card can respond more quickly during fast-action burst mode shooting, and store large images in RAW format.



Excellent compatibility

Transcend's CompactFlash 133 cards are developed to work across a wide range of CompactFlash compatible devices, including entry-level DSLRs, hybrid cameras and Full HD camcorders. When paired with a high-end card reader such as Transcend's USB 3.1 Gen 1 RDF8, the CompactFlash 133 cards can achieve optimum read/write speed and provide seamless data transfer.



Durable and Reliable

Transcend's CompactFlash 133 memory cards are manufactured with top-tier MLC NAND flash memory, making them durable and reliable. Featuring built-in ECC to detect and correct transfer errors, the CompactFlash 133 memory cards deliver reliability as well as data integrity.



CompactFlash Cards

CompactFlash 133

Features

- Supports up to Ultra DMA transfer mode 4
- Up to 32GB storage capacity
- Up to 50 MB/s read; 20 MB/s write
- MLC NAND flash memory
- Ideal for entry-level DSLRs
- Exclusive RecoverRx software



RecoverRx software

Transcend offers RecoverRx software, a data recovery utility that allows you to search deep within a storage device for traces of erased files including digital photos, documents, music and videos.

Specifications

Appearance

| | |
|-------------------|--|
| Dimensions (Max.) | 42.8 mm x 36.4 mm x 3.3 mm (1.69" x 1.43" x 0.13") |
|-------------------|--|

| | |
|---------------|-----------------|
| Weight (Max.) | 11.4 g (0.4 oz) |
|---------------|-----------------|

Storage

| | |
|------------|----------------|
| Flash Type | MLC NAND flash |
|------------|----------------|

| | |
|----------|---------------------------------|
| Capacity | 1 GB/2 GB/4 GB/8 GB/16 GB/32 GB |
|----------|---------------------------------|

Operating Environment

| | |
|-----------------------|------------------------------|
| Operating Temperature | -25°C (-13°F) ~ 85°C (185°F) |
|-----------------------|------------------------------|

| | |
|-------------------|-----------|
| Operating Voltage | 3.3V ~ 5V |
|-------------------|-----------|

Performance

| | |
|-------------------|---------|
| Read Speed (Max.) | 50 MB/s |
|-------------------|---------|

| | |
|--------------------|---------|
| Write Speed (Max.) | 20 MB/s |
|--------------------|---------|

| | |
|--------------------------|--------|
| Insertion/Removal Cycles | 10,000 |
|--------------------------|--------|

Note

Speed may vary due to host hardware, software, usage, and storage capacity.

Warranty

| | |
|-------------|----------------|
| Certificate | CE/FCC/RCM/EAC |
|-------------|----------------|

| | |
|----------|----------------------------|
| Warranty | Five-year Limited Warranty |
|----------|----------------------------|

Ordering Information

| | |
|-----|-----------|
| 1GB | TS1GCF133 |
|-----|-----------|

| | |
|-----|-----------|
| 2GB | TS2GCF133 |
|-----|-----------|

| | |
|-----|-----------|
| 4GB | TS4GCF133 |
|-----|-----------|

| | |
|-----|-----------|
| 8GB | TS8GCF133 |
|-----|-----------|

| | |
|------|------------|
| 16GB | TS16GCF133 |
|------|------------|

| | |
|------|------------|
| 32GB | TS32GCF133 |
|------|------------|