

## **PC Hard Drives**

## High Capacity, Proven Reliability

WD expands their award-winning desktop and mobile storage lineup with WD Blue PC hard drives. Extensively tested and built to WD's high standards, WD Blue offers a wide variety of capacities - ranging from 250 GB to the massive 6 TB – in both desktop and mobile models. Drive WD Blue with con dence – our colors never fade.



INTERFACE

FORM FACTOR

**ROTATIONAL SPEED** 

CAPACITIES

SATA 6 Gb/s

WD40EZRZ

WD30F7R7

3.5-inch

7200 RPM Class and 5400 RPM Class

250 GB to 6 TB

**MODEL NUMBERS** 

WD60EZRZ WD20EZRZ WD50EZRZ WD10EZRZ

WD10EZRZ WD10EZRZ WD10EZEX WD7500AZEX WD5000AZRZ WD5000AZLX WD5000AAKX WD3200AAKX WD2500AAKX

# Product Features

### Storage Capacity Up to 6 TB

Boost your PC storage with WD Blue drives, the brand designed speci cally for desktop and all-in-one PCs. The WD Blue family now delivers data storage capacities up to 6 TB.

### Improve PC Performance

Pair a larger capacity drive with an SSD to give your desktop a performance and storage boost. The SSD maximizes speed of data access, while the WD Blue drive stores up to 6 TB of movies, games, les, applications and more.

### Upgrade and Backup with Ease

WD hard drives come with free access to WD Acronis True Image. Backup and restore functions make it easy to save and retrieve your personal data without the need to reinstall the OS.

#### Trust in WD

Customers around the world know that WD's reliability is legendary. Every WD Blue drive is designed, tested and built to last, and each ships with a 2-year limited warranty.

### Future-Proof Your Storage

With better technology comes bigger storage needs. Cameras that record ultra-high de nition video at 4K resolution at 30 frames per second require a ton of storage. Handling all that media is a snap with our 6 TB drive.

#### NoTouch Ramp Load Technology

Safely positions the recording head off the disk surface to protect your data.

#### IntelliSeek

Calculates optimum seek speeds to lower power consumption, noise and vibration.

## **Applications**

- WD Blue storage is tested and recommended for use in desktop and All-in-One PCs, notebooks, and external enclosures.
- Desktop / Consumer RAID Environments WD Blue PC Hard Drives are tested and recommended for use in consumer-type RAID applications (RAID 0 and RAID 1).\*
  - Business Critical RAID Environments WD Blue PC Hard Drives are not recommended for and are not warranted for use in RAID environments utilizing Enterprise HBAs and/or expanders and in multi-bay chassis, as they are not designed for, nor tested in, these speci c types of RAID applications. For all Business Critical RAID applications, please consider WD's Enterprise Hard Drives that are speci cally designed with RAID-speci c, time-limited error recovery (TLER), are tested extensively in 24x7 RAID applications, and include features like enhanced RAFF technology and thermal extended burn-in testing.

### The WD Advantage

WD puts our products through extensive Functional Integrity Testing (F.I.T.) prior to any product launch. This testing ensures our products consistently meet the highest quality and reliability standards of the WD brand. WD also has a detailed Knowledge Base with more than 1,000 helpful articles as well as helpful software and utilities. Our customer support lines have longer operational hours to ensure you get the help you need when you need it. Our toll-free customer support lines are here to help or you can access our WD Support site for additional details.



Speci cations	6 TB	5 TB	4 TB	3 TB	2 TB
Model number <sup>1</sup>	WD60EZRZ	WD50EZRZ	WD40EZRZ	WD30EZRZ	WD20EZRZ
Interface	SATA 6 Gb/s				
Formatted capacity <sup>2</sup>	6 TB	5 TB	4 TB	3 TB	2 TB
Advanced Format (AF)	Yes	Yes	Yes	Yes	Yes
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
RoHS compliant <sup>3</sup>	Yes	Yes	Yes	Yes	Yes
Performance					
Data transfer rate (max) Buffer to host Host to/from drive (sustained)	6 Gb/s 175 MB/s	6 Gb/s 170 MB/s	6 Gb/s 150 MB/s	6 Gb/s 147 MB/s	6 Gb/s 147 MB/s
Cache (MB)	64	64	64	64	64
Rotational speed (RPM)	5400 RPM Class				
Reliability/Data Integrity	5 TOO THE WE OLGSS	5 TOO THE WE CHASS	0 TOO THE WE CHASS	0 100 111 111 01033	0 100 Ttl W Oldss
Load/unload cycles <sup>4</sup>	300.000	300.000	300.000	300.000	300.000
Non-recoverable read errors per bits read	<1 in 10 <sup>14</sup>				
Limited warranty (years) <sup>5</sup>	2	2	2	2	2
Power Management					
12VDC ±10% (A, peak)	1.75	1.75	1.75	1.73	1.73
Average power requirements (W)	11.70	1170	1170	1170	1170
Read/Write	5.3	5.3	5.3	4.1	4.1
Idle	3.4	3.4	3.4	3.0	3.0
Standby/Sleep	0.4	0.4	0.4	0.4	0.4
Environmental Speci cations <sup>6</sup>					
Temperature (°C)					
Operating	0 to 60				
Non-operating	-40 to 70				
Shock (Gs) Operating (2 ms, write) Operating (2 ms, read) Non-operating (2 ms)	30 65 250	30 65 250	30 65 250	30 65 250	30 65 250
Acoustics (dBA) <sup>7</sup>					
Idle	25	25	25	23	23
Seek (average)	28	28	28	27	27
Physical Dimensions					
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.65/0.75	1.65/0.75	1.50/0.68	1.40/0.64	1.32/0.60

 $<sup>^{\,1}\,</sup>$  Not all products may be available in all regions of the world.

As used for storage capacity one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one billion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (GB) = 0.048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second, and gigabit per second. Gib/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA speci cation published by the SATA-IO organization as of the date of this speci cation sheet. Visit www. sata-io.org for details.

<sup>3</sup> WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

<sup>&</sup>lt;sup>4</sup> Controlled unload at ambient condition.

 $<sup>^{\,\,5}\,</sup>$  The term of the limited warranty may vary by region. Visit support.wd.com/warranty for details.

<sup>&</sup>lt;sup>6</sup> No non-recoverable errors during operating tests or after non-operating tests.

<sup>7</sup> Sound power level.



Speci cations	1 TB	1 TB	750 GB	500 GB	500 GB
Model number <sup>1</sup>	WD10EZRZ	WD10EZEX	WD7500AZEX	WD5000AZRZ	WD5000AAKX
Interface	SATA 6 Gb/s				
Formatted capacity <sup>2</sup>	1 TB	1,000,204 MB	750,156 MB	500 GB	500,107 MB
Advanced Format (AF)	Yes	Yes	Yes	Yes	No
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
RoHS compliant <sup>3</sup>	Yes	Yes	Yes	Yes	Yes
Performance					
Data transfer rate (max)  Buffer to host  Host to/from drive (sustained)	6 Gb/s 150 MB/s	6 Gb/s 150 MB/s	6 Gb/s 150 MB/s	6 Gb/s 150 MB/s	6 Gb/s 126 MB/s
Cache (MB)	64	64	64	64	16
Rotational speed (RPM)	5400 RPM Class	7200 RPM Class	7200 RPM Class	5400 RPM Class	7200 RPM Class
Reliability/Data Integrity					
Load/unload cycles <sup>4</sup>	300,000	300.000	300.000	300.000	300.000
Non-recoverable read errors per bits read	<1 in 10 <sup>14</sup>				
Limited warranty (years) <sup>5</sup>	2	2	2	2	2
Power Management					
12VDC ±10% (A, peak)	1.2	2.5	2.5	1.2	1.77
Average power requirements (W) Read/Write Idle Standby/Sleep	3.3 2.5 0.4	6.8 6.1 1.2	6.8 6.1 1.2	3.3 2.5 0.4	6.0 5.6 0.9
Environmental Speci cations <sup>6</sup>					
Temperature (°C) Operating Non-operating	0 to 60 -40 to 70				
Shock (Gs) Operating (2 ms, write) Operating (2 ms, read) Non-operating (2 ms)	30 65 350	30 65 350	30 65 350	30 65 350	30 65 350
Acoustics (dBA) <sup>7</sup> Idle Seek (average)	21 24	29 30	29 30	21 22	29 30
Physical Dimensions					
Height (in./mm, max)	1.028/26.1	1.028/25.4	1.028/25.4	1.028/26.1	1.028/25.4
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	0.99/0.45	0.99/0.45	0.99/0.45	0.99/0.45	0.95/0.43

<sup>1</sup> Not all products may be available in all regions of the world

As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one billion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second. (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA speci cation published by the SATA-IO organization as of the date of this speci cation sheet. Visit www. sata-io.org for details.

<sup>3</sup> WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

Controlled unload at ambient condition.

 $<sup>^{\,\,5}\,</sup>$  The term of the limited warranty may vary by region. Visit support.wd.com/warranty for details.

 $<sup>^{\,\,6}\,</sup>$  No non-recoverable errors during operating tests or after non-operating tests.

<sup>7</sup> Sound power level.



Speci cations	500 GB	320 GB	250 GB
Model number <sup>1</sup>	WD5000AZLX	WD3200AAKX	WD2500AAKX
Interface	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s
Formatted capacity <sup>2</sup>	500,107 MB	320,072 MB	250,059 MB
Advanced Format (AF)	Yes	No	No
Form factor	3.5-inch	3.5-inch	3.5-inch
RoHS compliant <sup>3</sup>	Yes	Yes	Yes
Performance			
Data transfer rate (max) Buffer to host Host to/from drive (sustained)	6 Gb/s 150 MB/s	3 Gb/s 126 MB/s	6 Gb/s 126 MB/s
Cache (MB)	32	16	16
Rotational speed (RPM)	7200 RPM Class	7200 RPM Class	7200 RPM Class
Reliability/Data Integrity			
Load/unload cycles <sup>4</sup>	300,000	300,000	300,000
Non-recoverable read errors per bits read	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>	<1 in 10 <sup>14</sup>
Limited warranty (years) <sup>5</sup>	2	2	2
Power Management			
12VDC ±10% (A, peak)	2	1.77	1.77
Average power requirements (W) Read/Write Idle Standby/Sleep	6.8 6.1 1.2	6.0 5.6 0.9	5.3 4.9 0.7
Environmental Speci cations <sup>6</sup>			
Temperature (°C) Operating Non-operating	0 to 60 -40 to 70	0 to 60 -40 to 70	0 to 60 -40 to 70
Shock (Gs) Operating (2 ms, write) Operating (2 ms, read) Non-operating (2 ms)	30 65 350	30 65 350	30 65 350
Acoustics (dBA) <sup>7</sup> Idle Seek (average)	29 30	29 30	29 30
Physical Dimensions			
Height (in./mm, max)	1.028/25.4	1.028/25.4	1.028/25.4
Length (in./mm, max)	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	0.99/0.45	0.95/0.43	0.99/0.45

Western Digital Technologies 3355 Michelson Drive, Suite 100 Irvine, California 92612 U.S.A.

Learn more about WD Blue Desktop hard drives



#### For service and literature:

http://support.wd.com www.wd.com

800.ASK.4WDC (800.275.4932) 800.832.4778 +800.6008.6008 00800.27549338 North America Spanish Asia Paci c

Europe

+31.880062100

(toll free where available) Europe/Middle East/Africa





























Canada ICES-003 Class B / NMB-003 Classe B

Western Digital, WD, and the WD logo are registered trademarks in the U.S. and other countries; and WD Blue, WD Red, WD Black, NoTouch, and FIT Lab are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product speci cations subject to change

© 2015 Western Digital Technologies, Inc. All rights reserved.

2879-771436-A10 Nov 2015

<sup>2</sup> As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (MB) = one megabyte (MB) = 1,0.48,576 bytes. As used for transfer rate calculated according on operating environment. As used for buffer or cache, one megabyte (MB) = 1,0.48,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabl per second, and gigabl per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA speci cation published by the SATA-10 organization as of the date of this speci cation sheet. Vist www.

<sup>3</sup> WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

<sup>&</sup>lt;sup>4</sup> Controlled unload at ambient condition.

 $<sup>^{5}\,</sup>$  The term of the limited warranty may vary by region. Visit support.wd.com/warranty for details.

 $<sup>^{\</sup>rm 6}\,$  No non-recoverable errors during operating tests or after non-operating tests.

<sup>7</sup> Sound power level.