







EVOLVE 30II

Engineered for flexible connectivity and great sound for calls and music.

-  Great calls and music
-  Plug-and-play connectivity
-  Manage calls easily
-  Flexible connectivity via 3.5 mm jack, USB-A or USB-C



TECHNICAL SPECIFICATIONS

| | | |
|------------------------------|--|--|
| General info | Box content | Jabra Evolve 30 II headset, pouch, foam inlay (only available for duo), layer card, poly bag, documentation |
| | Packaging dimensions LxWxH | Mono: 149.6x59.5x170.1 mm/5.88x2.3x6.7 inch Stereo: 151.2x59.5x170.4 mm/5.9x2.3x6.7 inch |
| | Main unit dimension | Stereo with cable 138.2 mm/without cable 103.6 mm Stereo with cable 5.44 inch/without cable 4.08 inch Mono with cable 107.8 mm/without cable 72.8 mm Mono with cable 4.24 inch/ without cable 2.87 inch |
| | Weight including main wearing style | Stereo 171g/ 6.03oz Mono 142g / 5.02oz |
| | Material used | Soft headband and comfortable on-the-ear foam ear pads |
| | Warranty | 2 years |
| | Jabra Direct/Jabra Xpress | Yes |
| | Jabra Sound+ | No |
| | LED features and functions | Busylight, incoming calls, Teams notifications |
| | Audio | Headset bandwidth |
| Speaker size | | ø28x3.9mm |
| Speaker sensitivity | | 93.6dB SPL @ 1kHz |
| Speaker impedance | | 32+/-4.8 Ω @ 1.0kHz |
| Speaker max input power | | Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V |
| Speaker frequency range | | 150Hz-7kHz, @ Output S.P.L -10dB |
| Speaker bandwidth Speak mode | | 150Hz-7kHz, @Output S.P.L -10dB |
| Microphone type | | Electret condenser (ECM) |
| Microphone sensitivity | | F=1kHz, pin=1Pa, 0dB=1V/Pa, Min=-48dB, Max=-44dB |
| Microphone frequency range | | 100Hz ~ 10kHz @ 6dB |
| Microphone bandwidth | | Wideband |
| User hearing protection | PeakStop™ | |
| Certifications | Leading UC vendors; Microsoft Teams-certified* | |
| Fit & Comfort | Headset form factor | On-ear headband |
| Connectivity | Connection (computer and mobile devices) | 3.5 mm jack, USB-A/USB-C |
| | Cord length | Control cable: 95 cm/37.4 in, HS cable: 120 cm/47.24 in |
| | AC power supply | USB power supply by PC |
| Extended Info | Power consumption speaker | Rated Input 5mW @ 0.4V, max input 10mW @ 0.56V |
| | Operating temperature | -10°C to +50°C, 14°F to 122°F |
| | Storage temperature | -30°C to + 80°C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour < 20% degradation) |

*Microsoft Teams variants only

| PRODUCT TYPE | SKU | DESCRIPTION | EAN CODE |
|--------------|--------------|--|---------------|
| Stereo | 5399-823-309 | Jabra Evolve 30 II MS Stereo, USB-A | 5706991019964 |
| | 5399-823-389 | Jabra Evolve 30 II MS Stereo, USB-C | 5706991023879 |
| | 5399-829-309 | Jabra Evolve 30 II UC Stereo, USB-A | 5706991019971 |
| | 5399-829-389 | Jabra Evolve 30 II UC Stereo, USB-C | 5706991023886 |
| Mono | 5393-823-309 | Jabra Evolve 30 II MS Mono, USB-A | 5706991019940 |
| | 5393-823-389 | Jabra Evolve 30 II MS Mono, USB-C | 5706991023893 |
| | 5393-829-309 | Jabra Evolve 30 II UC Mono, USB-A | 5706991019957 |
| | 5393-829-389 | Jabra Evolve 30 II UC Mono, USB-C | 5706991023909 |
| Accessory | 14208-35 | Jabra Evolve 30 II LINK MS Controller, USB-C | 5706991023923 |
| | 14208-36 | Jabra Evolve 30 II LINK UC Controller, USB-C | 5706991023930 |