



WWS650 | 2D Wireless Barcode Scanner **Durable and Dependable Multi-Tasking, Bluetooth Barcode Scanner**



Key Features

- Scans Popular 1D and 2D Barcodes
- Data Collect 82ft (25m) from Base
- Stores 500+ Linear Codes in Memory
- Durable 5ft (1.5m) Drop Spec and IP42 Rating
- Green Spot Technology for Good-Read Feedback

WWS650 | 2D Wireless Barcode Scanner

OPTIC & PERFORMANCE

Aiming: 2 Blue LED's
Illumination: Red LED 610 - 650 nm
Imager Sensor: Wide VGA: 752 x 480 pixels
Resolution: 0.102 mm / 4 mils (Linear Codes)
Scan Angle: Pitch: +/- 65°; Roll (Tilt): 360°; Skew (Yaw): +/- 60°
Print Contrast Ratio: 25%

DEPTH OF FIELD

Code 39 5 mils: 0.5 to 15.0 cm / 0.2 to 5.9 in
EAN/UPCA 13 mils: 0.5 to 35.0 cm / 0.2 to 13.8 in
PDF417 6.6 mils: 2.0 to 15.0 cm / 0.8 to 5.9 in
Data Matrix 10 mils: 2.0 to 16.0 cm / 0.8 to 6.3 in

PHYSICAL CHARACTERISTICS

Dimension: 6.4 x 3.6 x 1.6 in (16.3 x 9.1 x 4.1 cm)
Scanner Weight: 7.1 oz. (200 g.)
Base/Charger Weight: 7.1 oz. (200 g.)
Color: Gray & Black
Connector: USB
Trigger: Scan button
Indicator: Beeper (Adjustable Tone and Volume); 'Green Spot'
Good Read Feedback and Good Read LED

ELECTRICAL

Battery Type: Lithium-Ion 1400 mAh
Charging Time: External Power: < 3 hrs. @ 12 VDC (30,000+ reads per Charge)
Input Voltage: 4.75 - 14 VDC

CONNECTIVITY

Bluetooth 3.0 Certified Class 2
USB

USER ENVIRONMENT

Operating Temperature: 32 to 122 °F (0 to 50 °C)
Storage Temperature: -40~158°F (-40~70°C)
Humidity: 5- 95% (Non-condensing)
Scanner Drop Durability: Withstands repeated drops from 5.0 ft. (1.50 m) onto a concrete surface
Sealing: IP42
Ambient Light: 0 - 100,000 lux
Symbologies: Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes. Aztec Code; Aztec Mesas; Data Matrix; MaxiCode; QR Code, Micro QR Code; China Han Xin Code; Australian Post; British Post; Canadian Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC); EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

REGULATORY

ESD Protection: 16 kV
EMC: FCC Part15, CE EC-113_01
Environmental: WEEE and RoHS



Wasp North America

1400 10th Street
Plano, Texas 75074
1-866-547-9277

www.waspbarcode.com

Wasp Europe

Dunstable Road
Redbourn, St Albans AL3 7PR, UK
0845-430-1971

www.waspbarcode.co.uk

Wasp International

+1 214-547-4100