



HDMI ► HDMICable

- With Ethernet

Part no. DP-HDMI-XX-MM



4K Video



HDMI



HDMI 2.0



Part no	Length	Part no	Length
HDMI-0.5-MM-V4	0.5m	HDMI-01-MM-V4B	1m (Retail)
HDMI-01-MM-V4	1m	HDMI-02-MM-V4B	2m (Retail)
HDMI-1.5-MM-V4	1.5m	HDMI-03-MM-V4B	3m (Retail)
HDMI-02-MM-V4	2m	HDMI-05-MM-V4B	5m (Retail)
HDMI-03-MM-V4	3m	HDMI-10-MM-V4	10m (Retail)
HDMI-05-MM-V4	5m	HDMI-15-MM-V4	15m (Retail)
HDMI-7.5-MM-V4	7.5m		
HDMI-10-MM-V4	10m		
HDMI-15-MM-V4	15m		







Connect HDMI Source to a HDMI Display

- Conforms to HDMI Ver 2.0 Specification. Data rates up to 10.2 Gbps. Refresh rates to 120Hz. Colour depth to 48 bits - 16 bits per colour
- HDMI Ethernet Channel can take advantage of IPenabled devices without a separate Ethernet cable.
- Supports ARC (Audio Return Channel, which allows a HDMI host to transmit audio data upstream eliminating the need for a separate audio cable

User Interface

Input

HDMI Male x 2

Resolution

Up to Ultra HD 4K 4096 x 2160

Video

Supports 3D Video Refresh rates to 120Hz Colour depth to 48 bits - 16 bits per colour

Audio

Supports ARC (Audio Return Channel)

Package Includes

VGA to VGA Cable × 1

Physical Characteristics

- 30 AWG Cable
- TPE (Thermo Plastic Elastomer) low profile connectors

Compliance

HDMI 2.0

Data Rate

Up to 10.2 Gbps

Warranty

Lifetime