

HuddleCamHD Webcam

Conferencing Webcam

The HuddleCamHD webcam is an easy to use, Plug-and-Play camera with USB 2.0 connectivity & power.

Model Number:
 HC-WEBCAM-104-v2
<https://huddlecamed.com/webcam/>

KEY FEATURES

- Plug & Play USB power
- USB 2.0
- 1920 x 1080
- 104° Field of View
- Up to 30 fps
- Webcam v2 Configuration Tool



WHAT'S IN THE BOX

- Plug & Play Webcam
- Quick Start Guide
- Privacy cover



- | | | |
|--|--|--|
| <p>1. Lens
104° Horizontal Field of View lens</p> <p>4. Lens Cover
Rubber lens cover</p> | <p>2. LED Indicator
LED is illuminated during use</p> <p>5. Mounting Base
To mount camera to monitor or 1/4-20 screw</p> | <p>3. Microphone Array
Beamforming microphones for high quality pickup</p> <p>6. USB 2.0 Cable
For connection to PC USB 2.0 port</p> |
|--|--|--|

Image Sensor & Lens	
Video CMOS Sensor	1/2.7" CMOS, 2.07 Mega Pixel
Resolution	1080p-30/25, 720p-30/25
Frame Rate	up to 30fps (MJPEG)
Lens	Focus: f=2.26mm
Horizontal Field of View	104°
Min. Illumination	0.5 Lux @ (F2.0, AGC ON)
Digital Noise Reduction	2D, 3D DNR
Electrical Index	
Input Voltage	5V (USB Power)
Current Consumption	200mA
Power Consumption	1W
Working Environment	Indoor

Physical Specifications	
Cable Length	55 in. 139.7 cm
Material	Plastic
Dimensions (in.)	4.6"W x 1.5"H x 1.2"D (not including bracket)
Dimensions (mm)	118 x 37.2 x 30.8 (not including bracket)
Weight	0.35 lbs (0.16 kg)
Box Dimensions	5.4"W x 3.1"H x 3.0"D (137mm x 79mm x 76mm)
Boxed Weight	0.75 lbs (0.34 kg)
Operating Temperature	14°F to 104°F (-10°C to 40°C)
Storage Temperature	-40°F to 140°F (-40°C to 60°C)
Rear Board Connectors	
Video/Power Interface	USB 2.0
Other	
Mfg. Warranty	5 Years Parts & Labor