

ViewSonic® LCD DISPLAY XG271QG

Key Features

- Lightning-fast 240Hz Refresh Rate
- Lower system latency with NVIDIA® Reflex
- Fast-IPS QHD screen with DisplayHDR™ 400
- Smoothest and fastest gameplay with NVIDIA® G-Sync



Product Description

Dominate the competition with greater precision and exceptional motion fidelity on the minimalistic 27" XG271QG gaming monitor. Geared with blazing fast refresh rate of 240Hz and true-to-life colors from VESA certified DisplayHDR™ 400, see your favorite games in stunning realism and deeper immersion. Experience incredibly smooth, stutter-and-tear-free, and low latency gameplay with NVIDIA® Reflex and G-Sync for highly accurate aims and quicker reload speeds. With the ELITE XG271QG, it's gaming levelled up.

Visit Us  www.viewsonic.com

DISPLAY

| | |
|------------------------------|--------------------------------|
| Display Size (in.): | 27 |
| Viewable Area (in.): | 27 |
| Panel Type: | IPS Technology |
| Resolution: | 2560 x 1440 |
| Resolution Type: | QHD |
| Static Contrast Ratio: | 1,000:1 (typ) |
| Dynamic Contrast Ratio: | 120M:1 |
| Light Source: | LED |
| Brightness: | 400 cd/m ² (typ) |
| Colors: | 16.7M |
| Color Space Support: | 8 bit true |
| Aspect Ratio: | 16:9 |
| Response Time (Typical GTG): | 1ms |
| Viewing Angles: | 178° horizontal, 178° vertical |
| Backlight Life (Hours): | 30000 Hrs (Min) |
| Curvature: | Flat |
| Refresh Rate (Hz): | 240 |
| Adaptive Sync: | G-Sync |
| Blue Light Filter: | Yes |
| Flicker-Free: | Yes |

| | |
|--------------|--|
| Color Gamut: | Adobe RGB: 99% coverage (Typ) DCI-P3: 95% coverage (Typ) NTSC: 109% size (Typ) sRGB: 154% size (Typ) |
|--------------|--|

| | |
|--------------------|-------------------------------|
| Pixel Size: | 0.233 mm (H) x 0.233 mm (V) |
| Surface Treatment: | Anti-Glare, Hard Coating (3H) |

COMPATIBILITY

| | |
|------------------------|--|
| PC Resolution (max): | 2560x1440 |
| Mac® Resolution (max): | 2560x1440 |
| PC Operating System: | Windows 7/8/10 certified; macOS tested |
| Mac® Resolution (min): | 2560x1440 |

CONNECTOR

| | |
|-----------------------------|-----------------------------|
| USB 3.2 Type A Down Stream: | 3 |
| USB 3.2 Type B Up Stream: | 1 |
| 3.5mm Audio Out: | 1 |
| HDMI 2.0 (with HDCP 2.2): | 2 |
| DisplayPort: | 1 |
| Power in: | DC Socket (Center Positive) |

AUDIO

| | |
|--------------------|-----------|
| Internal Speakers: | 3Watts x2 |
|--------------------|-----------|

POWER

| | |
|------------------------|------------------------|
| Eco Mode (Conserve): | 44W |
| Eco Mode (optimized): | 53W |
| Consumption (typical): | 60W |
| Consumption (max): | 65W |
| Voltage: | AC 100-240V |
| Stand-by: | 0.5W |
| Power Supply: | External Power Adaptor |

ADDITIONAL HARDWARE

| | |
|-----------------------|-----|
| Kensington Lock Slot: | 1 |
| Cable Organization: | Yes |

CONTROLS

| | |
|--------------------|--|
| Physical Controls: | Joystick key: Up, Right, Down, Left, Center; Quick Access; Power |
| On Screen Display: | Game Modes, Display, NVIDIA Reflex, Input Select, Audio Adjust, Setup Menu |

OPERATING CONDITIONS

| | |
|----------------------------|-----------------------------|
| Temperature: | 32°F to 104°F (0°C to 40°C) |
| Humidity (non-condensing): | 20% to 90% |

WALL MOUNT

| | |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

INPUT SIGNAL

| | |
|-----------------------|--|
| Frequency Horizontal: | HDMI (v2.0): 30 ~ 230KHz, DisplayPort (v1.4): 30 ~ 250KHz |
| Frequency Vertical: | HDMI (v2.0): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 240Hz |

VIDEO INPUT

| | |
|---------------|--|
| Digital Sync: | TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4) |
|---------------|--|

ERGONOMICS

| | |
|----------------------|-----------|
| Height Adjust (mm): | 120 |
| Swivel: | 60° |
| Tilt (Forward/Back): | -5° / 20° |
| Pivot (Right/Left): | 90° / 90° |

WEIGHT (IMPERIAL)

| | |
|--------------------------|------|
| Net (lbs): | 16.8 |
| Net Without Stand (lbs): | 10.1 |
| Gross (lbs): | 26.3 |

WEIGHT (METRIC)

| | |
|-------------------------|-----|
| Net (kg): | 7.6 |
| Net Without Stand (kg): | 4.6 |
| Gross (kg): | 12 |

DIMENSIONS (IMPERIAL) (WXHXD)

| | |
|-------------------------------|--------------------------|
| Packaging (in.): | 28.6 x 20 x 11 |
| Physical (in.): | 24.2 x 18.06~22.5 x 10.4 |
| Physical Without Stand (in.): | 24.2 x 14.6 x 2.7 |

DIMENSIONS (METRIC) (WXHXD)

| | |
|------------------------------|-------------------------|
| Packaging (mm): | 726 x 507 x 280 |
| Physical (mm): | 614 x 458.7~571.6 x 265 |
| Physical Without Stand (mm): | 614 x 370 x 69 |

GENERAL

| | |
|--------------|---|
| Regulations: | cTUVus, FCC-B, ICES003, CEC, NRCAN, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, CCC, China RoHS, China Energy Label |
|--------------|---|

| | |
|-------------------|---|
| PACKAGE CONTENTS: | XG271QG x1, 3-pin Mickey Mouse Plug (IEC C5) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1 |
|-------------------|---|

| | |
|-------------------|--|
| Recycle/Disposal: | Please dispose of in accordance with local, state or federal laws. |
|-------------------|--|

| | |
|-----------|--|
| Warranty: | *Warranty offered may differ from market to market |
|-----------|--|