

# PoE++ Injector

MODEL: TL-POE170S Datasheet

## Features


- 2 gigabit ports ensure faster transmission
- Complies with IEEE802.3af/at/bt\* standards, supplies up to 60 W
- Reduces infrastructure costs by transmitting data and power simultaneously via an Ethernet cable
- Automatically determines and supplies the exact power to meet the device's need
- Wall-mounting and desktop design accommodates most installations scenarios
- Plug & Play installation, requires no configuration
- Integrated power supply
- Durable metal casing

## Overview

The PoE++ Injector TL-POE170S fully complies with IEEE 802.3af/at/bt\* standards. The power supply can reach up to 60 W, which can power high-power PTZ IPC, LED and other equipment. Durable metal casing ensures a long product life and compact desktop/wall-mounting design offers more versatile installation at any location.



# Specifications

Product Picture	
Model	TL-POE170S
Standards	IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3af, IEEE802.3at, IEEE802.3bt
Ports	1 10/100/1000Mbps RJ45 data-in port 1 10/100/1000Mbps RJ45 power+data-out port 1 AC socket
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 cable(maximum 100m)
Basic Function	Auto-Sensing Algorithm enables providing power with 802.3af/at/bt* PD Auto-determine the necessary power requirements Wall-mounting and desktop installation supported Plug-and-Play
Power	Input: 100-240 V, 50/60 Hz, 1.6 A Output: Auto-determine the necessary power requirements (max. 60 W)
Dimensions ( W x D x H )	154.7 x 70 x 42 mm
Distance between Wall-mounting Holes	102 mm
Certification	FCC, CE, RoHS
Package Contents	TL-POE170S, power cord, RJ45 cable, installation guide
Environment	Operating Temperature: 0°C to 45°C (32°F to 113°F) Storage Temperature: -40°C to 70°C (-40°F to 158°F) Operating Humidity: 10% to 90%RH non-condensing Storage Humidity: 5% to 90%RH non-condensing

## Note:

\* TL-POE170S is incompatible with EAP235, EAP225 and EAP225-Outdoor. For these three products, it is recommended to use TL-POE160S.

[www.tp-link.com](http://www.tp-link.com)

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. © 2021 TP-Link