



Manhattan USB-C Dock/Hub with Card Reader, Ports (x3): USB-A (x3), 5 Gbps (USB 3.2 Gen1 aka USB 3.0), External Power Supply Not Needed, SuperSpeed USB, Black, Three Year Warranty, Retail Box



Brand : Manhattan

Product code: 164948

Product name : USB-C Dock/Hub with Card Reader, Ports (x3): USB-A (x3), 5 Gbps (USB 3.2 Gen1 aka USB 3.0), External Power Supply Not Needed, SuperSpeed USB, Black, Three Year Warranty, Retail Box

- Adds three SuperSpeed USB-A ports and card-reader access to a USB-C device for more access to peripherals such as a keyboard, mouse, flash drive and more
- Compatible with Secure Digital (SD), Micro Secure Digital (MicroSD), MultiMediaCard (MMC) and USB Flash Drive; supports automatic card detection
- Supports data transfer rates up to 5 Gbps
- Backward compatible with all USB 2.0 and 1.1 devices
- Bus powered: no external power supply needed
- Includes an LED power indicator
- Plug-and-Play installation; hot swappable
- Windows and Mac compatible
- Three-year warranty

USB-C Hub/Dock with Card Reader, 3x USB-A ports, 5 Gbps (USB 3.2 Gen1), SD and MicroSD, Bus Power, Black

| Ports & interfaces | | Operational conditions | |
|-------------------------------------|---|-----------------------------------|-------------|
| Host interface * | USB 2.0 Type-C | Storage temperature (T-T) | -20 - 60 °C |
| Performance | | Operating relative humidity (H-H) | 0 - 96% |
| Card reader integrated * | ✓ | Weight & dimensions | |
| Compatible memory cards | MMC, MicroSD (TransFlash), MicroSDHC, MicroSDXC, SD, SDHC, SDXC | Width | 43 mm |
| Product colour * | Black | Depth | 97 mm |
| Hub interfaces | USB 3.2 Gen 1 (3.1 Gen 1) Type-A | Height | 14 mm |
| Housing material | Plastic | Weight | 46 g |
| Certification | FCC CE RoHS WEEE | Packaging data | |
| Power | | Quantity per pack | 1 pc(s) |
| Output current | 0.9 A | Packaging content | |
| Software | | Manual | ✓ |
| Windows operating systems supported | ✓ | Other features | |
| Mac operating systems supported | ✓ | Cable length | 0.135 m |
| | | Maximum operating temperature | 40 °C |



0766623164948



766623164948

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-NOV-2024. Prints or copies of Information are only valid on the printed Publication date