Viewsonic IFP6552-1A Signage Display Interactive flat panel 165.1 cm (65") 350 cd/m² 4K Ultra HD Black Touchscreen Built-in processor Android 9

Brand : Viewsonic

Product name : IFP6552-1A

Product code: IFP6552-1A

- INTUITIVE AND ULTRA-RESPONSIVE TOUCHSCREEN
- FRONT-FACING SOUNDBAR
- BUILT-IN BEAMFORMING MICROPHONE
- POWER DELIVERY

65", 3840 x 2160, 1200:1, LCD, 60 Hz, 16:9, 350 cd/m2, 8ms
Viewsonic IFP6552-1A. Product design: Interactive flat panel. Display diagonal: 165.1 cm (65"), Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD, Touchscreen. Operating system installed: Android 9. Product colour: Black

Display

Panel type	IPS
LED backlighting type	Direct-LED
Display diagonal *	165.1 cm (65")
Display resolution *	3840 x 2160 pixels
Display brightness *	350 cd/m²
HD type *	4K Ultra HD
Touchscreen *	✔
Number of simultaneous touchpoints	20
Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	5000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours

Ports & interfaces

HDMI ports quantity *	3
HDMI version	2.0
HDMI output ports quantity	1
DisplayPorts quantity *	1
DisplayPort version	1.2
Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s

Audio

Built-in speaker(s) *	✔
Number of built-in speakers	2

Computer system

Built-in processor *	✔
Processor architecture	ARM Cortex-A73
Processor frequency	1.8 GHz
Processor cores	4
Operating system installed	Android 9

Weight & dimensions

Width	1509 mm
Depth	119 mm
Height	955 mm
Weight	43.9 kg

Packaging data

Package width	1660 mm
Package depth	245 mm
Package height	1045 mm
Package weight	55.4 kg

Packaging content

Cables included	AC, AV, HDMI, USB

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%

Certificates

Certification	EMC/CE, CB, RoHS & DOC, REACH, WEEE, ErP. EEI

Logistics data

Harmonized System (HS) code	85285210

Design

Product design *	Interactive flat panel
Product colour *	Black
VESA mounting *	✔
Panel mounting interface	600 x 400 mm

Performance

HDCP	✔
HDCP version	2.2

Power

Power consumption (typical) *	190 W
Power consumption (standby) *	0.5 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	147 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Features

Wall mountable	✔

Technical details

OPS slot	1
Sustainability compliance	✔
Sustainability certificates	ENERGY STAR, EPEAT Silver, ErP
Compliance certificates	CE, RoHS, WEEE

Other features

Graphics card family	ARM
Graphics card	Mali-G52
User memory	32 GB
Maximum refresh rate	60 Hz
Built-in microphone	✔
Built-in subwoofer	✔
Headphone connectivity	3.5 mm
Subwoofer RMS power	15 W
USB 2.0 ports quantity	1
Energy efficiency class (old)	A+

0766907009316

766907009316