SAMSUNG

Display

USB hub version

quantity

USB Type-C downstream ports

Samsung LS27A400UJU computer monitor 68.6 cm (27") 1920 x 1080 pixels Full HD Black

Brand : Samsung

Product code: LS27A400UJUXXU

Product name : LS27A400UJU

27" 1920 x 1080 IPS, 16:9, 250 cd/m2, 5 ms, 75 Hz, FreeSync, DisplayPort, HDMI, USB, 616.6 x 365.9 x 42.8 mm, 4.8 kg, Black

Samsung LS27A400UJU. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black







Display diagonal * 68.6 cm (27") 1920 x 1080 pixels Display resolution * Full HD HD type * Native aspect ratio * 16:9 Panel type * IPS Touchscreen * × 250 cd/m² Display brightness (typical) Response time * 5 ms Screen shape * Flat 1000:1 Contrast ratio (typical) * Dynamic contrast ratio marketing Mega Contrast name Maximum refresh rate * 75 Hz Viewing angle, horizontal 178° 178° Viewing angle, vertical Display number of colours * 16.7 million colours 68 cm Display diagonal (metric) 72% NTSC coverage (typical) Performance AMD FreeSync * 1 AMD FreeSync type FreeSync Flicker-free technology 1 Game mode 1 Smart modes Game Design Market positioning * Business Product colour * Black Ports & interfaces Built-in USB hub * 1

2.0 / 3.2 Gen 1 (3.1 Gen 1) 1

Height adjustment *✓Height adjustment13.5 cmPivot✓Pivot angle-2 - 92°Swiveling✓Swivel angle range-45 - 45°Tilt adjustment✓Tilt angle range-4 - 24°PowerDEnergy efficiency class (SDR) *DEnergy consumption (SDR) per 1000 hours *17 kWhPower consumption (typical) *17 WPower consumption (standby) *0.5 WPower consumption (max)120 WPower consumption (max)100 - 240 VEuropean Product Registry for Energy Labelling (EPREL) code848122Operating temperature (T-T)0 - 40 °C Operating relative humidity (H-H)Derth (with stand)532.9 mmHeight (with stand)532.9 mmHeight (with stand)6.6 kgWidth (without stand)42.8 mmHeight (without stand)365.9 mmWeight (without stand)4.8 kg	Ergonomics	
Energy efficiency class (SDR) *DEnergy consumption (SDR) per 1000 hours *17 kWhPower consumption (typical) *17 WPower consumption (standby) *0.5 WPower consumption (max)120 WPower consumption (max)120 WPower consumption (off)0.3 WAC input voltage100 - 240 VEuropean Product Registry for Energy Labelling (EPREL) code848122Operational conditions0 - 40 °COperating remperature (T-T)0 - 40 °COperating relative humidity (H-H)10 - 80%Weight & dimensions192.9 mmHeight (with stand)532.9 mmWidth (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)42.8 mmHeight (without stand)365.9 mm	Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment	13.5 cm ✓ -2 - 92° ✓ -45 - 45°
Energy consumption (SDR) per 1000 hours *17 kWhPower consumption (typical) *17 WPower consumption (standby) *0.5 WPower consumption (max)120 WPower consumption (off)0.3 WAC input voltage100 - 240 VEuropean Product Registry for Energy Labelling (EPREL) code848122Operational conditions0 - 40 °COperating temperature (T-T)0 - 40 °COperating relative humidity (H-H)10 - 80%Weight & dimensions192.9 mmWidth (with stand)532.9 mmWeight (with stand)6.6 kgWidth (without stand)6.6 kgWidth (without stand)6.6 kgWidth (without stand)6.6 kgHeight (without stand)42.8 mmHeight (without stand)365.9 mm	Power	
Power consumption (standby)*0.5 WPower consumption (max)120 WPower consumption (off)0.3 WAC input voltage100 - 240 VEuropean Product Registry for Energy Labelling (EPREL) code848122Operational conditions0 - 40 °COperating temperature (T-T)0 - 40 °COperating relative humidity (H-H)10 - 80%Weight & dimensions192.9 mmWidth (with stand)532.9 mmWeight (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)6.6 kgWidth (without stand)6.6 kgHeight (without stand)6.6 kgHeight (without stand)6.6 kgWidth (without stand)6.6 kgHeight (without stand)365.9 mm	Energy consumption (SDR) per 1000	-
Energy Labelling (EPREL) code848122Operational conditionsOperating temperature (T-T)0 - 40 °COperating relative humidity (H-H)10 - 80%Weight & dimensionsWidth (with stand)616.6 mmDepth (with stand)192.9 mmHeight (with stand)532.9 mmWeight (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)616.6 mmHeight (without stand)616.6 mmDepth (without stand)616.6 mmDepth (without stand)616.6 mmDepth (without stand)616.6 mmDepth (without stand)616.6 mmHeight (without stand)365.9 mm	Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage	0.5 W 120 W 0.3 W
Operating temperature (T-T)0 - 40 °COperating relative humidity (H-H)10 - 80%Weight & dimensionsWidth (with stand)616.6 mmDepth (with stand)192.9 mmHeight (with stand)532.9 mmWeight (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)635.9 mm	1 3 3	848122
Operating relative humidity (H-H)10 - 80%Weight & dimensionsWidth (with stand)616.6 mmDepth (with stand)192.9 mmHeight (with stand)532.9 mmWeight (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)42.8 mmHeight (without stand)365.9 mm	Operational conditions	
Width (with stand)616.6 mmDepth (with stand)192.9 mmHeight (with stand)532.9 mmWeight (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)42.8 mmHeight (without stand)365.9 mm		
Depth (with stand)192.9 mmHeight (with stand)532.9 mmWeight (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)42.8 mmHeight (without stand)365.9 mm	Weight & dimensions	
Weight (with stand)6.6 kgWidth (without stand)616.6 mmDepth (without stand)42.8 mmHeight (without stand)365.9 mm	, ,	
Depth (without stand)42.8 mmHeight (without stand)365.9 mm		
Height (without stand) 365.9 mm		
	Height (without stand)	365.9 mm

Ports & interfaces		Packaging data	Packaging data		
HDMI *	1	Package width	685 mm		
HDMI ports quantity	1	Package depth	435 mm		
HDMI version	1.4	Package height	215 mm		
DisplayPorts quantity	1	Package weight	8.7 kg		
DisplayPort version	1.2	Packaging content	Packaging content		
Headphone out *	4	Cables included	AC, HDMI, USB Type-C		
Ergonomics		Logistics data			
VESA mounting * Panel mounting interface	✓ 100 x 100 mm	Harmonized System (HS) code	85285210		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.