



Lindy 140m Cat.6 DVI-D, USB, Audio and RS-232 KVM Extender

Brand : Lindy

Product code: 39245

Product name : 140m Cat.6 DVI-D, USB, Audio and RS-232 KVM Extender



- Extends DVI-D, USB 2.0, Audio and RS-232 up to 140m using only one Cat.6 cable
- Supports DVI Single Link resolutions up to 1920x1200
- 4 USB 2.0 Type A ports to connect keyboard, mouse and mass storage devices
- Easy, user friendly installation - no software required
- 2 year warranty

140m Cat.6 DVI-D, USB, Audio and RS-232 KVM Extender

Lindy 140m Cat.6 DVI-D, USB, Audio and RS-232 KVM Extender. Type: Transmitter & receiver, Connectivity technology: Wired, Maximum transfer distance: 140 m. Transmitter video port type: DVI-I. Receiver local video port type: DVI-I. USB port type: USB Type-A/USB Type-B. Transmitter width: 12.5 cm, Transmitter depth: 14 cm, Transmitter height: 3 cm



Features		Weight & dimensions	
Type *	Transmitter & receiver	Transmitter depth	14 cm
Connectivity technology *	Wired	Transmitter height	3 cm
Maximum transfer distance	140 m	Receiver width	12.5 cm
Cable types supported	Cat6	Receiver depth	14 cm
Maximum refresh rate	60 Hz	Receiver height	3 cm
Product colour	Black	Packaging data	
Material	Metal	Package width	355 mm
Certification	CE, UKCA, FCC, RoHS, REACH & California Proposition 65	Package depth	195 mm
Transmitter		Package height	60 mm
Transmitter video port type	DVI-I	Package weight	1.52 kg
RJ-45 ports quantity (transmitter)	1	Packaging content	
Receiver		AC adapter included	✓
Receiver local video port type	DVI-I	Screwdriver included	✓
RJ-45 ports quantity (receiver)	1	Cables included	Audio (3.5mm), RS-232, USB Type-A to USB Type-B
Ports & interfaces		Manual	✓
USB port type	USB Type-A/USB Type-B	Operational conditions	
USB 2.0 ports quantity	4	Operating temperature (T-T)	-20 - 60 °C
RJ-45 ports quantity	2	Storage temperature (T-T)	-20 - 85 °C
PC Audio in	✓	Operating relative humidity (H-H)	0 - 95%
Weight & dimensions		Technical details	
Transmitter width	12.5 cm	Maximum resolution	1920 x 1200 pixels
		Power requirements	5VDC 2.6A
		Weight	1.27 kg
		Logistics data	
		Harmonized System (HS) code	84733080



4002888392457

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-NOV-2024. Prints or copies of Information are only valid on the printed Publication date