

Lindy 100m Cat.6A HDMI 4K60, Audio, IR and RS-232 HDBaseT 3.0 KVM Extender

Brand : Lindy Product code: 38344

Product name: 100m Cat.6A HDMI 4K60, Audio, IR and

RS-232 HDBaseT 3.0 KVM Extender

- Distributes HDMI resolutions up to 100m over Cat.6A or above network cable via HDBaseT technology
- Supports HDMI 18G resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- ARC Support as well as USB, RS-232, CEC and Ethernet pass-through and bi-directional IR for simple control
- Supports PoC (Power over cable), requiring a power supply connection from only one side of the installation
- 2 year warranty

100m Cat.6A HDMI 4K60, Audio, IR and RS-232 HDBaseT 3.0 KVM Extender Lindy 100m Cat.6A HDMI 4K60, Audio, IR and RS-232 HDBaseT 3.0 KVM Extender. Type: Transmitter & receiver, Connectivity technology: Wired, Maximum transfer distance: 100 m. Transmitter video port type: HDMI, Transmitter local keyboard/mouse port type: USB. Receiver local video port type: HDMI, Receiver local keyboard/mouse port type: USB. AC adapter output voltage: 24 V, AC adapter output current: 1 A. Transmitter width: 17 cm, Transmitter depth: 8.8 cm, Transmitter height: 2 cm





Features		Power	
Type * Connectivity technology * Maximum transfer distance Cable types supported Maximum digital resolution Maximum refresh rate Colour depth Product colour Material LED indicators Certification	Transmitter & receiver Wired	AC adapter output voltage AC adapter output current	24 V 1 A
		Weight & dimensions	
		Transmitter width Transmitter depth Transmitter height Transmitter weight Receiver width Receiver depth Receiver height Receiver weight	17 cm 8.8 cm 2 cm 862 g 17 cm 8.8 cm 2 cm 862 q
Transmitter		Packaging data	
Transmitter video port type Transmitter local keyboard/mouse port type RJ-45 ports quantity (transmitter)	HDMI USB 2	Package width Package depth Package height Package weight	290 mm 220 mm 75 mm 1.1 kg
Receiver		Packaging content	9
Receiver local video port type Receiver local keyboard/mouse port type RJ-45 ports quantity (receiver)	HDMI USB 2	AC adapter included Cables included Manual	√ IR √
Ports & interfaces		Operational conditions	
HDMI version RS-232 ports		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 60 °C 20 - 90%
		Sustainability	
		Sustainability compliance	✓
		Other features	
		Compliance certificates	CE, REACH, RoHS



4002888383448

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.