

Part No. 43275

7 PORT USB 3.1 GEN 2 METAL HUB

7 ADDITIONAL USB 3.1 GEN 2 PORTS - PERFECT FOR INDUSTRIAL APPLICATIONS



DESCRIPTION

- Connects 4 Type A and 3 Type C USB 3.1 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- Powered by external power supply or terminal block
- 2 year warranty

The Lindy 7 Port USB 3.1 Gen 2 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.1 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

Each port features individual short circuit protection - and all 7 USB ports support the Battery Charging specification 1.2 with a total charging power of 40 Watts for all 7 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

RELATED PRODUCTS

0

7 PORT USB 3.1 GEN 2 METAL HUB

SPECIFICATIONS

USB Standard	USB 3.1 Gen 2
Supported Bandwidth	10Gbps
Chipset	2x VL820
Compatibility	USB Type C equipped computers, Thunderbolt 3
Power Delivery	-
Special Features	Integrated brackets for mounting; allows connection of USB Type C locking cables; Terminal Block

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	184.5x64.3x20mm (7.26x2.53x0.79in)
(Fixed) Cable Length	-
Housing Material	Metal
Net Weight	0.3kg (0.66lb)
Operating Temperature	0°C - 50°C (32°F -122°F)
Storage Temperature	-20°C - 60°C (-4°F -140°F)
Humidity	90% RH (non-condensing)
Power Requirements	16VDC 3A
Colour	Black

PURCHASING INFORMATION

No.	43275
EAN	4002888432757

CONNECTORS

Inputs	1 x USB Type C (Female)
Outputs	3 x USB Type C (Female), 4 x USB Type A (Female)
Power	DC screw connector

MISCELLANEOUS

Packaging Type	Carton Box
Packaging Dimensions	260x180x70mm (10.24x7.09x2.76in)
Gross Weight	0.844kg (1.54lb)
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RCM, RoHS, REACH, California Proposition 65

PACKAGING CONTENT

7 Port USB 3.1 Gen 2 Metal Hub
 0.55m USB 3.1 Gen 2 Dual Screw Type C Male to Male Cable
 Multi-Country Power Supply (EU, UK, US, AUS) with screw type DC connector
 Lindy Manual

Part No. 43275

7 PORT USB 3.1 GEN 2 METAL HUB

7 ADDITIONAL USB 3.1 GEN 2 PORTS - PERFECT FOR INDUSTRIAL APPLICATIONS



DESCRIPTION

- Connects 4 Type A and 3 Type C USB 3.1 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- Powered by external power supply or terminal block
- 2 year warranty

The Lindy 7 Port USB 3.1 Gen 2 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.1 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

Each port features individual short circuit protection - and all 7 USB ports support the Battery Charging specification 1.2 with a total charging power of 40 Watts for all 7 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

RELATED PRODUCTS

0

7 PORT USB 3.1 GEN 2 METAL HUB

SPECIFICATIONS

USB Standard	USB 3.1 Gen 2
Supported Bandwidth	10Gbps
Chipset	2x VL820
Compatibility	USB Type C equipped computers, Thunderbolt 3
Power Delivery	-
Special Features	Integrated brackets for mounting; allows connection of USB Type C locking cables; Terminal Block

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	184.5x64.3x20mm (7.26x2.53x0.79in)
(Fixed) Cable Length	-
Housing Material	Metal
Net Weight	0.3kg (0.66lb)
Operating Temperature	0°C - 50°C (32°F -122°F)
Storage Temperature	-20°C - 60°C (-4°F -140°F)
Humidity	90% RH (non-condensing)
Power Requirements	16VDC 3A
Colour	Black

PURCHASING INFORMATION

No.	43275
EAN	4002888432757

CONNECTORS

Inputs	1 x USB Type C (Female)
Outputs	3 x USB Type C (Female), 4 x USB Type A (Female)
Power	DC screw connector

MISCELLANEOUS

Packaging Type	Carton Box
Packaging Dimensions	260x180x70mm (10.24x7.09x2.76in)
Gross Weight	0.844kg (1.54lb)
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RCM, RoHS, REACH, California Proposition 65

PACKAGING CONTENT

7 Port USB 3.1 Gen 2 Metal Hub
 0.55m USB 3.1 Gen 2 Dual Screw Type C Male to Male Cable
 Multi-Country Power Supply (EU, UK, US, AUS) with screw type DC connector
 Lindy Manual

Part No. 43275

7 PORT USB 3.1 GEN 2 METAL HUB

7 ADDITIONAL USB 3.1 GEN 2 PORTS - PERFECT FOR INDUSTRIAL APPLICATIONS



DESCRIPTION

- Connects 4 Type A and 3 Type C USB 3.1 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- Powered by external power supply or terminal block
- 2 year warranty

The Lindy 7 Port USB 3.1 Gen 2 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.1 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

Each port features individual short circuit protection - and all 7 USB ports support the Battery Charging specification 1.2 with a total charging power of 40 Watts for all 7 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

RELATED PRODUCTS

0

7 PORT USB 3.1 GEN 2 METAL HUB

SPECIFICATIONS

USB Standard	USB 3.1 Gen 2
Supported Bandwidth	10Gbps
Chipset	2x VL820
Compatibility	USB Type C equipped computers, Thunderbolt 3
Power Delivery	-
Special Features	Integrated brackets for mounting; allows connection of USB Type C locking cables; Terminal Block

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	184.5x64.3x20mm (7.26x2.53x0.79in)
(Fixed) Cable Length	-
Housing Material	Metal
Net Weight	0.3kg (0.66lb)
Operating Temperature	0°C - 50°C (32°F -122°F)
Storage Temperature	-20°C - 60°C (-4°F -140°F)
Humidity	90% RH (non-condensing)
Power Requirements	16VDC 3A
Colour	Black

PURCHASING INFORMATION

No.	43275
EAN	4002888432757

CONNECTORS

Inputs	1 x USB Type C (Female)
Outputs	3 x USB Type C (Female), 4 x USB Type A (Female)
Power	DC screw connector

MISCELLANEOUS

Packaging Type	Carton Box
Packaging Dimensions	260x180x70mm (10.24x7.09x2.76in)
Gross Weight	0.844kg (1.54lb)
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RCM, RoHS, REACH, California Proposition 65

PACKAGING CONTENT

7 Port USB 3.1 Gen 2 Metal Hub
 0.55m USB 3.1 Gen 2 Dual Screw Type C Male to Male Cable
 Multi-Country Power Supply (EU, UK, US, AUS) with screw type DC connector
 Lindy Manual

Part No. 43275

7 PORT USB 3.1 GEN 2 METAL HUB

7 ADDITIONAL USB 3.1 GEN 2 PORTS - PERFECT FOR INDUSTRIAL APPLICATIONS



DESCRIPTION

- Connects 4 Type A and 3 Type C USB 3.1 Gen 2 devices to a Type C port with SuperSpeed+ data rates up to 10Gbps
- Hard-wearing USB Hub - Perfect for industrial applications
- Robust metal housing with high EMC protection and integrated brackets for mounting
- Powered by external power supply or terminal block
- 2 year warranty

The Lindy 7 Port USB 3.1 Gen 2 Metal Hub has been designed to provide reliable performance in demanding operating environments at USB 3.1 Gen 2 speeds up to 10 Gbps. This industrial-grade hub features a rugged, all-metal chassis providing excellent EMC protection. With robust metal housing and integrated mounting brackets this hub is the ideal solution for industrial environments. All Type C sockets of the hub allow the connection of single or dual screw USB 3.1 cables which are compliant with USB-IF Type C locking specification.

Each port features individual short circuit protection - and all 7 USB ports support the Battery Charging specification 1.2 with a total charging power of 40 Watts for all 7 ports. The hub can be powered by the included power supply or the terminal block, ensuring flexible, secure and uninterrupted electricity supplies.

RELATED PRODUCTS

0

7 PORT USB 3.1 GEN 2 METAL HUB

SPECIFICATIONS

USB Standard	USB 3.1 Gen 2
Supported Bandwidth	10Gbps
Chipset	2x VL820
Compatibility	USB Type C equipped computers, Thunderbolt 3
Power Delivery	-
Special Features	Integrated brackets for mounting; allows connection of USB Type C locking cables; Terminal Block

PHYSICAL PROPERTIES

Dimensions (approx.) WxDxH	184.5x64.3x20mm (7.26x2.53x0.79in)
(Fixed) Cable Length	-
Housing Material	Metal
Net Weight	0.3kg (0.66lb)
Operating Temperature	0°C - 50°C (32°F -122°F)
Storage Temperature	-20°C - 60°C (-4°F -140°F)
Humidity	90% RH (non-condensing)
Power Requirements	16VDC 3A
Colour	Black

PURCHASING INFORMATION

No.	43275
EAN	4002888432757

CONNECTORS

Inputs	1 x USB Type C (Female)
Outputs	3 x USB Type C (Female), 4 x USB Type A (Female)
Power	DC screw connector

MISCELLANEOUS

Packaging Type	Carton Box
Packaging Dimensions	260x180x70mm (10.24x7.09x2.76in)
Gross Weight	0.844kg (1.54lb)
Warranty (Years)	2
Certificated	CE, UKCA, FCC, RCM, RoHS, REACH, California Proposition 65

PACKAGING CONTENT

7 Port USB 3.1 Gen 2 Metal Hub
 0.55m USB 3.1 Gen 2 Dual Screw Type C Male to Male Cable
 Multi-Country Power Supply (EU, UK, US, AUS) with screw type DC connector
 Lindy Manual