



# TP-Link Tapo Smart Wi-Fi Light Strip, Multicolor

**Brand :** TP-Link


**Product family:** Tapo

**Product code:** TAPO L930-5

**Product name :** Smart Wi-Fi Light Strip, Multicolor



- Zonal Color Control - make the most of 50-section addressable color zones, to suit every mood or scenario setting
  - Extra White LEDs - acts as general lights, strengthening the practicability of the colorful Wi-Fi light strip
  - Fancy Lighting Effects - amuse yourself with well-designed animated lighting effects, available on Tapo App
  - Music Sync - adds more vibe by emitting dynamic lights, parallel with the surrounding music beat
  - Apple HomeKit Supported - control your light strip with Siri using Apple HomeKit
  - Voice Control- compatible with your smart voice assistants, including Alexa and Google Assistant
  - Surface Coating-stays durable, tidy, and complete, thanks to the high-quality PU coating on its surface
  - Wi-Fi Connection - with a stable connection to your networks, it works well without hub requirements
  - Easy Setup - attach the Light Strip with 3M Adhesive on desired spots, connect it to Wi-Fi and configure it via App
- 13 W, 5000×10×3.0 mm, IEEE 802.11 b/g/n, 2.4 GHz, 100-240 V, 50/60 Hz



Features		Power	
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Power source type	AC
Type *	Smart strip light	Input voltage	100-240 V
Bulb type	LED	AC input frequency	50 - 60 Hz
Interface *	Wi-Fi	Rated power	13 W
Product colour *	White	AC input voltage	100-240 V
Colour changing	✓	Weight & dimensions	
Light colour	Multi	Width	10 mm
Dimmable	✓	Height	3 mm
Dimming range	1 - 100%	Length	5000 mm
Wi-Fi frequency	2.4 GHz	Packaging data	
Certification	CE, FCC, IC, JRF, VCCI, RCM, NCC, BSMI, RoHS	Package width	231.5 mm
Performance		Package depth	68.5 mm
Mobile operating systems supported	✓	Package height	204.5 mm
Power		Packaging content	
Energy efficiency class	G	Quantity per pack *	1 pc(s)
Energy consumption per 1000 hours	3 kWh	AC adapter included	✓
Energy efficiency scale	A to G	Other features	
		Operating relative humidity (H-H)	10 - 90%
		Operating temperature (T-T)	-15 - 40 °C



4897098681428



0840030707254



840030707254



4897098681367

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.