# BenQ ST7502S Digital signage flat panel 190.5 cm (75") LCD 400 cd/m² 4K Ultra HD Black Built-in processor Android 8.0 18/7

Brand : BenQ **Product code:** 9H.F89PT.DA2

Product name : ST7502S

- View vivid images on a 4K UHD display
- Ready-to-use with its built-in Android™ OS
- Utilize your display in more ways with an OPS slot-in PC
- Easily create content using custom X-Sign templates

75", 4K UHD (3840x2160), 400 cd/m², 1200:1, 18/7, A73×2 + A53×2, Mali-G51MP2, 2×10W, Android 8.0 BenQ ST7502S. Product design: Digital signage flat panel. Display diagonal: 190.5 cm (75"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 400 cd/m², HD type: 4K Ultra HD. Operating hours (hours/days): 18/7. Operating system installed: Android 8.0. Product colour: Black

Display

Panel type	ADS
LED backlighting type	Direct-LED
Display diagonal *	190.5 cm (75")
Display technology *	LCD
Display resolution *	3840 x 2160 pixels
Display brightness *	400 cd/m²
HD type *	4K Ultra HD
Touchscreen *	✘
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Active display area (W x H)	1649.7 x 927.9 mm
Display diagonal (metric)	191 cm
Panel life	30000 h
Supported graphics resolutions	3840 x 2160
Supported video modes	3840p
RGB colour space	NTSC

Ports & interfaces

HDMI ports quantity *	3
HDMI version	2.0
DVI port *	✔
DVI-D ports quantity	1
VGA (D-Sub) input ports	1
USB port *	✔
USB ports quantity	2
USB version	2.0
Ethernet LAN *	✔

Performance

Operating hours (hours/days)	18/7

Power

Power consumption (typical) *	177 W
Power consumption (standby) *	0.5 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	177 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Computer system

Computer system *	✔
Built-in processor *	✔
Internal memory	3 GB
Internal storage capacity	16 GB
Operating system installed	Android 8.0

Weight & dimensions

Display width	1683.5 mm
Display depth	82.9 mm
Display height	961.7 mm
Display weight	35.9 kg

Packaging data

Package width	203 mm
Package depth	1848 mm
Package height	1158 mm
Package weight	46.1 kg

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi *	✘
PC Audio in	✔

Audio

Built-in speaker(s) *	✔
Number of built-in speakers	2
RMS rated power	20 W

Design

Product design *	Digital signage flat panel
Product colour *	Black
Screen shape	Flat
VESA mounting *	✔
Panel mounting interface	600 x 400 mm

Performance

Purpose *	Universal

Packaging content

Remote control included	✔
Cables included	HDMI

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 80%

Certificates

Certification	CE

Logistics data

Country of origin	China
Products per pallet	6 pc(s)
Harmonized System (HS) code	8528529100

Technical details

Security updates end date	01/09/2024
Compliance certificates	CE

4718755089046

4544438080877

0840046047009

840046047009