



APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery



Brand : APC

Product code: SRTL2200RMXLI-NC

Product name : Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery

Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery


APC Smart-UPS On-Line, 2200VA, Rackmount 3U, 230V, 6x C13+2x C19 IEC, Network Card, Extended runtime, W/ rail kit, W/ Lithium-ion external battery:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 2200VA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with BS1363A British, IEC 320 C20, and Schuko CEE 7/EU1-16P inputs, 6x IEC 320 C13 and 2x IEC 320 C19 outlets. The UPS has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty on the UPS and Lithium-ion battery.

Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	2.2 kVA	Rack capacity	3U
Output power *	1980 W	Cable length	1.83 m
Waveform *	Sine	Product colour *	Black, Silver
Input operation voltage (min) *	160 V	Control type	Buttons
Input operation voltage (max) *	275 V	Display type	LCD
Input frequency *	40 - 70 Hz	International Protection (IP) code	IP20
Output operation voltage (min)	220 V	Certification	CE, EAC
Output operation voltage (max)	240 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	432 J	Storage temperature (T-T)	-20 - 50 °C
Crest factor	3:1	Operating relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	2%	Technical details	
Noise level	50 dB	Sustainability certificates	Green Premium
Surge protection	✓	Weight & dimensions	
Audible alarm(s)	✓	Width	432 mm
Auto shut-off	✓	Depth	639 mm
Power source type	AC	Height	128 mm
Ports & interfaces		Weight	30.5 kg
AC outlet types	C13 coupler, C19 coupler	Package width	870 mm
AC outlets quantity	8 AC outlet(s)	Package depth	600 mm
Emergency Power Off (EPO) connector	✓	Package height	245 mm
Battery		Package weight	41.4 kg
Battery technology	Lithium-Ion (Li-Ion)	Packaging data	
Battery voltage	48 V	Rack mount kit	✓
Battery life (max)	10 year(s)	Cables included	Output power cable, USB cable
Battery recharge time	4 h	Manual	✓
		Quick installation guide	✓
		Logistics data	
		Harmonized System (HS) code	85078000
		Other features	
		Bypass	Built-in



0731304347545



731304347545



8592978146061

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.