![BenQ logo]

BenQ MW826STH data projector Short throw projector 3500 ANSI lumens DLP WXGA (1280x800) 3D White

Brand : BenQ

Product code: 9H.JMW77.13E

Product name : MW826STH

- 0.49 Short Throw Ratio
- SmartEco Power Saving Technology
- PointWrite Interactive Solution Compatible

DLP, 3500 ANSI Lumen, 1280 x 800, 16:10, 20000:1, RMS 10W

BenQ MW826STH. Projector brightness: 3500 ANSI lumens, Projection technology: DLP, Projector native resolution: WXGA (1280x800). Light source type: Lamp, Service life of light source: 6000 h, Service life of light source (economic mode): 10000 h. Throw ratio: 0.49:1, Offset: 105%. Supported 3D formats: Frame Sequential, Frame packing, Side by side, Top and bottom, Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1200 (WUXGA), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232

Projector

Screen size compatibility *	1778 - 3048 mm (70 - 120")
Projector brightness *	3500 ANSI lumens
Projection technology *	DLP
Projector native resolution *	WXGA (1280x800)
Contrast ratio (typical) *	20000:1
Native aspect ratio *	16:10
Number of colours	1.07 billion colours
Keystone correction, vertical	-30 - 30°
Matrix size	1.65 cm (0.65")

Light source

Light source type *	Lamp
Service life of light source *	6000 h
Service life of light source (economic mode)	10000 h
Lamps quantity	1 lamp(s)

Lens system

Zoom capability	✖
Throw ratio	0.49:1
Offset	105%

Video

Full HD *	✖
3D *	✔
Supported 3D formats	Frame Sequential, Frame packing, Side by side, Top and bottom
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1200 (WUXGA)
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Ports & interfaces

S-Video inputs quantity	1
USB 2.0 ports quantity *	1
Mini-USB 2.0 ports quantity	1

Network

Ethernet LAN (RJ-45) ports	1

Storage

Card reader integrated *	✖

Features

Interactive *	✔
Noise level (economic mode)	29 dB
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish
Noise level *	33 dB

Multimedia

Built-in speaker(s) *	✔
RMS rated power	10 W
Number of built-in speakers	1

Design

Market positioning *	Presentation
Product type *	Short throw projector
Product colour *	White
Cable lock slot	✔
Cable lock slot type	Kensington

Power

Power source *	AC
Power consumption (typical) *	260 W
Power consumption (standby) *	0.5 W
AC input voltage	100 - 240 V

Ports & interfaces

Audio (L/R) in *	1
Serial interface type *	RS-232
PC Audio in	✔
PC Audio out	✔
VGA (D-Sub) ports quantity *	3
HDMI ports quantity *	2
Composite video in *	1
DVI port *	✘
AC (power) in	✔

Network

Ethernet LAN *	✔

Power

AC input frequency	50 / 60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Weight & dimensions

Width	296 mm
Depth	239 mm
Height	120 mm
Weight *	2.6 kg

Packaging content

Remote control included *	✔
Remote control type	IR
Batteries included	✔
Cables included	AC
Manual	✔

Logistics data

Quantity per pack	1 pc(s)
Harmonized System (HS) code	85286200

Ports & interfaces

Audio (L/R) in *	1
Serial interface type *	RS-232
PC Audio in	✔
PC Audio out	✔
VGA (D-Sub) ports quantity *	3
HDMI ports quantity *	2
Composite video in *	1
DVI port *	✘
AC (power) in	✔

Power

AC input frequency	50 / 60 Hz

4718755083808