

Samsung OM46B Digital signage flat panel 116.8 cm (46") LCD Wi-Fi 4000 cd/m² Full HD Black Tizen 5.0 24/7

Brand : Samsung

Product family: OMB

Product code:
LH46OMBEBGBXEN

Product name : OM46B



Samsung OM46B. Product design: Digital signage flat panel. Display diagonal: 116.8 cm (46"), Display technology: LCD, Display resolution: 1920 x 1080 pixels, Display brightness: 4000 cd/m², HD type: Full HD. Wi-Fi. Operating hours (hours/days): 24/7. Operating system installed: Tizen 5.0. Product colour: Black

Display		Design	
Panel type	VA	Panel mounting interface	400 x 400 mm
Display diagonal *	116.8 cm (46")	Bezel width (bottom)	1.99 cm
Display technology *	LCD	Bezel width (side)	1.99 cm
Display resolution *	1920 x 1080 pixels	Bezel width (top)	1.99 cm
Display brightness *	4000 cd/m ²	Performance	
HD type *	Full HD	TV tuner integrated	✗
Touchscreen *	✗	Operating hours (hours/days)	24/7
Native aspect ratio	16:9	HDCP	✓
Response time	6 ms	International Protection (IP) code	IP5X
Contrast ratio (typical)	6000:1	HDCP version	2.2
Dynamic contrast ratio marketing name	Mega Contrast	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	350 W
Viewing angle, vertical	178°	Power consumption (sleep)	0.5 W
Pixel pitch	0.53 x 0.53 mm	AC input voltage	100 - 240 V
Colour saturation	72%	AC input frequency	50 - 60 Hz
Horizontal scan range	15 - 135 kHz	Computer system	
Vertical scan range	24 - 75 Hz	Internal storage capacity	8 GB
RGB colour space	NTSC	Operating system installed	Tizen 5.0
Ports & interfaces		Weight & dimensions	
HDMI ports quantity *	2	Display width	1062 mm
HDMI version	2.0	Display depth	54.5 mm
HDMI input ports quantity	2	Display height	616.6 mm
DVI port *	✗	Display weight	18.2 kg
DisplayPorts quantity *	1	Packaging data	
DisplayPorts in	1	Package width	1189 mm
USB port *	✓	Package depth	158 mm
USB ports quantity	1	Package height	757 mm
Ethernet LAN *	✓	Package weight	23 kg
Ethernet LAN (RJ-45) ports	2	Operational conditions	
Wi-Fi *	✓	Operating temperature (T-T)	0 - 40 °C
Composite video out	1	Operating relative humidity (H-H)	10 - 80%
RS-232 interface	✓	Technical details	
RS-232C	✓	Audio in (mini jack)	✗
Infrared data port	✓	Other features	
Design		Audio output	Stereo Mini Jack
Product design *	Digital signage flat panel	Bluetooth	✗
Product colour *	Black		
VESA mounting *	✓		

Other features

Video out

Yes



8806094039474

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-NOV-2024. Prints or copies of Information are only valid on the printed Publication date