



Lindy 2m USB 4 240W Type C Cable, Anthra Line

Brand : Lindy

Product code: 36958

Product name : 2m USB 4 240W Type C Cable, Anthra Line

- Professional choice USB 4 Gen 3x2 Type C to C cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 40Gbps (backwards compatible to USB 3.2 , USB 2.0 and Thunderbolt 3)
- Supports USB Power Delivery up to 240 Watt and DisplayPort 2.0 Alternate Mode with single 8K or dual 4K@60Hz
- Triple shielded coaxial cable, gold plated contacts and nickel plated connectors
- 2 year warranty

2m USB 4 240W Type C Cable, Anthra Line

Lindy 2m USB 4 240W Type C Cable, Anthra Line. Cable length: 2 m. Connector 1: USB C, Connector 2: USB C, USB version: USB4 Gen 3x2, Maximum data transfer rate: 40 Gbit/s, Connector contacts plating: Gold, Product colour: Black



Features

USB version *	USB4 Gen 3x2
Connector 1 *	USB C
Connector 2 *	USB C
Connector 1 gender *	Male
Connector 2 gender *	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	23/30/34
Connector material	Nickel
Connector contacts plating	Gold
Cable jacket material	Thermoplastic elastomer (TPE)
Conductor material	Copper
Connector shielding	✓
Connector shield material	Copper
Maximum data transfer rate	40000 Mbit/s
Maximum data transfer rate	40 Gbit/s
Product colour *	Black
Cable type	Round cable
Plug and Play	✓
USB Power Delivery	✓
USB Power Delivery revision	3.1
USB Power Delivery up to	240 W
Maximum resolution	3840 x 2160 pixels

Features

Maximum refresh rate	60 Hz
Certification	RoHS, REACH, California Proposition 65 & UL

Weight & dimensions

Cable length *	2 m
Cable diameter	4.8 mm
Bend radius (min)	2.88 cm
Connector 1 dimensions (WxDxH)	30 x 12.4 x 6.5 mm
Connector 2 dimensions (WxDxH)	30 x 12.4 x 6.5 mm

Packaging content

Quantity per pack *	1 pc(s)
---------------------	---------

Sustainability

Sustainability compliance	✓
Sustainability certificates	UL ECOLOGO

Operational conditions

Operating temperature (T-T)	-20 - 40 °C
Storage temperature (T-T)	-40 - 80 °C

Certificates

UN number	\
-----------	---

Other features

Warranty period	2 year(s)
Compliance certificates	REACH, RoHS



4002888369589

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-NOV-2024. Prints or copies of Information are only valid on the printed Publication date