

ZYXEL

Zyxel GS1915-8EP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Brand : Zyxel

Product code: GS1915-8EP-GB0101F

Product name : GS1915-8EP

GS1915-8EP, 8-port GbE Smart Managed PoE Switch

Zyxel GS1915-8EP. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE.... Power connector: AC-in jack. Power over Ethernet (PoE)

Management features		Design	
Switch type *	Managed	LED indicators	✓
Switch layer	L2	Electromagnetic compatibility	LVD EN60950-1, BSMI CNS14336-1
Quality of Service (QoS) support	✓	Performance	
Web-based management	✓	Mean time between failures (MTBF)	1641000 h
System event log	✓	Power	
MIB support	RFC 1213 MIB II, RFC 2819, RFC 1215, RFC 1493	Power source *	AC
Ports & interfaces		AC input voltage	200 - 240 V
Basic switching RJ-45 Ethernet ports quantity *	8	Power consumption (max)	72 W
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
Gigabit Ethernet (copper) ports quantity	8	Power over Ethernet (PoE) *	✓
Power connector	AC-in jack	Power over Ethernet (PoE) ports quantity	8
Network		Total Power over Ethernet (PoE) budget	60 W
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Operational conditions	
10G support *	✗	Operating temperature (T-T)	0 - 40 °C
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Storage temperature (T-T)	-40 - 70 °C
Full duplex	✓	Operating relative humidity (H-H)	10 - 95%
Flow control support	✓	Storage relative humidity (H-H)	10 - 95%
Broadcast storm control	✓	Heat dissipation	245.52 BTU/h
Rate limiting	✓	Weight & dimensions	
Auto MDI/MDI-X	✓	Width	250 mm
VLAN support	✓	Depth	104 mm
Number of VLANs	8	Height	27 mm
Data transmission		Weight	620 g
Switching capacity *	16 Gbit/s	Packaging content	
Forwarding rate	11.9 Mpps	Cables included	AC
MAC address table *	8000 entries	Quick start guide	✓
Jumbo frames support	✓	User guide	✓
Jumbo frames	9000	Manual	✓
Packet buffer memory	0.525 MB	Packaging data	
Security		Package width	302 mm
IGMP snooping	✓	Package depth	227 mm
MAC address filtering	✓	Package height	64 mm
		Package weight	1.4 kg

Security		Certificates	
SSH/SSL support	✓	Certification	CE, FCC, C-Tick, Class A, Class B, BSMI CNS13438
Multicast features		Logistics data	
Multicast support	✓	Harmonized System (HS) code	85176990
Protocols			
Management protocols	SNMP v1,v2,v3, RMON (1,2,3,9)		
Design			
Product colour	Black		



4718937621941

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-NOV-2024. Prints or copies of Information are only valid on the printed Publication date