

# USB-C Multiport Adapter - USB-C Travel Docking Station with 4K HDMI - 60W Power Delivery Pass-Through, GbE, 2pt USB-A 3.0 Hub - Portable Mini USB Type-C Dock for Laptop

Product ID: DKT30CHPD



Turn your MacBook or Windows® laptop into a workstation, anywhere you go, with this USB-C™ multiport adapter with HDMI.

## Connect a UHD 4K HDMI Monitor

Connect your USB-C or Thunderbolt 3 laptop to a 4K 30Hz monitor, using this USB-C video adapter to create a dual-display workstation. Get more work done with an additional display, allowing you to multitask more efficiently or connect your laptop to an HDMI projector or TV for presentations in a boardroom.

## **Charge Your Laptop**

The portable laptop docking station features a USB-C Power Delivery port that lets you power and charge your USB-C laptop during a presentation or while you're working. It's perfect for port limited laptops with a single USB-C port. Even with the adapter connected to the laptop, you can still power and charge your laptop with a USB-C power adapter.

## **Enhance Productivity**

The 4K HDMI adapter gives you the connections you need to get more work done. You can connect peripherals like a flash drive or mouse using the two USB 3.0 Type-A ports. You can also add wired network connectivity with the Gigabit Ethernet port, making it ideal in areas without Wi-Fi.

DKT30CHPD is TAA compliant and is backed by a StarTech.com 3-year warranty and free lifetime technical support.

*Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery and DP Alt Mode.*

## Certifications, Reports and Compatibility



## Applications

- Connect to an external HDMI monitor for multitasking
- Deliver presentations on an HDMI TV or projector in a boardroom or classroom
- Connect to an HDMI TV in a hotel or hot desk space

## Features

- **4-IN-1 TRAVEL DOCK:** USB-C multiport adapter has 4K 30Hz UHD HDMI video output for a single display, 2x USB-A 3.0 (5Gbps) ports, Gigabit Ethernet (GbE), and 60W Power Delivery 2.0 charging pass through
- **EXTRA LONG CABLE:** The portable USB-C mini dock's 25cm (10 in.) attached cable provides extended reach to reduce port/connector strain on 2-in-1 devices or laptops on riser stands
- **WIDE DEVICE COMPATIBILITY:** USB C multiport adapter for USB-C & Thunderbolt 3 laptops, Ultrabooks, Chromebooks, tablets & phones for brands like HP, Dell, Lenovo, MacBooks, Surface and Samsung Galaxy
- **WIDE OPERATING SYSTEM COMPATIBILITY:** With automatic driver setup, this all-in-one USB 3.1 Gen 1 Type-C docking station supports Windows, macOS, Chrome OS, Android (Galaxy S9 & up, Pixel 3)
- **POWERED BY LAPTOP OR EXTERNAL ADAPTER:** This dock can draw power from the laptop USB bus or charge the laptop via PD-Passthrough if a USB-C power adapter is connected (12W for dock & 48W for charging)

|                                     |                             |   |
|-------------------------------------|-----------------------------|---|
| <b>Hardware</b>                     | Warranty                    | 3 Years   |
|                                     | 4K Support                  | Yes   |
|                                     | Bus Type                    | USB-C   |
|                                     | Chipset ID                  | VIA/VLI - VL813<br>VIA/VLI - VL100<br>Chrontel - CH7525A<br>ASIX - AX88179  |
|                                     | Displays Supported          | 1   |
|                                     | Fast-Charge Port(s)         | No  |
|                                     | Industry Standards          | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab<br>USB 3.0 - Backward compatible with USB 2.0 and 1.1   |
|                                     | <b>Performance</b>          | Auto MDIX   |
|                                     | Compatible Networks         | 10/100/1000 Mbps  |
|                                     | Full Duplex Support         | Yes   |
|                                     | Maximum Data Transfer Rate  | 5 Gbps (USB 3.0)<br>2 Gbps (Ethernet; Full-Duplex)  |
|                                     | Maximum Digital Resolutions | 4096 x 2160p @ 24Hz or 3840 x 2160p (HDMI) @ 30Hz<br>Lower resolutions are also supported.  |
|                                     | Type and Rate               | USB 3.0 - 5 Gbit/s  |
|                                     | UASP Support                | Yes   |
| <b>Connector(s)</b>                 | Connector Type(s)           | 1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Male<br><br>1 - HDMI (19 pin) Female<br><br>1 - RJ-45 Female<br><br>2 - USB Type-A (9 pin) USB 3.0 Female<br><br>1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Female   |
| <b>Software</b>                     | OS Compatibility            | Windows® 7, 8, 8.1, 10<br>Mac OS® 10.9 to 10.15<br>Chrome OS™   |
| <b>Special Notes / Requirements</b> | <b>Note</b>                 | Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 and DP alt mode.<br><br>The adapter can connect to a host laptop's USB-C port that doesn't support USB Power Delivery 2.0. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop. |

|                                 |                               |  |
|---------------------------------|-------------------------------|--|
|                                 |                               | <p>A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K)</p> <p>USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps.</p> <p>Your laptop might have specific charging requirements. For example, if your laptop requires exactly 60W of power and an adapter consumes some of the 60W, your laptop might not recognize that it is getting enough power. For more information about Power Delivery, refer to the manufacturer of your hardware.</p> |
|                                 | System and Cable Requirements | <p>A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode)</p> <p>Optional: USB-C power adapter (for example, your laptop's USB-C based power adapter)</p>  |
| <b>Power</b>                    | Power Delivery                | 60W  |
|                                 | Power Source                  | USB-Powered  |
| <b>Environmental</b>            | Humidity                      | 0~85% RH (Non-condensing)  |
|                                 | Operating Temperature         | 0°C to 50°C (32°F to 122°F)  |
|                                 | Storage Temperature           | -10°C to 65°C (14°F to 149°F)  |
| <b>Physical Characteristics</b> | Cable Length                  | 13.7 in [348 mm]   |
|                                 | Color                         | Black  |
|                                 | Material                      | Plastic  |
|                                 | Product Height                | 0.7 in [1.8 cm]  |
|                                 | Product Length                | 3.8 in [96 mm]   |
|                                 | Product Width                 | 2 in [51 mm]   |
|                                 | Weight of Product             | 2.3 oz [64 g]  |
| <b>Packaging Information</b>    | Package Height                | 1.6 in [41 mm]   |
|                                 | Package Length                | 8.3 in [21.2 cm]   |
|                                 | Package Width                 | 5.7 in [14.6 cm]   |
|                                 | Shipping (Package) Weight     | 7 oz [198 g]   |
| <b>What's in the Box</b>        | Included in Package           | <p>1 - USB-C multiport adapter</p> <p>1 - quick-start guide</p>  |

Product appearance and specifications are subject to change without notice.