

3 Port 2b 1a Low Profile 1394 PCI Express FireWire Card Adapter

Product ID: PEX1394B3LP



This 3 Port PCI Express FireWire card comes equipped with a low profile bracket for installation in small form factor PCs, and includes an optional full-size bracket for installation in a standard-sized PC case.

The FireWire card can be installed in a PCIe slot to add two IEEE1394b (FireWire 800 - 9 pin) ports and one IEEE1394a (FireWire 400 - 6 pin) port, providing broad compatibility with a wide range of FireWire devices (e.g. DV camcorders, external hard drives, digital cameras, etc.).

The 2x FireWire 800 and 1x FireWire 400 card features a native (single chip) PCI Express chipset, which provides faster, more reliable and cost-effective performance than expansion cards that utilize a "bridge" chip.

Certifications, Reports and Compatibility



Applications

- Add a high-speed FireWire port to a desktop without any FireWire support
- Connect a digital camera to a desktop with a PCI Express slot to download photos and video
- Connect a high-speed external hard drive to a PCI Express-enabled system

Features

- Two 9-pin FireWire 800 ports, each with transfer rates up to 800Mbps
- One 6-pin FireWire 400 port, each with transfer rates up to 400Mbps
- Includes full/standard profile installation bracket
- Built with a native PCI Express chipset, no bridge chip
- Internal power connector for high-powered FireWire devices
- Compliant with IEEE 1394b and backwards compatible with IEEE 1394a - 2000 as well as 1394-1995 standards
- Plug-and-Play and hot-swap compatible

| | | |
|-------------------------------------|-------------------------------|--|
| Hardware | Warranty | Lifetime |
| | Bus Type | PCI Express |
| | Card Type | Low Profile (SP bracket incl.) |
| | Chipset ID | LSI/Agere - FW643 |
| | Interface | FireWire 800 (1394b) |
| | Ports | 3 |
| Performance | Maximum Data Transfer Rate | 800 Mbps |
| | Type and Rate | FireWire 800 IEEE-1394b - 800 Mbit/s |
| Connector(s) | Connector Type(s) | 1 - PCI Express x1 Male |
| | External Ports | 1 - FireWire 400 (6 pin, IEEE 1394a) Female 2 - FireWire 800 (9 pin, IEEE 1394b) Female |
| | Internal Ports | 1 - SP4 (4 pin, Small Drive Power) Male |
| Software | OS Compatibility | Windows® 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server® 2003, 2008 R2, 2012, 2016 Mac OS® 10.6 to 10.12 Linux 3.5.x to 4.4.x <i>LTS Versions Only</i> |
| Special Notes / Requirements | System and Cable Requirements | PCI Express enabled computer with an available PCI Express x1 slot or higher |
| Environmental | Humidity | 0~90% RH |
| | Operating Temperature | 0°C to 70°C (32°F to 158°C) |
| | Storage Temperature | -20°C to 90°C (-4°F to 194°C) |
| Physical Characteristics | Product Height | 0.8 in [20 mm] |
| | Product Length | 3.5 in [90 mm] |
| | Product Weight | 1.4 oz [40 g] |
| | Product Width | 2.3 in [58 mm] |
| Packaging Information | Package Quantity | 1 |
| | Shipping (Package) Weight | 6.7 oz [190 g] |
| What's in the Box | Included in Package | 1 - PCI Express FireWire Card 1 - FireWire Cable 1 - Full Profile Bracket 1 - Software CD 1 - Instruction Manual |

Product appearance and specifications are subject to change without notice.