



> PRINT > COPY > SCAN > FAX

ECOSYS M8130cidn

COLOUR MULTIFUNCTIONAL
FOR A4/A3 FORMAT

FEATURE RICH COMPACT DESIGN



Low power consumption
saves energy.

HyPAS™ solution
platform enables
powerful customisations.

7" colour touch screen
and intuitive operation.

High durability:
200,000 maintenance
free prints.



This ECOSYS colour device suits all of your output requirements. It offers highly advanced functionality that is easily accessed by a colour touch panel using a simple wizard-style navigation. No matter if you print, copy, scan or fax in A4 or A3, colour or black and white, this compact device offers a range of paper handling options that will accommodate your individual document management requirements.



ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.

GENERAL

Technology: KYOCERA ECOSYS, Laser, Colour, HyPAS™ solution platform
Operation panel: 177.8 mm (7 inch) full-colour touch panel display, speaker for job notification
Type: Desktop
Engine speed: Up to 30/15 pages A4/A3 per minute in colour and black and white. Duplex print speed: 26 page per minute, A4. Duplex copy speed: 26 page per minute, A4
Resolution: 1200 x 1200 dpi (print), 600 x 600 dpi (scan/copy)
Warm-up time: Approx. 30 seconds or less
Time to first print: Approx. 6.5 seconds or less in black and white, 8.3 seconds or less in colour
Time to first copy: Approx. 7.4 seconds or less in black and white (DP), 9.3 seconds or less in colour (DP), Approx. 6.5 seconds or less in black and white (platen cover), Approx. 8.3 seconds or less in colour (platen cover)
CPU: ARM Cortex-A9 Dual core 1.2GHz
Memory: Standard 1.5 GB, max. 3GB
Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), optional Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO slots, for optional internal print server or SSD hard disc and for optional fax system, Slot for optional SD Card, NFC tag
Integrated accounting: 100 department codes
Dimensions (WxDxH): 590 x 590 x 753 mm (with standard Document Processor)
Weight: Approx. 79 kg (with standard Document Processor)
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption
 Printing: 600 W
 Copying: 600 W
 Low power mode: 40 W
 Ready mode: 70 W
 Sleep-mode: 0.5 W
Noise (sound pressure level: ISO 7779/ISO 9296)
 Copying/Printing in black and white: 53 dB (A)
 Copying/Printing in colour: 54 dB (A)
 Stand-by: 34 dB (A)
Safety standards: TUV/GS, CE
 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity:
 100-sheet multi-purpose tray, 60–256 g/m², A3, A4, A5, A6, B5, Ledger, Letter, Legal, Folio, Custom (98 x 148 to 297 x 432 mm), 500-sheet Standard universal paper cassette, 60–256 g/m², A3, A4, A5, B5, Ledger, Letter, Legal, Folio, Max. input capacity with options: 1,600 sheets
Duplex unit: Duplex as standard supports 60–220 g/m²
Standard reversing document processor: 50-sheets, A3, A4, A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm), Simplex scan 45–160 g/m², Duplex scan 50–120 g/m²
Output capacity: Max. 280 sheets; 250 sheets face-down (Main Tray) plus 30 sheets (standard Job Separator Tray)

PRINT FUNCTIONS

Controller language: PRE SCRI BE II e
Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XPS
Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 101 outline fonts (PCL 6, KPDL 3, Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)
Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality
Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

COPY FUNCTIONS

Max. original size: A3/Ledger
Continuous copying: 1–999
Zoom range: 25–400% in 1% steps
Preset magnification ratios: 5 Reductions / 5 Enlargements
Exposure mode: Auto, manual: 7 steps
Image adjustments: Text + Photo, Photo, Text, Map, Printed document
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through, ID card copy, Skip blank page

SCAN FUNCTIONS

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA, WSD scan
Scan speed: 50 ipm (300 dpi, A4, black and white), 50 ipm (300 dpi, A4, colour)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales per colour)
Max. scan size: A3, Ledger
Original recognition: Text, photo, text + photo, light text, optimised for OCR
File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u
Compression method: MMR/JPEG
Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Max. 33.6 kbps
Scanning speed: 2.0 seconds or less
Address book: 200 entries
Scanning density:
 Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi)
 Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi)
 Super fine: 8 dot/mm x 15.4 line/mm (200 x 400 dpi)
 Ultra fine: 16 dot/mm x 15.4 line/mm (400 x 400 dpi)
 Halftone: 256 grey scales

Maximum original size: A3, Ledger
Compression method: JBIG, MMR, MR, MH
Memory reception: 700 sheets or more
Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798
TK-8115K Toner Kit: Micro fine toner black for 12,000 pages A4
TK-8115C, TK-8115M, TK-8115Y: Micro fine toner cyan, magenta, yellow for 6,000 pages A4
 Capacity of starter toner is black 3,000 pages, cyan, magenta, yellow 1,500 pages A4
Staple: SH-10, 5000 x 3 staples

OPTIONS

Fax System 13
Paper handling
PF-470 Paper feeder: Max. 500 sheets; 60–163 g/m²; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)
PF-471 Paper feeder: Max. 1,000 sheets; 60–163 g/m²; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm)
DF-470* Paper feeder: Document finisher with AK-470, Max. 500 sheets A4; 60–163 g/m²; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm), 3 positions stapling up to 50 sheets A4 or 25 sheets A3
 *Bridge unit AK-470 is required for the use of DF-470
Security: Data security kit (E)
Memory upgrade: DDR3 1GB/2GB
HD-6: SSD 32 GB for easy document management
HD-7: SSD 128 GB for easy document management
SD card: for printing forms, fonts, logos, macro storage and for HyPAS™ applications
USB Flash Memory: Supports direct printing and scanning of PDF, XPS, TIFF, JPEG files via USB Host interface
UG-33: ThinPrint support
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available. The card holder is standard
Optional interface
IB-36: Wireless LAN (802.11b/g/n) with Wi-Fi Direct
B-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/1,000 BaseT
IB-51: Wireless LAN Interface (802.11b/g/n)
CB-470 Cabinet: Wooden desk with storage capacity, including castors (wheels)
CB-472 Cabinet: Metal desk with storage capacity, including castors (wheels)

WARRANTY

2-year warranty as standard. ** KYOCERA guarantees the drum and developer for 3 years or 200,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYO LIFE Up to 5-year on-site warranty extensions available for product and options.



KYOCERA Document Solutions (UK) Ltd
 Eldon Court, 75-77 London Road, Reading RG1 5BS
 Tel: 0118 931 1500, Fax: 0118 931 1108
www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country

YOUR KYOCERA BUSINESS PARTNER

