



# APC NetBotz Series

Monitor and protect your IT infrastructure with certainty.

[apc.com/netbotz](http://apc.com/netbotz)

Life Is 

**APC**<sup>™</sup>  
by Schneider Electric

# The industry's most comprehensive solution for your IT security and environmental monitoring needs

APC™ NetBotz™ is designed to protect your IT infrastructure against environmental threats and unauthorized access risks that can cause unexpected downtime.

Compute is quickly moving closer to where it is used at the Edge, increasing the risks of water damage, high temperature & humidity, fire or other conditions bringing down business-critical applications. Intentional or malicious access events not only threaten compute availability, but also leave enterprises vulnerable to costly compliance violations.

NetBotz series provides integrated sensing, surveillance<sup>1</sup> and badged rack-access control to help mitigate these risks through a wide array of intelligent sensors, camera<sup>1</sup> clip captures, configurable alerts and robust management options.

## Why should you consider NetBotz?



4MP HD camera support with video storage<sup>1</sup>



Badged access control



Wide array of intelligent sensors



Instant, highly customizable user-defined alerts



Highly scalable with expansion pods



Remote management with built-in network management



Seamless 3rd party IT infrastructure integration



Enhanced cyber security



Easy to deploy and configure

1. Camera pod is only available on the NetBotz 750 and 755 series models.

# NetBotz Portfolio Overview

## NetBotz 250



The cost-effective and essential sensing, access control and instant alerting for IT environments of all sizes where IT rack space is available. Supports up to 42 wired sensors, 47 wireless sensors and badged access for 2 rack doors.

Ideal environment: Data Center and Edge

## NetBotz 750



Integrated surveillance, sensing, access control and instant alerting for IT environments of all sizes where IT rack space is available. Supports up to 4 HD cameras, 78 wired sensors, 47 wireless sensors and badged access for 26 rack doors.

Ideal environment: Data Center and Edge

## NetBotz 755
















Integrated surveillance, sensing, access control and instant alerting for IT environments of all sizes where IT rack space is unavailable. Supports up to 4 HD cameras, 16 wired sensors, 47 wireless sensors and badged access for 2 rack doors.

Ideal environment: Edge

	NetBotz 250	NetBotz 755	NetBotz 750
Product series	NetBotz Rack Monitor	NetBotz Room Monitor	NetBotz Rack Monitor
Plug and play sensors	•	•	•
Embedded network management	•	•	•
Email/SNMP based instant alerts	•	•	•
EcoStruxure ready	•	•	•
Enhanced web UI experience		•	•
True private network support		•	•
3rd party IT integration		•	•
Pricing	\$	\$\$	\$\$\$
Sensors and pods (maximum number supported)			
HD camera pod 165	-	4	4
Integrated rack access handles	2	-	2
Universal wired sensors	42	16	78
Wireless sensors	47	47	47
Rack access pod 170	-	1	12
Sensor pod	6	2	12

# Sensors and Pods Overview

Sensors		
Type		Description
	Temperature	Provides real-time temperature data
	Humidity	Provides real-time humidity data
	Wireless	Available for temperature and humidity sensing (helps reduce the clutter and expense of cabling)
	Spot and Rope Leak	Provides early detection of fluid in your data center or network closet
	Door Switch	Monitors access to a room or rack
	Smoke	Detects smoke in IT spaces (supplements the existing fire safety system)
	Dry Contact	Connects to 3 <sup>rd</sup> party devices to provide critical monitoring
	Vibration	Detects vibration in racks that may indicate movement of IT assets
	0-5V	Connects to 3 <sup>rd</sup> party pressure sensors to help monitor liquids and gasses
Pods		
Type		Description
	Camera	Provides high definition surveillance with motion detection
	Rack Access	Provides badged access control for a rack
	Rack Sensor	Supports 6 additional sensors (rackmount)
	Room Sensor	Supports 4 additional sensors (wallmount)

For detailed sensor and pod compatibility information please refer to the compatibility chart on any NetBotz product page.

# NetBotz Management Solutions



## Built-in network management

### For remote access and management

Connect to your network and gain instant control

Built-in network management allows for secure connection and control of an individual NetBotz unit via web browser, command-line interface or SNMP. The configurable and highly customizable notification feature keeps you informed about problems as they occur.



## EcoStruxure IT

### Connecting hybrid IT environments for advanced insights

Cloud-based vendor-neutral monitoring with EcoStruxure™ IT

EcoStruxure IT monitors and protects your critical equipment, providing 24/7 visibility through live data, smart alarming and data-driven insights on the health of your connected assets directly to your smartphone.

When you upgrade to EcoStruxure™ Asset Advisor, remote troubleshooting is provided by the experts monitoring your connected assets 24x7.



## 3<sup>rd</sup> party infrastructure solution

### For better user experience and flexibility

Connect to your 3<sup>rd</sup> party central management software with ease<sup>1</sup>

APC NetBotz 750 and 755 series now provides simplest integrations into third party systems via REST API so you can manage your NetBotz without any roadblocks.

### 3<sup>rd</sup> party camera support<sup>1</sup>

APC NetBotz 750 and 755 series now allows you to pull in camera feeds from many third party vendors that support ONVIF<sup>2</sup>.

1. 3<sup>rd</sup> party integration and camera support is only available on the NetBotz 750 and 755 series models.

2. ONVIF Profile S cameras will not have full functionality of NetBotz 165 camera, including motion detection; learn more at [www.onvif.com](http://www.onvif.com)

# Web Interface Overview

The screenshot displays the NetBotz 750 web interface with a top navigation bar including 'Overview', 'Alarms', 'Devices', 'Rack Access', 'Wireless', and 'Settings'. The main content area is divided into several sections:

- Cameras:** Four camera feeds are shown, each with a status indicator (e.g., 'Motion Detected' or 'No Motion').
- Appliance:** A table listing various ports and their status:
 

Port	Label	Status	Value
1	Switched Outlet	Inactive	
2	Voltage Input 1	0 V	
3	Temperature 6	25.2 °C	47 % RH
4	Output 1	Inactive	
5	Output 2	Inactive	
6	Current Input 1	0 mA	
7	Current Input 2	0 mA	
- Appliance Rack Access:** Shows 'No Rack Doors'.
- Wireless:** Lists a 'Wireless Coordinator' with ID 2029000000BFA1A.
- Sensors:** Three sensor data points are shown:
 

NetBotz 150.1	Port	Label	Value	Unit
	1	Temperature 1	25.2 °C	54 % RH
NetBotz 150.2	1	Temperature 1	25 °C	54 % RH
NetBotz 150.3	1	Temperature 1	24.9 °C	52 % RH

Real-time alerts overview

Multiple camera feeds on a single screen

Real-time sensor data overview

The screenshot shows the 'Alarms' section of the NetBotz 750 web interface. It features a list of active alarms with filters for 'Critical', 'Warning', 'Informational', 'All', 'Actual', and 'Resolved'. A detailed view of a specific alarm is shown:

- Alarm:** High Temperature: Temperature 6
- Temperature:** 26.2 °C
- Threshold:** 1 Above threshold 20°C
- Start time:** Jun 22, 2020, 10:21:33 am
- Connected to Appliance:** Port 6

View active alarms in real-time to quickly respond to emergencies

The screenshot displays the 'Alarm Configurations' section of the NetBotz 750 web interface. It shows a table of configured alarms with columns for Name, Type, Description, and Action:

Name	Type	Description	Action
APC-9A1844Y00174_Camera1	Motion	Threshold equal to Motion Detected	Edit   Delete
APC-9A1844Y00189_Camera2	Motion	Threshold equal to Motion Detected	Edit   Delete
APC-9A1844Y00185_Camera2_gh	Motion	Threshold equal to Motion Detected	Edit   Delete
APC-9A1844Y00189_Camera3	Motion	Threshold equal to Motion Detected	Edit   Delete
APC-9A1844Y00189_Camera3_gh	Motion	Threshold equal to Motion Detected	Edit   Delete
APC-9A1844Y00189_Camera4	Motion	Threshold equal to Motion Detected	Edit   Delete
APC-9A1844Y00471_Camera4_gh	Motion	Threshold equal to Motion Detected	Edit   Delete
Default Contact	Contact	Threshold equal to Open	Edit   Delete
Default Door	Door	Threshold equal to Open	Edit   Delete
Default Humidity (High)	Humidity	1 Above threshold 50% RH	Edit   Delete
Default Humidity (Low)	Humidity	1 Below threshold 20% RH	Edit   Delete
Default Motion	Motion	Threshold equal to Motion Detected	Edit   Delete
Default Output Relay	Output Relay	Threshold equal to Active	Edit   Delete
Default Switched Outlet	Switched Outlet	Threshold equal to Active	Edit   Delete
Default Temperature (High)	Temperature	1 Above threshold 35°C	Edit   Delete
Default Temperature (Low)	Temperature	1 Below threshold 10°C	Edit   Delete
Default Temperature (Too High)	Temperature	1 Above threshold 32°C	Edit   Delete

User-configurable extensive alarm threshold options

# SKU Technical Specifications

	NBRK0250	NBRK0750	NBWL0755 NBWL0756 <sup>1</sup>
Product Series	NetBotz Rack Monitor	NetBotz Rack Monitor	NetBotz Room Monitor
Hardware			
Includes	NBRK0250 Device, Power Cord, Micro USB Cable, Mounting Gear, A-Link Terminator, Wireless Coordinator, Wireless Temperature Sensor, Wired Temperature & Humidity Sensor	NBRK0750 Device, Power Cord, Micro USB Cable, Mounting Gear, A-Link Terminator, Wireless Coordinator, Wireless Temperature Sensor, Wired Temperature & Humidity Sensor	NBWL0755/NBWL0756 Device, HD Camera Pod 165, Micro USB Cable, Wall Anchor, Mounting Gear, POE Injector NBAC0303NA2 <sup>1</sup>
External cameras supported	None	NetBotz Camera Pod 165, ONVIF Profile S Cameras <sup>2</sup>	
Universal wired sensors supported	Temp, Temp/Humidity, Door Contact, Smoke, Spot Leak, Vibration, Dry Contact	Temp, Temp/Humidity, Door Contact, Smoke, Spot Leak, Rope Leak, Vibration, Dry Contact, 0-5V	
Wireless sensors supported	Wireless Temp, Wireless temp/humidity, Wireless Coordinator/Router (NBWC100U only)		
Expansion pods supported	Rack Sensor Pod 150	Rack Sensor Pod 150, Room Sensor Pod 155, Rack Access Pod 170 <sup>3</sup>	
Communications and management			
Connectors and ports	(1)10/100 Base-T Public LAN, (6) APC Universal Sensor, (2) Access Control Handles, (2) Door Contact, (1) 12/24V control IO, (1) voltage relay, (1) USB ports, (2) A-link ports, (1) Wireless Coordinator Port, (1) Beacon Port, (1) Switched Outlet, (1) Mini-USB Console Port	(1) 10/100/1000 Base-T Public LAN, (6) APC Universal Sensor, (2) Access Control Handles, (2) Door Contact, (4) PoE Private Network Ports for Camera, (2) 4-20mA Sensor, (2) 12/24V relay IO, (2) USB ports, (2) Rope Leak, (2) A-link ports, (1) Wireless Coordinator Port, (1) Beacon Port, (1) Switched Outlet, (1) Micro-USB Console Port	(1) 10/100/1000 Base-T public LAN, (4) APC Universal Sensor, (1) PoE Private Network Ports for Camera, (2) 12/24V relay IO, (1) USB ports, (1) Rope Leak, (1) A-link ports, (1) Wireless Coordinator Port, (1) Micro-USB Console Port
Indicators	Power, Network Link		Power, Network Link, Temp and Humidity OLED screen
Protocols	A-Link, DHCP, DNS, HTTPS, SMTP, SNMP v1 and v3, SSHv2, TCP/IP, TLS 1.2		
Management interface	Google Chrome, Mozilla Firefox, StruxureWare Data Center Expert <sup>4</sup>	Google Chrome, Mozilla Firefox, REST API, StruxureWare Data Center Expert <sup>4</sup>	
Physical			
Dimensions H x W x D, inches (mm)	1.72 x 17.0 x 2.33 (44.0 x 432.0 x 59.0)	1.7 x 17.0 x 7.0 (43.5 x 432.0 x 178.0)	5.5 x 9.6 x 3.6 (140 x 244 x 91.28)
Shipping dimensions H x W x D, inches (mm)	2.6 x 17.8 x 8.9 (67 x 450 x 225)	4.75 x 21.0 x 12.5 (121.0 x 533.0 x 318.0)	4.75 x 21.0 x 12.5 (121.0 x 533.0 x 318.0)
Net weight, lb (kg)	2.80lbs (1.26kg)	5.40lbs (2.45kg)	3.44lbs (1.56kg)
Shipping weight, lb (kg)	6.50lbs (3.00kg)	9.20lbs (4.17kg)	8.20lbs (3.72kg)
Environmental			
Operating temperature	32 - 113 °F (0 - 45 °C)		
Storage temperature	5 - 149 °F (-15 - 65 °C)		
Relative humidity	10 - 95%		
Operating elevation	0 -10,000 ft (0-3,000 meters)		
Storage elevation	0-50,000 ft (0-15,000 meters)		
Conformance			
Regulatory approvals	CE; FCC 47 CFR Part 15 Class A, ICES-003 Class A, AS/NZS CISPR 22, VCCI Class A, Low Voltage Directive 2014/35/EC, EMC Directive 2014/30/EC, RoHS Directive 2011/65/EU, UL 60950-1, CAN/CSA No. 60950-1-03		
Standard warranty	2 years		

1. NetBotz Room Monitor 756 is NetBotz Room Monitor 755 with 120/240V PoE Injector

2. Motion detection and other features may be limited when using non-NetBotz ONVIF cameras. Learn more at [www.onvif.org](http://www.onvif.org)

3. The handle ports integrated with the NBRK0750 support only NBHN125 handle kits, which has different form factor from those included with NBP0171

4. Data Center Expert v7.7 or higher is required for video surveillance functionality with NetBotz 750 and 755

Life Is On



Visit [apc.com/netbotz](https://apc.com/netbotz) to learn more  
and explore the configurator tool.

132 Fairgrounds Rd  
West Kingston, RI 02892  
Phone: + 01 (401) 789-5735  
[www.apc.com](https://www.apc.com)

© 2020 Schneider Electric. All Rights Reserved. Schneider Electric | Life Is On, APC, and NetBotz are trademarks and the property of Schneider Electric SE, its subsidiaries, and affiliated companies. All other trademarks are the property of the respective owners.