

# IntelliSHOT<sup>®</sup> ePTZ Camera

## ePTZ CAMERA WITH AUTOFRAMING TECHNOLOGY

### ORDERING INFORMATION

#### Black

999-21100-000 (North America)

999-21100-001 (Europe/UK)

999-21100-009 (Australia/New Zealand)

#### White

999-21100-000W (North America)

999-21100-001W (Europe/UK)

999-21100-009W (Australia/New Zealand)



### OVERVIEW

The IntelliSHOT<sup>®</sup> professional camera makes video collaboration and streaming classes easy and effortless. Equipped with advanced IntelliFrame<sup>™</sup> technology, the IntelliSHOT ePTZ camera is the only auto-framing device that can be adjusted based on the room conditions and user's preferences. Vaddio's IntelliFrame technology is the culmination of years of research and engineering delivering the most precise and reliable autoframing experience.

Other cameras on the market that rely on facial recognition fail with facial coverings or falsely identify objects like posters on the wall as people. IntelliFrame uses a combination of exceptionally sensitive motion detection and complex algorithms to deliver smooth, accurate and reliable participant framing.

AV Integrators can now promise personalized video performance with every installation. Because IntelliFrame is adjusted via the web interface, it can be fine-tuned remotely by support staff.

The IntelliSHOT is a great choice for conference rooms as people expect great video when joining their Microsoft Teams Room or Zoom Room. The IntelliSHOT has two built-in beamforming microphones making it a great choice for simplifying audio endpoints in small to mid-size conference rooms.

The IntelliSHOT is PoE+ powered and the ethernet network connectivity allows you to manage and control the IntelliSHOT via our web-based user interface.

### FEATURES

- Advanced Intelligent Framing algorithms keep your participants in view
- 30x zoom with 70.2 degree field of view
- Simultaneous USB 3.0, HDMI and H.264 IP Streaming (RTSP or RTMP)
- Two integrated beamforming microphones with built-in Acoustic Echo Cancellation (AEC)
- Balanced audio line in and out
- Customizable autoframing experience
- Free Vaddio Deployment Tool for remote management, updates and more



A brand of **legrand**

COMMERCIAL AV BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

# Vaddio IntelliSHOT ePTZ Camera



## TECHNICAL SPECIFICATIONS

CAMERA & IMAGE	Outputs/protocols	IP (H.264), USB 3.0, HDMI 1.4, Balanced Audio
	Aspect ratio	IP (H.264) Streaming: 16:9, 3:2 and 4:3   HDMI: 16:9   USB: 16:9
	Resolutions/frame rates	Up to 1080p/30
	Image device	1/2.5-Type Exmor R CMOS sensor
	Pixels	8.51 million; (8.57M Total Megapixels)
	Lens and Horizontal FOV	30x zoom, 20x optical zoom + 10x IntelliZoom, 70.2° (Wide End) 31° (Tele End)
	Min. working distance	80mm (wide), 800mm (tele)
	Min. illumination	1.6 lux; 100+ lux recommended
	Backlight compensation	On/o
	Aperture/detail	16 steps
	Focusing system	Auto Focus / Manual Focus Mode / One-push Trigger Mode
	Gain	Auto / Manual (0 to 33 dB)
	White balance	Auto, ATW, Indoor, Outdoor, One-push, Manual
	S/N ratio	More than 50 dB
	Power	PoE+
	Remote management	Wireless Remote, web interface via Vaddio Device Controller, Telnet
	Enhanced Wide Dynamic Range	Yes
	Spotlight Compensation Mode	Yes
	Noise Reduction	Yes
	Presets	16 + Custom Home
Invertible	Yes	
Manual Tilt Range	-20°, +30°	
Warranty	3 years with 1 year Advanced Replacement	
AUDIO	Signal to Noise Ratio	64.3dB
	Cardioid Type	Omnidirectional
	Frequency Response	Flat
	Audio Processing (Internal Mics)	Acoustic Echo Cancellation
	Microphone Configuration	2x Beamforming
PHYSICAL & ENVIRONMENTAL	Weight	4.25 lbs (1.93 kg)
	Height	8.375" (21.27 cm)
	Width	6" (15.24 cm)
	Depth	4.5" (11.43 cm)
	Operating/storage temperature	0°C to +40°C (32°F to 104°F)
	Operating/storage humidity (relative)	20% to 80% RH, non-condensing

### WHAT'S IN THE BOX:

- IntelliSHOT ePTZ Camera (black or white)
- On-wall mount and hardware (black or white)
- Cable cover (black or white)
- 6 ft (1.8m) USB 3.0 cable, type A to B
- PoE+ power injector
- Vaddio Wireless Remote
- 3.3 ft (1m) Cat-5e cable
- Quick-Start Guide

THE ART OF EASY | [legrandav.com](http://legrandav.com)

USA 800.572.2011 [av.vaddio.support@legrand.com](mailto:av.vaddio.support@legrand.com)  
 EMEA +31.495.580.840 [av.emea.sales@legrand.com](mailto:av.emea.sales@legrand.com)  
 APAC +852.2145.4099 [av.asia.sales@legrand.com](mailto:av.asia.sales@legrand.com)

A brand of **legrand**

COMMERCIAL AV BRANDS

©2021 Legrand AV Inc. 210162 Rev B 5/21 Vaddio is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold