

APC Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts

Brand : APC

Product code: AP9613

Product name : Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts

Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts

APC Dry contact, Management Options, Dry Contact I/O Card, monitor external UPS environmental sensors, output relays, and input contacts:

The Dry Contact I/O Card provides 6 configurable output relays and 4 input contacts to monitor external triggers and initiate actions on external devices. The 2 Universal I/O (UIO) ports support optional environmental sensors and the Dry Contact I/O Accessory. The Dry Contact I/O Accessory provides 2 additional dry contact input and relay output interfaces. Connect the included USB cable to the Card and a PC to use the Configuration Utility user interface. Configure UPS settings and output relay, input contact and environmental sensor actions based on status changes or UPS events.



		Dry Contact I/O SmartSlot Card Configuration Utility				Schneider	
line ((edgecation	Distance	and			0	
- Universal 10 P							
- Input Care	H15	(and		(10.00)	-		
June 1	•	(144	. in		11		
agest 2	0	(Octord Real 1	· Abierra		(1)		
- CARDIA RVS	•	Total		(water		10.000	
Ordjud	•	Eislikut I mende	· Filmera		14 144		
- Environa		(April)		1000	-		
Tropolation of	ane :	Dub/Filler1	· (stangering		1		
Trepulators B		(sam	• Ni Artes				
Harning Room		(iim	* Newson				
Discountly Bullion		(1210			18		
Imposture		- Children	10	thomas .	100 C		
Starting.		(H)	14		10001		
	tion, Please and	Spiller you disk to supp					

Features		Weight & dimensions			
Product colour	Black	Depth	114 mm		
	REACH RoHS EN 55022 A, EN 55024, EN 61000-3-2, EN 61000-3-3, EN61000-4-2, EN61000-4-3, EN61000-4-4,	Height	38 mm		
Certification		Weight	210 g		
		Operational conditions			
	EN61000-4-6, FCC 15 A	Operating temperature (T-T)	0 - 40 °C		
Ports & interfaces		Storage temperature (T-T)	-15 - 65 °C		
Ethernet LAN (RJ-45) ports 2		Logistics data			
Weight & dimensions		Harmonized System (HS) code	85079080		
Width 121 mm					





731304293842

0731304293842



7313042938426

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.