iiyama

iiyama ProLite TF5539UHSC-W1AG computer monitor 139.7 cm (55") 3840 x 2160 pixels 4K Ultra HD LED Touchscreen Multi-user White

Brand : iiyama

Product name : TF5539UHSC-W1AG

Product family: ProLite

Product code: TF5539UHSC-W1AG

55 ", 3840 x 2160 @ 60Hz, IPS LED, 16:9, VGA, HDMI, DP, RS-232C, RJ-45, RMS 2x 8W, IP54, 1271.5x749.4x68 mm
iiyama ProLite TF5539UHSC-W1AG. Display diagonal: 139.7 cm (55"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: White

Display

Display diagonal *	139.7 cm (55")
Display resolution *	3840 x 2160 pixels
HD type *	4K Ultra HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✔
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	15
Display brightness	500 cd/m²
Response time *	8 ms
Screen shape *	Flat
Contrast ratio (typical) *	1100:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.78 million colours
Pixel pitch	0.315 x 0.315 mm
Viewable size, horizontal	121.2 cm
Viewable size, vertical	68.3 cm
Digital horizontal frequency	30 - 83 kHz
Display diagonal (metric)	139 cm
Surface hardness	7H

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘

Multimedia

Number of speakers	2
RMS rated power	16 W
Built-in speaker(s) *	✔

Ports & interfaces

HDMI ports quantity	2
HDMI version	1.4/2.0
DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	1
Audio output	1
HDCP	✔
RS-232C	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	600 x 400 mm
Wall mountable	✔

Power

Power consumption (typical) *	155 W
Power consumption (standby) *	1.5 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
European Product Registry for Energy Labelling (EPREL) code	431973

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C

Weight & dimensions

Width (without stand)	1271.5 mm
Depth (without stand)	68 mm
Height (without stand)	749.4 mm
Weight (without stand)	41 kg

Packaging data

Package width	1400 mm
Package depth	245 mm
Package height	930 mm
Package weight	46.5 kg

Multimedia			**Packaging content**	
Built-in microphone	✘		Cables included	DisplayPort, HDMI, LAN (RJ-45), USB
Built-in camera *	✘		**Other features**	
Design			International Protection (IP) code	IP54
Product colour *	White		Placement supported	Horizontal/Vertical
Housing material	Metal		Mean time between failures (MTBF)	50000 h
Glass thickness	4 mm		Ethernet LAN (RJ-45) ports	1
Ports & interfaces			**Logistics data**	
VGA (D-Sub) ports quantity	1		Harmonized System (HS) code	85285210
HDMI *	✔			

4948570118076