

2 Port PCI Express SATA 6 Gbps eSATA Controller Card - Dual Port PCIe SATA III Card - 2 Int/2 Ext

Product ID: PEXESAT322I



The PEXESAT322I PCI Express SATA III Controller Card (6 Gbps) gives you the option to add 2 internal or external SATA ports to your computer, through a single PCI Express (x1) card slot. The card features on board jumper selection, which enables you to configure the card to provide 2 internal or external SATA III ports, or one of each, as needed.

The SATA III card features Port Multiplier (PM) support on each port, which allows multiple drives to be connected over a single cable when necessary to maximize the number of SATA device connections while reducing the amount of cabling required.

The card is fully compliant with the SATA revision 3.0 specification (up to 6Gbps of data bandwidth), enabling you to utilize the speeds of high performance hard drives and Solid State Drives (SSD), as well as SATA-based optical drives (CD-ROM, DVD-ROM, Blu-Ray).

The PEXESAT322I SATA III Controller card is backed by our 2-year manufacturer warranty and free lifetime technical support.

Certifications, Reports and Compatibility





























Applications

- Upgrade an older PCIe-based system with SATA 6Gbps connectivity, to better utilize faster SATA drives
- Add more internal SATA ports to a computer system, for connecting additional storage drives and/or optical drives
- Add internal and/or external SATA III ports to a computer through a single PCI Express slot, with the option to change the available connections to external/internal, as needed based on updated system requirements or applications

Features

- HOGERE OPSLAGCAPACITEIT: Deze 2-port PCIe SATA en eSATA Controller Kaart biedt ondersteuning voor twee interne SATA of externe (eSATA) drives via PCI Express; Een kostenefficinte oplossing om de opslagcapaciteit van uw systeem te vergroten
- ASM1061 CONTROLLER: De SATA en eSATA controllerkaart heeft een speciale chipset en biedt twee schakelbare SATA- en eSATA 6Gbps-poorten via n x1 PCIe-slot; ondersteunt FIS-gebaseerde Port Multiplier, Command-based switching, NCQ en ATA/ ATAPI-commando's
- WIDE COMPATIBILITY: Supports Windows and standard SATA and eSATA SSDs (solid-state drives) and HDDs (hard drives); Supports SATA III (6 Gbps) and earlier revisions; Compliant with PCI Express 2.0
- CONVENIENT SETUP: This 2-port SATA/eSATA controller card installs in a full or low-profile PCIe slot; Compatible with PCIe x1, x4, x8, or x16 slots; Includes full-profile (pre-installed) & low-profile brackets, and 7-pin SATA cable
- DE KEUZE VAN DE IT-PRO: deze 2-port PCIe SATA en eSATA Controller Kaart werd ontworpen en gemaakt voor IT-professionals en geniet van gratis levenslange 24/5 meertalige technische ondersteuning

Hardware		
	Warranty	2 Years
	Ports	2
	Interface	eSATA & SATA
	Bus Type	PCI Express
	Card Type	Standard Profile (LP bracket incl.)
	Port Style	Integrated on Card
	Chipset ID	ASMedia - ASM1061
Performance		
	Type and Rate	SATA III (6 Gbps)
	Port Multiplier	Yes





Number of Ports That Support Port Multiplier

2 (can use 2 PM at a time)

Number of Drives Supported Through Port

Multiplier

1 to 8

Bootable Yes

48-bit LBA support

Hardware Raid Supported No

ATAPI Support Yes

Connector(s)

Connector Type(s) 1 - PCI Express x1

Internal Ports 2 - SATA (7 pin, Data)

External Ports 2 - eSATA (7 pin, Data)

Software

OS Compatibility Windows XP, Vista, 7, 8, 8.1, 10, 11

Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019

Environmental

Operating Temperature 0C to 50C (32F to 122F)

Storage Temperature -20C to 60C (-4F to 140F)

Humidity 5% ~ 85% RH

Physical Characteristics

> Color Black

Material Steel

Product Length 4.8 in [12.1 cm]

Product Width 3.6 in [92 mm]

Product Height 0.8 in [2 cm]

Weight of Product 1.7 oz [48 g]

Packaging





Information

Package Quantity 1

Package Length 5.7 in [14.4 cm]

Package Width 6.8 in [17.3 cm]

Package Height 1.2 in [30 mm]

Shipping (Package) Weight

5.4 oz [152 g]

What's in the Box

Included in Package 1 - PCIe SATA Controller

1 - SATA Cable

1 - Low Profile Bracket

1 - Driver CD

1 - Instruction Manual



^{*}Product appearance and specifications are subject to change without notice.