

POWERSCAN™ PD9630

Everlasting handheld industrial scanners for 1D/2D barcode reading with top flexibility



ULTRA-RUGGED WITH NEW BALANCED ERGONOMICS!

The PowerScan family of bar code readers are the ultimate industrial handheld scanners designed and constructed to withstand the toughest environmental conditions. The PowerScan PD9630 imagers have an ultra-rugged design, an ergonomic shape with well-balanced weight to reduce operator stress during daily activities and an intuitive aiming system, allowing the highest first-pass reading rate while reducing unnatural wrist movement.

THREE OPTIC OPTIONS TO FULFILL ANY CUSTOMER NEED

The PowerScan PD9630 area imagers are available in three different optics, to satisfy any customer need. The **Standard Range** optic is ideal for most of the applications requiring barcode reading at intuitive distance; the **High Performance** optic adds the capability to decode high density barcodes together with an increased depth of field on standard 1D/2D codes; the **Document Capture** model is thought for Wide Angle code reading and Document Capture applications.

THE BEST FEEDBACK TO THE OPERATOR

The PD9630 area imagers also feature Datalogic's exclusive 3 Green Lights (3GL™) for superior good-read feedback together with a loud beeper and vibration. The 'Green Spot' technology directly on the code and dual Good Read LEDs increase visibility at any angle. All models have multi-interface capabilities featuring the most popular interfaces: RS-232, USB and offer an optional Ethernet for standard or industrial uses.

Datalogic's Motionix™ motion-sensing technology detects the natural actions of the operator to automatically switch the scanner into the desired scanning mode (handheld or presentation scanning).

FEATURES

- Snappy omnidirectional reading from contact to over 2.0 m / 6.5 ft
- Datalogic's new instinctive 'frame' aimer
- Water and Particulate Sealing Rating: IP65 and IP67
- 10 million trigger hits
- White light illumination
- Datalogic's 3GL™ (3 Green Lights) technology and loud beeper for good-read feedback
- Datalogic's Motionix™ motion-sensing technology
- Ergonomic shape provides hours of tireless data collection for the user
- Supports 1D, stacked and 2D codes, postal codes and image capture
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI.

INDUSTRY APPLICATION

- **Manufacturing Shop Floor:**
 - Work-in-Progress
 - Sub-Assembly
 - Component Tracking
 - Quality Control
 - Time and Cost Analysis
 - Machine Replenishment /Configuration
 - Line Inventory Control
- **Warehouse and Logistic Centers:**
 - Shipping / Receiving
 - Parcel Preparation
 - Picking / Put Away
 - Automatic Sorting Back-Up
 - End of Line Sorting



TECHNICAL SPECIFICATIONS

DECODING CAPABILITY

1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot code
Postal Codes	Australian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post
Digital Watermarking	Digimarc Barcodes (PD9630-HP and PD9630-DC)

ELECTRICAL

Current	Operating (Typical): PD9630-SR: 200mA @ 5V; 120mA @ 12V PD9630-HP/ PD9630-DC: 280mA @ 5V / 140mA @ 12V Standby/Idle (Typical): 187mA @ 5V / 92mA @ 12V
Input Voltage	5 - 30 VDC ± 5%

ENVIRONMENTAL

Ambient Light	0 - 100,000 lux
Drop Resistance	Withstands 50 drops from 2.5 m / 8.2 ft @ 20 °C / 68 °F; Withstands 50 drops from 2.0 m / 6.6 ft @ -20 °C / -4 °F
Tumble	5,000 @ 1 m / 3.3 ft
Trigger Resistance	Withstands 10 million hits
ESD Protection (Air Discharge)	20 kV
Humidity (Non-Condensing)	0 - 95%
Particulate and Water Sealing	IP67 and IP65
Temperature	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F

INTERFACES

Interfaces	RS-232 / USB
-------------------	--------------

PHYSICAL CHARACTERISTICS

Colors Available	Yellow/Black
Dimensions H x L x W	19.0 x 14.0 x 7.9 cm / 7.5 x 5.5 x 3.1 in
Weight	318.0 g / 11.2 oz

READING PERFORMANCE

Imager Sensor	PD9630-SR/HP: 1280 x 800 PD9630-DC: 1280 x 800 color sensor
Light Source	Aiming: 630 - 680 nm VLD Illumination: White LED reading light
Print Contrast Ratio (Minimum)	15%
Reading Angle	Pitch: +/- 52°; Roll (Tilt): 360°; Skew (Yaw): +/- 52°
Field Of View	SR and HP: 38° H, 24° V DC: 50° H, 33° V
Reading Indicators	Beeper (Adjustable Tone and Volume); Datalogic's 3GL™ (Three Green Lights) technology for good-read feedback; Datalogic 'Green Spot' on the Code; Dual Good Read LEDs; Vibration.
Resolution (Maximum)	PD9630-SR/PD9630-DC: 1D Codes: 3 mil; 2D Codes: 6 mil PD9630-HP: 1D Codes: 2.5 mil; 2D Codes: 4 mil

DECODING CAPABILITY

Typical Depth of Field	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.	
	PD9630-SR	PD9630-HP
	Code 128	Code 128
	5 mils: 6.4 to 30.9 cm / 2.5 to 12.2 in	2.5 mils: 6.3 to 11.5 cm / 2.5 to 4.5 in
	20 mils: 4 to 103.7 cm / 1.6 to 40.8 in	5 mils: 3.8 to 41 cm / 1.5 to 16.1 in
	40 mils: 5.5 to 175 cm / 2.2 to 68.9 in	20 mils: 4 to 157 cm / 1.6 to 61.8 in
	EAN/UPC 13 mils: 4 to 67.5 cm / 1.5 to 26.5 in	40 mils: 5.5 to 242.9 cm / 2.1 to 95.6 in
	DataMatrix 10 mils: 6 to 30 cm / 2.5 to 11.8 in	EAN/UPC 13 mils: 4 to 120 cm / 1.5 to 40.2 in
	PD9630-DC	PDF417 10 mils: 0.5 to 46.1 cm / 0.2 to 18.1 in
	5 mils: 3.1 to 39.7 cm / 1.2 to 15.6 in	DataMatrix 4 mils: 6.5 to 9.3 cm / 2.5 to 3.6 in
	20 mils: 3.5 to 119.1 cm / 1.3 to 46.9 in	DataMatrix 10 mils: 4.2 to 32 cm / 1.6 to 12.6 in
	DataMatrix 10 mils: 4.2 to 30.2 cm / 1.6 to 11.8 in	

SAFETY & REGULATORY

Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use. The Regulatory Addendum for this product can be referred to for a complete list of certifications.
Environmental Compliance	Complies to China RoHS; Complies to EU RoHS; Complies to R.E.A.C.H.
Laser Classification	Caution Laser Radiation - Do not stare into beam CDRH Class II; IEC 60825 Class 2
LED Classification	IEC 62471 LED Class: Exempt

UTILITIES

Datalogic Aladdin™	Datalogic Aladdin configuration program is available for download at no charge.
OPOS / JavaPOS	OPOS and JavaPOS Utilities are available for download at no charge.
Remote Host Download	Available on request

WARRANTY

Warranty	3-Year Factory Warranty
-----------------	-------------------------

ACCESSORIES

Cases / Holsters



HLS-P080 Universal Holster (HLS-8000)

Mounts / Stands



STD-P096 Stand, Hands-free (STD-9600)



HLD-P096 Desk/Wall Holder (HLD-9600)



7-0404 Industrial Take-Up Reel

POWERSCAN™ PM9600

Everlasting handheld industrial scanners for 1D/2D barcode reading with top flexibility



ULTRA-RUGGED WITH NEW BALANCED ERGONOMICS!

The PowerScan family of bar code readers are the ultimate industrial handheld scanners designed and constructed to withstand the toughest environmental conditions. The PowerScan 9600 imagers have an ultra-rugged design, an ergonomic shape with well-balanced weight to reduce operator stress during daily activities and an intuitive aiming system, allowing the highest first-pass reading rate while reducing unnatural wrist movement.

MOBILITY ENHANCES PRODUCTIVITY

The PowerScan 9600 cordless model further enhances the operator efficiency and safety with Datalogic's STAR Cordless System™. Accurate power management allows long lasting battery life to always guarantee more than one shift of intensive scanning. The PowerScan 9600 scanner features Datalogic's Wireless Charging System. Based on inductive-charging technology, Datalogic's Wireless Charging System eliminates battery contacts and pins that often get dirty, bent, or broken over time – and this removes a key point of failure for devices used in industrial and retail functions.

MODULARITY WITH THE BEST FLEXIBILITY

The BC9600 base/charger has a modular design and is available with multiple interface plug-ins for standard and industrial communication, such as RS-232, USB, Standard Ethernet and Industrial Ethernet protocols.

FEATURES

- Snappy omnidirectional reading on 1D, stacked and 2D codes, postal codes
- Standard Range and High Performance models
- Water and Particulate Sealing Rating: IP65 and IP67; Cradle IP65; 10 million hits trigger
- Center of gravity design
- Modular cradle design allowing interface expansion
- White light illumination
- High visibility OLED Display with 4-Keys /16-Keys keypad options
- Datalogic's 3GL™ (3 Green Lights) technology and loud beeper for good-read feedback
- Datalogic's Motionix™ motion-sensing technology
- Wireless Charging reducing total cost of ownership
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI.

INDUSTRY APPLICATION

- **Manufacturing Shop Floor:**
 - Work-in-Progress
 - Sub-Assembly
 - Component Tracking
 - Quality Control
 - Time and Cost Analysis
 - Machine Replenishment /Configuration
 - Line Inventory Control
- **Warehouse and Logistic Centers:**
 - Shipping / Receiving
 - Parcel Preparation
 - Picking / Put Away
 - Automatic Sorting Back-Up
 - End of Line Sorting



TECHNICAL SPECIFICATIONS

CORDLESS COMMUNICATIONS	
Datalogic STAR Cordless System™	Radio Frequency: 433 MHz; 910 MHz; Effective Radiated Power: 433 MHz: < 10 mW; 910 MHz: < 50 mW; Point-to-Point/Multi-Point Configuration; Max. Readers per Radio Receiver: 16; Two Way Communications. Radio Range (Open Air): 433 MHz: 150 m / 492 ft low speed; 100 m / 328 ft high speed 910 MHz: 230 m / 754 ft low speed; Frequency hopping; 180 m / 590 ft high speed

DECODING CAPABILITY	
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code; Dot code
Postal Codes	Australian Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Portuguese Post; Postnet; Royal Mail Code (RM4SCC); Swedish Post
Stacked Codes	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites
Digital Watermarking	Digimarc Barcodes (HP and DC models)

ELECTRICAL	
Battery	Battery Type: Lithium-Ion: 3350 mAh Charge time @ 12 VDC: 2.5 hours to charge up to 95%, 3.2 hours to charge 100%, External Power. Reads per charge: 80,000
Current	Charging (Typical) < 15 W Scanner only: 480 mA @ 3.7 V (Operative) Cradle only: 150 mA @ 5 V (Operative)
Input Voltage	Host powered: 5V DC ± 5% or 10 - 30 VDC External power supply: 10 - 30 VDC ± 5%

ENVIRONMENTAL	
Ambient Light	0 - 100,000 lux
Drop Resistance	Withstands 50 drops from 2.5 m / 8.2 ft @ 20 °C / 68 °F; Withstands 50 drops from 2.0 m / 6.6 ft @ -20 °C / -4 °F
Trigger Resistance	Withstands 10 million hits
ESD Protection (Air Discharge)	20 kV
Humidity (Non-Condensing)	0 - 95%
Particulate and Water Sealing	IP67 and IP65; Cradle IP65 (specific models)
Temperature	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F Charging: 0 to 40 °C / 32 to 104 °F nominal; 0 to 35 °C / 32 to 95 °F ideal

INTERFACES	
Interfaces	RS-232 / USB / Keyboard Wedge Multi-Interface / Ethernet and Industrial Protocols

PHYSICAL CHARACTERISTICS	
Colors Available	Yellow/Black
Dimensions H x L x W	19.8 x 14.0 x 7.9 cm / 7.8 x 5.5 x 3.1 in
Display	PM9600-D/DK. 1.8" OLED graphic display; Font Dimensions: User selectable.
Keypad	PM9600-D: 4 Keys, PM9600-DK: 16 Keys; Configurable
Weight	PM9600-XX: 425 g / 15.0 oz PM9600-DXX: 445 g / 15.7 oz PM9600-DKXX: 455 g / 16.0 oz

READING PERFORMANCE	
Imager Sensor	1280 x 800 pixels
Light Source	Aiming: 630 - 680 nm VLD Illumination: White LED reading light
Print Contrast Ratio (Minimum)	15%
Reading Angle	Pitch: +/- 52°; Roll (Tilt): 360°; Skew (Yaw): +/- 52°
Field Of View	SR and HP: 38° H, 24° V
Reading Indicators	Beeper (Adjustable Tone and Volume); Datalogic's 3GL™ (Three Green Lights) technology for good-read feedback; Datalogic 'Green Spot' on the Code; Dual Good Read LEDs; Vibration.
Resolution (Maximum)	SR: 1D Codes: 3 mil; 2D Codes: 6 mil HP: 1D Codes: 2.5 mil; 2D Codes: 4 mil





READING RANGES	
Typical Depth of Field	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.
SR Models Code 128	HP Models Code 128
5 mils: 6.4 to 30.9 cm / 2.5 to 12.2 in	2.5 mils: 6.3 to 11.5 cm / 2.5 to 4.5 in
20 mils: 4 to 103.7 cm / 1.6 to 40.8 in	5 mils: 3.8 to 41 cm / 1.5 to 16.1 in
40 mils: 5.5 to 175 cm / 2.2 to 68.9 in	40 mils: 5.5 to 242.9 cm / 2.1 to 95.6 in
EAN/UPC 13 mils: 4 to 67.5 cm / 1.5 to 26.5 in	EAN/UPC 13 mils: 4 to 120 cm / 1.5 to 40.2 in
DataMatrix 10 mils: 6 to 30 cm / 2.5 to 11.8 in	PDF417 10 mils: 0.5 to 46.1 cm / 0.2 to 18.1 in
	DataMatrix 10 mils: 4.2 to 32 cm / 1.6 to 12.6 in

SAFETY & REGULATORY	
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use. The Regulatory Addendum for this product can be referred to for a complete list of certifications.
Environmental Compliance	Complies to China RoHS; Complies to EU RoHS; Complies to R.E.A.C.H.
Laser Classification	Caution Laser Radiation - Do not stare into beam CDRH Class II; IEC 60825 Class 2
LED Classification	IEC 62471 LED Class: Exempt

UTILITIES	
Datalogic Aladdin™	Datalogic Aladdin configuration program is available for download at no charge.
OPOS / JavaPOS	OPOS and JavaPOS Utilities are available for download at no charge.

WARRANTY	
Warranty	3-Year Factory Warranty

ACCESSORIES

<p>Base Stations / Chargers</p>  <p>BC9630 Base station/charger Multi-Interface BC9631 Base station/charger Multi-Interface, IP65</p>	<p>Battery</p>  <p>RBP-PM96 Removable battery</p>	<p>Multi-Battery Charger</p>  <p>MC-P096-M2 Multi Battery Charger 2 slots MC-P096-M4 Multi Battery Charger 4 slots MC-P096-E2 Extension modules 2 slots</p>	<p>Holder</p>  <p>HLD-P096 Desk/Wall Holder (HLD-9600)</p>
---	---	---	--