

AXIS M5075-G PTZ Camera

Palm-sized PTZ camera with 5x optical zoom and wireless I/O

AXIS M5075-G is a discreet, palm-sized PTZ camera designed to fit in anywhere. It delivers sharp, detailed video in HDTV 1080p/2 MP resolution. PTZ functionality with 5x optical zoom and 12x digital zoom allows you to benefit from sweeping overviews and zoom in to get the details. This plug & play solution offers wireless I/O connectivity with up to 32 Z-Wave[®] devices (six in VMS) in a system setup, for instance using on/off commands. Featuring a built-in microphone, it also includes analytics such as scream detection to alert you whenever a scream is detected in the camera's proximity.

- > [PTZ with 5x optical zoom, 12x digital zoom](#)
- > [Autofocus and WDR](#)
- > [Built-in analytics](#)
- > [Zipstream with H.264/H.265](#)
- > [Z-Wave for smart home devices](#)



AXIS M5075-G PTZ Camera

Models	AXIS M5075-G EUR AXIS M5075-G JP AXIS M5075-G US	Event conditions	Audio: audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption, storage health issues detected I/O: digital input, I/O Z-Wave, manual trigger, virtual input MQTT subscribe PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: average bitrate degradation, day-night mode, live stream open, tampering
Camera		Event actions	Day-night mode I/O MQTT publish Overlay text Preset positions Recordings Status LED WDR mode Z-Wave Notification: email, HTTP, HTTPS, TCP and SNMP trap Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email
Image sensor	1/2.8" progressive scan RGB CMOS	Data streaming	Event data
Lens	Varifocal. 2.2–11.0 mm, F1.4–F2.5 Horizontal field of view: 14°–71° Vertical field of view: 8°–40° Autofocus	Built-in installation aids	Leveling assistant, pixel counter
Minimum illumination	Color: 0.1 lux at 30 IRE F1.4	Analytics	
Shutter speed	1/17000 s to 2 s	Applications	Included AXIS Video Motion Detection, audio detection, active tampering alarm, gatekeeper, AXIS Scream Detection, AXIS Removed Object Detection Support for additional applications if the device is used with compatible accessories. For more information, contact your Axis partner. Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Pan/Tilt/Zoom	Pan: ±179°, 100°/s Tilt: 90°, 100°/s Zoom: 5x optical, 12x digital 256 preset positions, control queue, on-screen directional indicator, set new pan 0°, autofocus area, focus recall	General	
System on chip (SoC)		Casing	IP51-rated plastic casing, clear dome Color: white NCS S 1002-B For repainting instructions, go to the product's support page. For information about the impact on warranty, go to axis.com/warranty-implication-when-repainting .
Model	ARTPEC-7	Sustainability	PVC free, BFR/CFR free
Memory	1024 MB RAM, 512 MB Flash	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.4 W, max 9.5 W
Video		Connectors	RJ45 10BASE-T/100BASE-TX PoE
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High profile H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Resolution	1920x1080 to 320x180 (16:9)	Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–90% RH (non-condensing)
Frame rate	Up to 50/60 fps (50/60 Hz) in all resolutions	Storage conditions	-30 °C to 60 °C (-22 °F to 140 °F) Humidity 5–95% RH (non-condensing)
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 Video streaming indicator	Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A Safety CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1 Environment IEC/EN 60529 IP51 Radio AXIS M5075-G EUR: EN 300220-1, EN 300220-2, EN 301489-1, EN 301489-3, EN 62479, TEC AXIS M5075-G US: FCC Part 15 Subpart C, ISED AXIS M5075-G JP: Radio Law Network NIST SP500-267
Image settings	Saturation, contrast, brightness, sharpness, WDR, white balance, day/night threshold, local contrast, tone mapping, exposure mode, exposure zones, compression, rotation: 0°, 180°, barrel distortion correction, text and image overlay, polygon privacy masks		
Audio			
Audio streaming	One-way		
Audio encoding	24 bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate		
Audio input	Built-in microphone		
Network			
Security	Password protection, IP addressing, HTTPS encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot		
Supported protocols	IPv4, IPv6, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , HTTP/2, TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf) Z-Wave Plus™ v2		
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S and ONVIF [®] Profile T; specification at onvif.org		
Onscreen controls	Day/night shift Video streaming indicator Focus recall zone Privacy masks		

Dimensions	Ø130 x 63 mm (Ø5.1 x 2.5 in)
Weight	380 g (0.84 lb)
Included accessories	AXIS M50 Mounting Kit, Installation Guide, Windows decoder 1-user license
Optional accessories	AXIS M50 Clear Dome Cover A For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms

Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
-----------	---

Warranty	5-year warranty, see axis.com/warranty
----------	--

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

[axis.com/environmental-responsibility](https://www.axis.com/environmental-responsibility)