## Key **Features**

- 165Hz refresh rate delivers fluid, tear-free visuals
- Rapid 1ms (MPRT) response time for crisp movements
- QHD 1440p resolution
- AMD FreeSync™ Premium prevents screen tearing
- 1500R curved screen for a perfect balance of immersion and comfort



## Product **Description**

With an immersive curved screen and 165Hz refresh rate, the ViewSonic VX2718-2KPC-MHDJ provides a stunning viewing experience. The monitor has been designed with a 1500R curved and borderless panel for an immersive experience. A high 165Hz refresh rate delivers smooth animations with minimal input lag while AMD FreeSync™ Premium virtually eliminates screen tearing and stuttering for a fluid gaming experience. With 1ms MPRT response time, the monitor delivers unprecedented screen quality and speed. VX2718-2KPC-MHDJ is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications, such as watching movies, editing, or playing video games. In addition, a DisplayPort and two HDMI inputs offer flexible connectivity for both general use and entertainment.

Visit Us www.viewsonic.com

	napo.//www.viewoonk	J. O.
DISPLAY		El
Display Size (in.):	27	F
Viewable Area (in.): Panel Type:	27 VA Technology	T W
Resolution:	2560 x 1440	١
Resolution Type:	QHD (Quad HD)	١
Static Contrast Ratio:	4,000:1 (typ)	(
Dynamic Contrast Ratio:	80M:1	W
Light Source:	LED	1
Brightness:	250 cd/m² (typ)	1
Colors:	16.7M	(
Color Space Support:	8 bit (6 bit + FRC)	D
Aspect Ratio:	16:9	F
Response Time (MPRT):	1ms	F
Viewing Angles:	178º horizontal, 178º vertical	F
Backlight Life (Hours):	30000 Hrs (Min)	D
Curvature:	1500R	F
Refresh Rate (Hz):	165	F
Adaptive Sync:	FreeSync	F
Blue Light Filter:	Yes	G
Flicker-Free:	Yes	F
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102%	
Dival Cira	size (Typ)	 
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	
Surface Treatment:  COMPATIBILITY	Anti-Glare, Hard Coating (3H)	F
PC Resolution (max):	2560x1440	ı
Mac® Resolution (max):	2560x1440	١
PC Operating System:	Windows 11 certified; macOS tested	(
Mac® Resolution (min):	2560x1440	_
CONNECTOR		
3.5mm Audio Out:	1	
HDMI 2.0:	2	
DisplayPort:	1	
Power in:	DC Socket (Center Positive)	
AUDIO		
Internal Speakers:	2Watts x2	
POWER		
Eco Mode (Conserve):	22W	
Eco Mode (optimized):	26W	
Consumption (typical):	31W	
Consumption (max):	35W	
Voltage:	AC 100-240V	
Stand-by:	0.5W	
Power Supply:  ADDITIONAL HARDWARE	External Power Adaptor	
Kensington Lock Slot:	1	
CONTROLS	•	
Physical Controls:	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)	
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu	
OPERATING CONDITIONS		
Temperature:	32°F to 104°F (0°C to 40°C)	
Humidity (non-condensing):	20% to 90%	
WALL MOUNT		
VESA Compatible:	75 x 75 mm	
NPUT SIGNAL		
Frequency Horizontal:	HDMI (v2.0): 30 ~ 222KHz, DisplayPort (v1.4): 30 ~ 243KHz	
Frequency Vertical:	HDMI (v2.0): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 165Hz	
VIDEO INPUT Digital Sync:	TMDS - HDMI (v2.0), PCI-E -	
	DisplayPort (v1.4)	

ERGONOMICS	
Height Adjust (mm):	130
Tilt (Forward/Back):	-5° / 20°
WEIGHT (IMPERIAL)	
Net (lbs):	9.4
Net Without Stand (lbs):	7.3
Gross (lbs):	13.8
WEIGHT (METRIC)	
Net (kg):	4.3
Net Without Stand (kg):	3.3
Gross (kg):	6.3
DIMENSIONS (IMPERIAL) (W	XHXD)
Packaging (in.):	27 x 21.4 x 6.1
Physical (in.):	24 x 16.92~22.04 x 8.9
Physical Without Stand (in.):	24 x 14.3 x 2.9
DIMENSIONS (METRIC) (WXI	HXD)
Packaging (mm):	<b>HXD)</b> 687 x 543 x 156
, , ,	•
Packaging (mm):	687 x 543 x 156
Packaging (mm): Physical (mm):	687 x 543 x 156 611 x 430~560 x 226
Packaging (mm): Physical (mm): Physical Without Stand (mm):	687 x 543 x 156 611 x 430~560 x 226
Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL	687 x 543 x 156 611 x 430~560 x 226 611 x 363 x 75 CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO,
Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations:	687 x 543 x 156 611 x 430~560 x 226 611 x 363 x 75  CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA  VX2718-2KPC-MHDJ x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC
Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations: PACKAGE CONTENTS:	687 x 543 x 156 611 x 430~560 x 226 611 x 363 x 75  CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA  VX2718-2KPC-MHDJ x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1  Please dispose of in accordance with
Packaging (mm): Physical (mm): Physical Without Stand (mm): GENERAL Regulations: PACKAGE CONTENTS: Recycle/Disposal:	687 x 543 x 156 611 x 430~560 x 226 611 x 363 x 75  CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA  VX2718-2KPC-MHDJ x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1  Please dispose of in accordance with local, state or federal laws.  *Warranty offered may differ from

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.