

SD4849Pv USB-C Triple Video Driverless Docking Station with 100W Power Delivery

Part Number: K37060EU, EAN Code: 5028252633475 | K37060UK, EAN Code: 5028252633482

Work on three screens quickly and easily If you're looking for an easy-to-use plug-and-play USB-C docking solution that offers speed, power and the flexibility to connect up to three monitors, the SD4849Pv USB-C Triple Video Driverless Docking Station is the ideal solution. No drivers, downloads or updates necessary - just plug it in and go. 100W Power Delivery keeps your laptop charged, while 10Gbps transfer speed ensures productivity is never compromised. With thirteen ports in all, you'll have the flexibility to add multiple devices without additional dongles or adapters.

Features include:

- · Driverless USB-C connectivity
- 10Gbps data transfer speeds
- 100W Power Delivery (PD 3.0)
- Universal Windows compatibility
- Numerous video ports
- 10Gbps data transfer speeds

- 13-port design with5 USB ports
- SD and Micro UHS-I SD 3.0 card readers
- Vertical design
- Free Kensington DockWorks™
 Software
- Three-year warranty

SD4849Pv USB-C Triple Video Driverless Docking Station with 100W Power Delivery

Part Number: K37060EU, EAN Code: 5028252633475 | K37060UK, EAN Code: 5028252633482



SD4849Pv USB-C Triple Video Driverless Docking Station with 100W Power Delivery

Part Number: K37060EU, EAN Code: 5028252633475 | K37060UK, EAN Code: 5028252633482



Driverless, USB-C Connectivity with 100W Power Delivery (PD 3.0)

No driver installation, download or update required - just plug and play. 100W Power Delivery charges most laptops at maximum speed.



Universal Windows Compatibility

Connects seamlessly to any USB-C laptop running Windows 10 and above.



Numerous Video Ports

With 2 x HDMI 2.0 ports, 1 x DP1.4++ port and 1 x VGA port to support legacy monitors, select the right connections and resolutions for your needs.



10Gbps Data Transfer Speeds

Supporting ultra-fast and efficient data transfer, this docking station includes a 1m USB-C to USB-C 3.2 Gen2 cable for flexible placement.



13-Port Design with 5 USB Ports

The front features 1 x USB-C 3.2 Gen2 port (up to 5V/1.5A/10Gbps), 2 x USB-A 3.2 Gen2 ports (up to 5V/0.9A/10Gbps), a combo audio port and SD and Micro SD UHS-I 3.0 card readers. The rear features 2 x USB-A 2.0 ports (ideal for keyboards and mice), 1 x Gigabit Ethernet port and four video ports (2 x HDMI 2.0 ports, 1 x DP1.4++ port and 1 x VGA port).



SD and Micro SD UHS-I 3.0 Card Readers

Transfer files fast, using the builtin SD and Micro SD card readers. No need for additional adapters and accessories to transfer hi-res photos and video footage.



Vertical Design

Maximises desktop space.



Free Kensington DockWorks™ Software and Three-Year Warranty

DockWorks™ WiFi Auto-Switch guarantees the fastest, most reliable internet connection.

MAC Address ID Pass-Through and Reset, together with Device Connection Monitoring give IT managers maximum network monitoring and visibility. A three-year warranty lets you rest assured knowing you're covered by Kensington.

SD4849Pv USB-C Triple Video Driverless Docking Station with 100W Power Delivery

Part Number: K37060EU, EAN Code: 5028252633475 | K37060UK, EAN Code: 5028252633482

	Systems Supported	All Laptops with USB-C port (must support USB-C Alt mode)
	Operating Systems Supported	Windows® 10 or above
	Plug & Play	Yes
	Software	n/a
	System Resource Requirement	CPU: Intel® Core™ i5 6th generation or above Memory: 8Gb or above GPU: Intel® HD Graphics 620 or above
	Additional Software Information	DockWorks (Windows 10+)
	USB-C Power Delivery	PD3.0, 5V/ 9V/ 15V/ 20V@5A (up to 100W)
USB Interface		
	Type of USB Connector	USB-C Connector
	Host Connector	Support USB3.2 Gen2 Type-C with USB-C Alt mod
USB Connections		
	Ports	Front Panel: -1 x Power Button -1 x USB-C 3.2 Gen2 (up to 5V/1.5A) -2 x USB-A 3.2 Gen2 (up to 5V/0.9A) -1 x SD/Micro SD 3.0 card reader (UHS-I) -1 x Audio Combo Jack Back Panel: -1 x USB-C Host Port (up to 100W Charging) -2 x HDMI 2.0 -1 x DP1.4++ / 1 x VGA -1 x 1Gbps Ethernet
Network Connections		- 2 x USB-A 2.0 (up to 5V/0.9A)
	Ethernet Port	RJ45
	Compatible Ethernet Speeds	10/100/1000 Mbps
Host Connectivity		**************************************
——————————————————————————————————————		Hab a little B little A document
	Host Docking Connector	USB-C with Power Delivery up to 100W

SD4849Pv USB-C Triple Video Driverless Docking Station with 100W Power Delivery

Part Number: K37060EU, EAN Code: 5028252633475 | K37060UK, EAN Code: 5028252633482

Video Connections

Video Connectors	1 x DisplayPort v1.4 ++ 2 x HDMI 2.0
Maximum Resolution Supported	Refer to table

	1X <u> </u>	
≅	DP1.2	DP1.4 (DSC ON)
HDMI DP++	3840*2160 @ 30Hz	3840*2160 @ 60Hz
VGA	1080p @ 60Hz	

	2X 🛄 🛄	
△	DP1.2	DP1.4 (DSC ON)
HDMI HDMI	1080p @ 60Hz	3840*2160 @ 60Hz
DP++ HDMI	1080p @ 60Hz	3840*2160 @ 60Hz
HDMI	— 1080p @ 60Hz	3840*2160 @ 60Hz
VGA		1080p @ 60Hz

	зх 🔲 🖵 🖵	
△	DP1.2	DP1.4 (DSC ON)
HOM HOM	1600*900 @ 60Hz	3840*2160 @ 30Hz
HDM HDM	1600*900 @ 60Hz	3840*2160 @ 30Hz
ICI VGA		1080p @ 60Hz

Audio Connections

	Audio Connectors	1 x 3.5mm audio combo jack
	Audio Channels Supported	Stereo LR
LED Indicator		
	Blue LED	Power indicator
Material Specifications		
	Exterior	Enclosure: PC + ABS with texture
	Bottom	Metal Base Plate: Sheet metal
	Product Colour	PMS Black
Other Features		
	Kensington Security Slot	Kensington Security Slot
Product Dimensions		
	Unit Weight	0.6kg (1.32lbs)
	Unit Dimensions without Peripherals	68 x 115 x 190mm (2.67 x 4.52 x 7.48") WDH
	Enclosure Colour & Material	PMS Black, PC ABS
	Desktop Footprint	78cm² (12.12sq.in)

SD4849Pv USB-C Triple Video Driverless Docking Station with 100W Power Delivery

Part Number: K37060EU, EAN Code: 5028252633475 | K37060UK, EAN Code: 5028252633482

Packaging	Dimensions
-----------	------------

Packaging Style	Bulk Package
Packaging Dimensions	210 x 125 x 90mm (8.26 x 4.92 x 3.54")
Packaging Weight	1.63kg (3.59lbs)
Packaging Content	1 x SD4849Pv Dock 1 x 1m USB-C cable 1 x Power Supply Unit (Power Cord varies by different SKUs) 1 x Instruction Guide 1 x Warranty Card 1 x Compliance Sheet
Master Carton	4
ental	
Power Adapter Rating	Input: 100-240V; 2.5A / Output: 20V DC 9A (180W)
Relative Humidity	55% RH operating temperature @ 25°C
Operating Temperature	0 to 45°
Storage Temperature	0 to 60°
gulatory, and Warranty	
Country of Origin	China
Certifications & Compliance	FCC, IC, CE, RCM, VCCI, UKCA, CB, RoHS, ACCO RSL
Warranty	3-Year Limited - worldwide
Multiple SKUS	Bulk Package (K37060EU/UK)
	Packaging Dimensions Packaging Weight Packaging Content Master Carton ental Power Adapter Rating Relative Humidity Operating Temperature Storage Temperature gulatory, and Warranty Country of Origin Certifications & Compliance Warranty



