



## StarTech.com 4-Port Gigabit Midspan - PoE+ Injector - 802.3at/af

**Brand :** StarTech.com

**Product code:** POEINJ4G

**Product name :** 4-Port Gigabit Midspan - PoE+ Injector - 802.3at/af



StarTech.com 4 Port Gigabit Midspan - PoE+ Injector - 802.3at and 802.3af - Wall-mountable Power over Ethernet Midspan

StarTech.com 4-Port Gigabit Midspan - PoE+ Injector - 802.3at/af. Type: Network transmitter, Maximum transfer distance: 100 m, Data transfer rate: 2000 Mbit/s. Cabling technology: 10/100/1000Base-T(X), Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u. Product colour: Black, Housing material: Steel, LED indicators: PoE, Power. AC input voltage: 100 - 240 V, Power consumption (max): 120 W, Output voltage: 52 V. Width: 70 mm, Depth: 94 mm, Height: 26 mm



Performance		Power	
Type *	Network transmitter	Output current	2.31 A
Maximum transfer distance *	100 m	Power over Ethernet (PoE)	✓
Data transfer rate	2000 Mbit/s	Power plug type	Type M
Auto MDIX IEEE	✓	<b>Operational conditions</b>	
Auto-negotiation	✓	Operating temperature (T-T)	0 - 50 °C
Duplex system	Full	Storage temperature (T-T)	-10 - 70 °C
Plug and Play	✓	Operating relative humidity (H-H)	5 - 95%
Mean time between failures (MTBF)	50000 h	<b>Weight &amp; dimensions</b>	
<b>Network</b>		Width	70 mm
Cabling technology	10/100/1000Base-T(X)	Depth	94 mm
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u	Height	26 mm
<b>Ports &amp; interfaces</b>		Weight	204 g
Ethernet LAN (RJ-45) ports	8	<b>Packaging content</b>	
Power over Ethernet (PoE) ports quantity	4	Cables included	AC
DC-in jack	✓	Manual	✓
<b>Design</b>		AC adapter included	✓
Product colour	Black	<b>Packaging data</b>	
Housing material	Steel	Package width	180 mm
LED indicators	PoE, Power	Package depth	305 mm
Certification	CE, FCC	Package height	90 mm
<b>Power</b>		Package weight	1.63 kg
AC input voltage	100 - 240 V	<b>Certificates</b>	
Power consumption (max)	120 W	Compliance certificates	RoHS
Output voltage	52 V	<b>Logistics data</b>	
		Harmonized System (HS) code	85176990



0065030859752



065030859752

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.