



## DELL S-Series S4112 Managed L2/L3 1U Black

Brand : DELL

Product family: S-Series

Product code: 210-AOYR



Product name : S4112

- 1U, L2/L3, 840Gbits, 630Mpps
- 12 x 10GbE SFP+, 3 x 100GbE QSFP28
- OS10
- L2/L3, 12 x 10GbE SFP+, 3 x 100GbE QSFP28, 1U, 2 x PSU, OS10



[DELL S-Series S4112 Managed L2/L3 1U Black:](#)

### Flexible, powerful and optimized

Designed for flexibility and high performance for today's demanding modern workloads and applications.

DELL S-Series S4112. Switch type: Managed, Switch layer: L2/L3. Switching capacity: 840 Gbit/s.

Networking standards: IEEE 802.3. Rack mounting, Form factor: 1U

Management features		Design	
Switch type *	Managed	Form factor	1U
Switch layer	L2/L3	Product colour	Black
Quality of Service (QoS) support	✓	Ventilation system	Front-to-back airflow
Configuring Location Settings (CLI)	✓	Number of fans	3 fan(s)
Ports & interfaces		Safety UL/CSA 60950-L Second Edition, EN 60950-1 Second Edition, IEC 60950-1 Second Edition Including all National Deviations and Group Differences, EN 60825-1 Safety of Laser Products Part1: Equipment Classification Requirements and User's Guide, EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fibre Communications Systems, FDA Regulation 21 CFR 1040.10 and 1040.11	
SFP module slots quantity	1		
SFP+ module slots quantity	12		
QSFP+ module slots quantity	3		
Network			
Networking standards *	IEEE 802.3		
10G support *	✓		
VLAN support	✓		
Data transmission		Power	
Switching capacity *	840 Gbit/s	Power supply included *	✓
Throughput	630 Mpps	Number of power supply units	2
Latency (10-100 Mbps)	800 µs	AC input voltage	100 - 240 V
Multicast features		AC input frequency	50 - 60 Hz
Multicast support	✓	Power consumption (typical)	90 W
Protocols		Power consumption (max)	180 W
GARP VLAN Registration Protocol (GVRP)	✓	Power over Ethernet (PoE)	
Design		Power over Ethernet (PoE) *	✗
Rack mounting *	✓	Operational conditions	
Stackable *	✓	Operating temperature (T-T)	5 - 40 °C
		Storage temperature (T-T)	-40 - 65 °C
		Operating relative humidity (H-H)	5 - 85%
		Storage relative humidity (H-H)	5 - 95%
		Heat dissipation	614 BTU/h
Weight & dimensions			
		Weight	3.76 kg
Logistics data			
		Harmonized System (HS) code	85176990



5397184124581



0884116417644



884116417644

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.