

ATEN OL1500HV uninterruptible power supply (UPS) Doubleconversion (Online) 1.5 kVA 1500 W 8 AC outlet(s)

Brand : ATEN Product code: OL1500HV

Product name: OL1500HV

Professional Online UPS

ATEN OL1500HV. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. AC outlet types: C14 coupler, IEC 320, Power plug: C13 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount/Tower, Product colour: Black, Rack capacity: 2U. Width: 880 mm, Depth: 438 mm, Height: 410 mm







Features		Battery				
Output power capacity * 1.5 kVA Output power * 1500 W Waveform * Sine Input operation voltage (min) * 110 V	1500 W Sine 110 V	Typical backup time at half load Charging current Hot-swap battery Cold start Replacement battery cartridge	10.3 min 12 A			
Input operation voltage (max) *	300 V	Design				
Input frequency * Output frequency Output voltage regulation Maximum current Response time Efficiency Input power factor Output power factor Crest factor ECO mode	40/70 Hz 50/60 Hz 1% 7.2 A 0 ms 97% 0.99 1 3:1	Form factor * Rack capacity Cable length Cooling type Built-in fan Product colour * Display type LED indicators Certification	Rackmount/Tower 2U 1.8 m Active Black LCD CE			
Emergency Power Off (EPO)	,	Operational conditions				
Noise level Ports & interfaces AC outlet types	se level 50 dB ts & interfaces outlet types C14 coupler, IEC 320	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -20 - 50 °C 20 - 90% 10 - 95%			
Power plug AC outlets quantity	C13 coupler 8 AC outlet(s)	Technical details				
USB port	✓ oathot(o)	Compliance certificates	RoHS			
Serial interface	✓	Weight & dimensions				
Serial interface type Emergency Power Off (EPO) connector	ency Power Off (EPO)	Width Depth	880 mm 438 mm			
Battery		Height Weight	410 mm 14.3 kg			
Battery technology	Sealed Lead Acid (VRLA)	Packaging data				
Battery capacity Battery voltage	9 Ah 12 V	Rack mount kit	✓			
Number of batteries supported	3 2.96 min	Cables included Manual	Power load cable, RS-232, USB cable ✓			

	_	_	:_	. :		_	_	
ᆫ	u	ч	13	u	cs	u	а	La

Harmonized System (HS) code

85078000

