

## ASUS ZenBeam S2 data projector Standard throw projector DLP 720p (1280x720) White

**Brand :** ASUS

**Product code:** 90LJ00C2-B01070

**Product name :** ZenBeam S2



- Up to 500 lumens light output with 720p native resolution, 100% NTSC color saturation short throw lens provides 40"@1m to 120"@3m projection
  - As a portable power backup (6000mAh) to charge mobile devices (ECO mode: 3.5 hours)
  - Fast 3 sec. Auto focus and 2D Keystone adjustment with Corner Correction
  - Offer a comprehensive set of connectivity: USB-C (signal input and power delivery), USB output, wireless mirroring, and HDMI
  - Palm size and lightweight (497g)
- 0.3" DLP, R/G/B LED, 1280 x 720, 500 lumens, 100%(NTSC), 5 V, 6000 mAh, HDMI, USB-C, USB Type A, 3.5mm Mini-Jack

ASUS ZenBeam S2. Projection technology: DLP, Projector native resolution: 720p (1280x720), Native aspect ratio: 16:9. Light source type: LED, Service life of light source: 30000 h, Lamps quantity: 1 lamp(s). Focus: Auto, Offset: 100%. Noise level: 32 dB. RMS rated power: 2 W

Projector		Multimedia	
Supported aspect ratios	16:9	Built-in speaker(s) *	✓
Screen size compatibility *	1524 - 3048 mm (60 - 120")	RMS rated power	2 W
Projection distance	1.5 - 3 m	Number of built-in speakers	1
Projection technology *	DLP	Design	
Projector native resolution *	720p (1280x720)	Market positioning *	Portable
Native aspect ratio *	16:9	Product type *	Standard throw projector
Number of colours	16.78 million colours	Product colour *	White
Light source		Power	
Light source type *	LED	Power source *	Battery
Service life of light source *	30000 h	Power consumption (typical) *	65 W
Lamps quantity	1 lamp(s)	Power consumption (standby) *	0.5 W
Lens system		Battery capacity	6000 mAh
Focus *	Auto	Operational conditions	
Throw ratio	1.12	Operating temperature (T-T)	0 - 40 °C
Offset	100%	Operating relative humidity (H-H)	20 - 90%
Video		Weight & dimensions	
3D *	✗	Width	120 mm
Ports & interfaces		Depth	120 mm
USB 2.0 ports quantity *	1	Height	35 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Weight *	497 g
Headphone outputs	1	Package width	224 mm
HDMI ports quantity *	1	Package depth	142 mm
DVI port *	✗	Package height	190 mm
Network		Package weight	1.6 kg
Smart TV *	✗	Packaging content	
Ethernet LAN *	✗	Manual	✓
Wi-Fi *	✗	Logistics data	
Features		Harmonized System (HS) code	85286200
Noise level *	32 dB		



4718017558730

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-NOV-2024. Prints or copies of Information are only valid on the printed Publication date