PHILIPS

Philips S Line 222S1AE/00 computer monitor 54.6 cm (21.5") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips **Product family:** S Line **Product code:** 222S1AE/00

Product name : 222S1AE/00

222S1AE LCD monitor

Philips S Line 222S1AE/00 computer monitor 54.6 cm (21.5") 1920 x 1080 pixels Full HD LCD Black:

Philips S Line monitor gives essential features for daily productivity and work comfortably. Virtually frameless with crisp FHD for an extended and clear view. EasyRead and Eye comfort with TUV certified to reduce eye fatigue.
Philips S Line 222S1AE/00. Display diagonal: 54.6 cm (21.5"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black

Display

Display diagonal *	54.6 cm (21.5")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Backlight type	W-LED
Touchscreen *	✘
Display brightness (typical)	250 cd/m²
Response time *	4 ms
Display surface	Matt
Anti-glare screen	✔
Screen shape *	Flat
Supported graphics resolutions	1280 x 720 (HD 720), 1360 x 768 (WXGA), 1920 x 1080 (HD 1080)
Supported video modes	720p, 768p, 1080p
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	50000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.24795 x 0.24795 mm
Pixel density	102 ppi
Horizontal scan range	30 - 85 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	47.6 cm
Viewable size, vertical	26.8 cm
Digital horizontal frequency	30 - 85 kHz

Ergonomics

Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Height adjustment	13 cm
Pivot	✔
Pivot angle	-90 - 90°
Swivelling	✔
Swivel angle range	-180 - 180°
Tilt adjustment	✔
Tilt angle range	-5 - 25°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Number of OSD languages	21
Plug and Play	✔
LED indicators	Operation, Stand-by

Power

Energy efficiency class (SDR) *	E
Energy consumption (SDR) per 1000 hours *	16 kWh
Power consumption (typical) *	11.8 W
Power consumption (standby) *	0.3 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	9.7 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Display

Digital vertical frequency	48 - 75 Hz
Display diagonal (metric)	54.6 cm
DDC/CI	✔
Haze rate	25%
Surface hardness	3H
Colour gamut standard	sRGB
Colour gamut	78%
sRGB coverage (typical)	102%
NTSC coverage (typical)	78%
Display sRGB	✔

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
VESA Adaptive Sync support	✔
Component video sync	Separate sync, Sync-on-green (SOG)
Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia

Number of speakers	2
RMS rated power	2 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Design

Market positioning *	Business
Product colour *	Black
Frameless design	✔
Front bezel colour	Black
Detachable stand	✔
Feet colour	Black

Ports & interfaces

Built-in USB hub *	✘
VGA (D-Sub) ports quantity	1
DVI port	✔
DVI-D ports quantity	1
HDMI *	✔
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Audio input	✔
Audio output	✔
Headphone out *	✔
Headphone outputs	1
Headphone connectivity	3.5 mm
PC Audio in	✔
HDCP	✔
HDCP version	1.4
DC-in jack	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm

Power

European Product Registry for Energy Labelling (EPREL) code	413328

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m

Weight & dimensions

Width (with stand)	489 mm
Depth (with stand)	205 mm
Height (with stand)	443 mm
Weight (with stand)	4.3 kg
Width (without stand)	489 mm
Depth (without stand)	50 mm
Height (without stand)	295 mm
Weight (without stand)	2.5 kg

Packaging data

Package width	565 mm
Package depth	380 mm
Package height	184 mm
Package weight	7.11 kg
Package type	Box

Packaging content

Stand included	✔
Cables included	VGA, HDMI, DisplayPort, Audio (3.5mm), AC
Manual	✔
Bundled software	SmartControl

Sustainability

Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	PVC/BFR, Mercury

Other features

Exterior finish type	Textured
Picture enhancement	SmartImage
Recyclable packaging material	100%
Regulatory Approvals	CB; EPA; TUV/GS; TUV Ergo; SEMKO; CU-EAC; EAEU RoHS; UKRAINIAN; CE Mark; FCC Class B; ICES-003; TUV Eye Comfort certified
Heavy metals free	Hg (mercury)
EasyRead mode	✔
LowBlue mode	✔
Compliance certificates	RoHS
Mean time between failures (MTBF)	70000 h
Certification	CB, EPA, TUV/GS, TUV Ergo, SEMKO, CU-EAC, EAEU RoHS, UKRAINIAN, CE Mark, FCC Class B, ICES-003, TUV Eye Comfort certified

Recycling data

Post-consumer recycled plastic	85%

Logistics data

Harmonized System (HS) code	85285210

8712581767259