ZYXEL

Zyxel GS1900-24E Managed L2 Gigabit Ethernet (10/100/1000) 1U Black

Brand : Zyxel

Product code: GS1900-24E-GB0103F

Product name : GS1900-24E

- Start up button
- VLAN
- QoS
- Link aggregation

24-port GbE, 24, 100/1000 Mbps, 48 Gbps, 35.7 Mpps, 525 K byte, 8 K MAC, 9 K byte, 100 - 240 V AC, 50/60 Hz, 15.1 W, 267 x 162 x 42 mm, 1.56 kg, GB

Zyxel GS1900-24E. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 8000 entries, Switching capacity: 48 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE.... Power connector: AC-in jack. Wall mountable, Rack mounting, Form factor: 1U

Management features	
Switch type *	Managed
Switch layer	L2
Quality of Service (QoS) support	✓
Web-based management	✓
System event log	✓
MIB support	RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9),RFC 1215 generic traps, RFC 1493 bridge, Zyxel private common MIB

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	24
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Power connector	AC-in jack

Network	
Networking standards *	IEEE 802.1D, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support *	✗
Port mirroring	✓
Full duplex	✓
Flow control support	✓
Link aggregation	✓
Spanning tree protocol	✓
Ethernet LAN data rates	10,100,1000 Mbit/s
MAC address auto-learning supported	✓
VLAN support	✓
Virtual LAN features	Stacked VLAN, VLAN mapping

Data transmission	
Switching capacity *	48 Gbit/s

Design	
Form factor	1U
Product colour	Black
Reset button	✓
LED indicators	✓
Wall mountable	✓

Performance	
Mean time between failures (MTBF)	804.714 h

Power	
Power source *	AC
Power supply included *	✓
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	15.1 W

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✗

Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 95%
Storage relative humidity (H-H)	10 - 95%
Heat dissipation	51.49 BTU/h

Weight & dimensions	
Width	267 mm
Depth	162 mm
Height	42 mm
Weight	1.56 kg

Packaging content	
Cables included	AC
Rack mount kit	✓

Data transmission	
Forwarding rate	35.7 Mpps
MAC address table *	8000 entries
Store-and-forward	✓
Jumbo frames support	✓
Jumbo frames	9000
Packet buffer memory	0.525 MB

Security	
DHCP features	DHCP client
IGMP snooping	✓
Security algorithms	802.1x RADIUS
MAC address filtering	✓
Static port security	✓
SSH/SSL support	✓
Password protection	✓
Authentication type	RADIUS, TACACS+

Design	
Rack mounting *	✓
Stackable *	✓

Packaging data	
Package type	Box
Package width	325 mm
Package depth	223 mm
Package height	71 mm
Package weight	2.05 kg

Certificates	
Certification	EMC ■ CE, FCC, C-Tick, Class A (GS1900-24/24EP/24HPv2/48/ 48HPv2) ■ CE, FCC, C-Tick, Class B (GS1900-8/8HP/10HP/16/24E) ■ BSMI CNS13438 • Safety ■ LVD EN60950-1 ■ BSMI CNS14336-1 ■ CB IEC60950-1 (GS1900-8HP/10HP/16/24E/24) • RoHS compliant

Logistics data	
Harmonized System (HS) code	85176990

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-NOV-2024. Prints or copies of Information are only valid on the printed Publication date