ZYXEL

Zyxel GS1900-8HP v3 PoE Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand : Zyxel **Product code:** GS1900-8HP-GB0103F

Product name: GS1900-8HP v3 PoE

 $8~ports,\,10/100/1000Base-T$ PoE, MAC8K, IEEE 802.1D STP / 802.1w RSTP / 802.1s MSTP, L2 Multicast, PoE, GB

Zyxel GS1900-8HP v3 PoE. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE.... Power connector: DC-in jack. Power over Ethernet (PoE)






Management features		Multicast features	
Switch type *	Managed	Multicast support	✓
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Product colour	Black
Web-based management	√	Reset button	1
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	8	Mean time between failures (MTBF)	533086 h
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Power connector	DC-in jack	Power source *	AC/DC 100 - 240 V
Network		AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3at, IEEE 802.3at, IEEE 802.3x	Power consumption (typical)	90 W
		Power over Ethernet (PoE)	
		` '	,
		Power over Ethernet (PoE) * Power over Ethernet (PoE) ports	✓
Full duplex	1	quantity	8
Flow control support	√	Total Power over Ethernet (PoE)	70 W
Broadcast storm control	V	budget	
Rate limiting Auto MDI/MDI-X	4	Operational conditions	
VLAN support	,	Operating relative humidity (H-H)	10 - 90%
Data transmission	•	Weight & dimensions	
	16 Chirle	Width	250 mm
Switching capacity * MAC address table *	16 Gbit/s 8000 entries	Depth	104 mm
Number of gueues	8	Height	27 mm
Jumbo frames support	√	Weight	710 g
Jumbo frames	9216	Certificates	
Security		Certification	CE, FCC, C-Tick, RoHS
DHCP features	DHCP client	Logistics data	
IGMP snooping	✓	Harmonized System (HS) code	85176990
Security algorithms	802.1x RADIUS	•	

_						
5	е	c	u	rı	t١	,

MAC address filtering



4718937621286

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.