



120GB, 240GB, 480GB*

SanDisk® SSD PLUS

Step up to SSD speeds

Performance

- Up to 20X faster than a typical hard disk drive¹
- Boosts burst write performance, making it ideal for typical PC workloads
- Faster boot-up, shutdown, application load and response¹

Proven Reliability

- Shock resistant for proven durability²—even if you drop your computer
- SanDisk SSD Dashboard monitors drive status and software updates³
- Generous battery life

Inject new life into your laptop or desktop PC with a durable solid state drive from SanDisk. You'll experience quicker boot-up and shutdown, quicker application response and data transfer speeds than with a typical hard disk drive¹, at just a fraction of the cost of a new computer. SLC caching boosts burst write performance, making it ideal for typical PC workloads such as web browsing, email, casual gaming, office productivity, and audio/video entertainment. Plus a solid state drive doesn't overheat, make noise or burn through battery. SanDisk® SSDs are resistant to shock, vibration and temperature extremes², so your SSD keeps working, no matter where or how hard you use your computer.

SanDisk®

SanDisk® SSD PLUS Specifications

Available capacities:	120GB, 240GB, 480GB*
Dimensions:	2.75 x 3.96 x 0.28 in. (69.95 x 100.50 x 7.00 mm)
Interface:	SATA Revision 3.0 (6 Gbit/s)
Operating temperature:	0°C to 70°C
Shock:	Resistant up to 1,500 G @ 0.5m/sec
Vibration (Operating/Non operating):	5 gRMS, 10 – 2000 Hz / 4.9 gRMS, 7 – 800 Hz
Warranty:	3-year limited warranty (U.S.); 3-year warranty (ROW)

SanDisk® SSD PLUS	120GB	240GB	480GB
Performance			
Sequential Read (up to)	530MB/s**	530MB/s	535MB/s
Sequential Write (up to)	400MB/s	440MB/s	445MB/s

SKU	Part Number	UPC	MC UPC
SDSSDA-120G-G26	80-56-15592-120G	619659146689	40619659146687
SDSSDA-240G-G26	80-56-15592-240G	619659146726	40619659146724
SDSSDA-480G-G26	80-56-15592-480G	619659146757	40619659146755
SDSSDA-120G-Q25	80-56-15596-120G	619659125363	40619659125361
SDSSDA-240G-Q25	80-56-15596-240G	619659125400	40619659125408
SDSSDA-480G-Q25	80-56-15596-480G	619659141493	40619659141491
SDSSDA-120G-Z26	80-56-15598-120G	619659125370	40619659125378
SDSSDA-240G-Z26	80-56-15598-240G	619659125417	40619659125415
SDSSDA-480G-Z26	80-56-15598-480G	619659141509	40619659141507

For more information, please visit
www.sandisk.com

SanDisk®

At SanDisk, we're expanding the possibilities of data storage. For more than 25 years, SanDisk's ideas have helped transform the industry, delivering next generation storage solutions for consumers and businesses around the globe.

SanDisk Corporation, Corporate Headquarters
951 SanDisk Drive | Milpitas | CA 95035 | USA

SanDisk International
The Concourse Building | Airside Business Park
Swords | County Dublin | Ireland

* 1GB = 1,000,000,000 bytes. Actual user storage less.

** Based on internal testing; performance may vary depending upon drive capacity, host device, OS and application. 1MB = 1,000,000 bytes.

¹ As compared to 7200 RPM SATA 2.5" hard drive. Based on published specifications and internal benchmarking tests using PCMark Vantage scores.

² Shock resistant (up to 1500G) and vibration resistant (5gRMS, 10-2000 HZ/4.9 gRMS, 7-800 HZ), temperature (from 0°C to 70°).

³ Download required from <http://www.sandisk.com/ssdswap/download>. Limit one time use per system.