

AXIS T94S01L Recessed Mount

Swift and effortless ceiling installation

AXIS T94S01L Recessed Mount enables sleek, elegant and discreet recessed ceiling installations of indoor Axis fixed dome cameras. It features a patent-pending single-screw ceiling attachment design, which makes the installation quick and easy without having to remove the ceiling tile. Axis fixed dome camera attached to the recessed mount is embedded into the ceiling, revealing only the camera dome and the low-profile cover ring.

- > [Cost-effective mount for Axis fixed dome cameras](#)
- > [Recessed ceiling installation made quick and easy](#)
- > [Enables sleek and discreet video surveillance](#)



AXIS T94S01L Recessed Mount

General	
Supported products	AXIS P32-V/-LV Mk II Network Camera Series
Casing	Material: plastic Color: white NCS S 1002-B
Sustainability	PVC free
Mounting	Recessed in drop ceilings
Environment	Indoor
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	Safety IEC/EN/UL 60950-1 Environment IEC 60068-2-2, IEC 60068-2-6 (vibration), IEC 60068-2-27 (shock), IEC/EN 62262 IK08, REACH, RoHS, WEEE
Dimensions	Outer dimensions 252 x 179 x 146 mm (9.9 x 7.0 x 5.7 in)

Dimensions when recess-mounted with a camera ∅ 179 mm (7.0 in), height 65 mm (2.6 in)

Weight	300 g (0.7 lb)
Maximum load	600 g (1.3 lb)
Cable routing	Top: cable hole
Included accessories	Installation Guide
Optional accessories	AXIS Safety Wire 3 m For more accessories, see www.axis.com
Warranty	Axis 3-year warranty, see www.axis.com/warranty

Environmental responsibility:

www.axis.com/environmental-responsibility