

MSA Uncoded SFP Module - 1000BASE-SX - 1GbE Multi Mode Fiber (MMF) Optic Transceiver - 1GE Gigabit Ethernet SFP - LC 550m - 850nm - DDM

Product ID: SFP1000SXST



• Wavelength: 850nm

• Maximum Data Transfer Rate: 1.25 Gbps

• Type: Multi Mode Fiber

• Connection Type: LC Connector

• Maximum Transfer Distance: 550 m (1804 ft)

• Power Consumption: Less than 1 Watt

• DDM: Yes

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP Cables, providing the convenience and reliability you need to ensure dependable network performance.

## **Certifications, Reports and Compatibility**

















## **Applications**

- Replace defective or damaged SFP modules
- Expand your network to remote segments

## **Features**

- 100% MSA UNCODED SFP TRANSCEIVER: Designed, programmed and tested to work with compatible MSA Compliant switches and routers to deliver reliable 1GbE connectivity
- TECHNICAL SPECS: 1000BASE-SX 1Gbps Multi Mode (MMF) LC Connector 850nm Digital Diagnostic Monitoring (DDM) Distances up to 550m (1804ft)
- TESTED FOR COMPATIBILITY: Hot-swappable in MSA Compliant routers and switches; DDM support reports the transceiver's status to most SNMP network management tools.
- WORKS WITH MSA COMPLIANT SWITCHES: Works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules
- THE IT PRO'S CHOICE: Designed and built for IT Professionals, this SFP module is backed for life (lifetime of module, not network switch), including free lifetime 24/5 multi-lingual technical assistance

Hardware

Lifetime Warranty

Compatible Brand MSA Compliant

**WDM** No

**Industry Standards** IEEE 802.3z 1000BASE-SX

**Performance** 

Maximum Data Transfer

Rate

1.25 Gbps

Max Transfer Distance 550 m (1804 ft)

Type Multi Mode

Wavelength 850nm

Fiber Operating Mode **Full-Duplex** 





DDM	Yes

Compatible Networks 1000 Mbps (1 Gbps)

Power Consumption (In

Watts)

Connector(s)

Local Unit Connectors 1 - Fiber Optic LC Duplex

< 1 W

**Environmental** 

Operating Temperature 0C to 70C (32F to 158F)

Storage Temperature -40C to 85C (-40F to 185F)

Humidity 5~95% RH

Physical Characteristics

Product Length 2.3 in [58.4 mm]

Product Width 0.5 in [13.9 mm]

Product Height 0.5 in [1.3 cm]

Weight of Product 0.8 oz [23.0 g]

Packaging Information

Package Length 4.7 in [12.0 cm]

Package Width 3.5 in [90.0 mm]

Package Height 1.2 in [30.0 mm]

Shipping (Package)

Weight

1.9 oz [53.0 g]

What's in the Box

Included in Package 1 - SFP transceiver

<sup>\*</sup>Product appearance and specifications are subject to change without notice.